


## NA2XY 1x16 CL-2 RM 0.6/1kV



### Description

NA2XY is used for electricity supply in low voltage installation systems. It is well adapted to underground use in industrial applications with an additional mechanical protection. For fixed installations, in indoor areas (trays, ducts), in underground ducts or buried direct in ground, in dry or wet locations.

### Core Identification

1 core: Black  
 2 core: Blue, Brown  
 3 core: Green/Yellow, Blue, Brown  
 3 core: Brown, Black, Grey  
 4 core: Green/Yellow, Brown, Black, Grey  
 4 core: Brown, Black, Grey, Blue  
 5 core: Green/Yellow, Blue, Brown, Black, Grey  
 6 core and above: Black with White numbers, Green/Yellow

### Standards

IEC 60332-1-2  
 IEC 60502-1  
 VDE 0276-603  
 IEC 60228

### Construction

**Conductor:** Class 2 stranded aluminum  
**Insulation:** XLPE  
**Sheath:** PVC

## Specifications

Cable Type	Single Core
Cable Overall Diameter	9.7
Cable Weight	113
Conductor Material	Aluminium
Number of Conductors	1
Conductor Cross-Section	16
Conductor Weight	40.2
Conductor Class	CL-2
Conductor Type	RM
Insulation Material	XLPE
Filling Material	PE
Outersheath Material	PVC
Rated Voltage (U <sub>0</sub> /U)	0.6/1
Max. Permissible Operating Temperature	-30 >< +90
Working Temperature	-40 >< +90
Short Circuit Temperature	250
Minimum Bending Radius (Installing)	15xD
Minimum Bending Radius (Operating)	13xD
Packing	Wooden Drum, Plywood Drum, Coil, Rolls
Delivery Lengths	To be confirmed by offer
Delivery Length Tolerance	±5%