



## TYNKOLIT-T 330

Primer for mineral, acrylic and mosaic plasters

**Areas of application:** The primer is intended for final groundwork preparation before the application of mineral, acrylic and mosaic plasters. Limits and levels absorbency, reinforces the groundwork, facilitates painting and increases paint adhesion to the groundwork.

- Properties:**
- Waterproof
  - Freezeproof
  - Vapor-permeable
  - Increases groundwork adhesion
  - Facilitates plaster application
  - Regulates groundwork absorbency

**Application procedure:**



Technical data		
Item No.	314516	314517
Packaging type		
Quantity per unit	7 kg	20 kg
Unit per pallet	80 Stk./Pal.	33 Stk./Pal.
Colour	white	
Consumption	approx. 0.25 kg/m <sup>2</sup>	

**More technical Details:** **Drying time:** about 4 hours under optimal conditions  
**Possibility of further works:** after 24 hours

- Material base:**
- Water dispersion of acrylic polymer
  - Refining agents
  - Quartz aggregate
  - Titanium white
  - Water

**Surface:** Depending on the absorbency and type of groundwork, prime with GRUNTOLIT-W 301 or GRUNTOLIT-SG 302  
 Eradicate all expressions of biological aggression on the groundwork using the SEPTOBUD 1008 solution.  
 Proceed to the execution of works after the dust settlement and groundwork drying period.  
 Repair cracked and scratched surfaces with the 428 mortar. Mortar in the repair sites must be dried and properly set.  
 Cover all surfaces not intended for priming before the primer is applied.

**Types of substrate:**  
**Reinforcing layer in the thermal insulation system:** without additional priming  
**Cement-lime plaster:** With high absorbency, prime with GRUNTOLIT-W 301  
**Cement plaster:** without additional priming  
**Gipsputz:** Prime with GRUNTOLIT-W 301 or EXPERT 6  
**Wallboards:** Prime with GRUNTOLIT-SG 302 or EXPERT 5  
**Concrete:** without additional priming

**Preparation:** Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use.  
 It is recommended to use a plaster primer colored in the color of the plaster. This is particularly true for plaster with a scratched structure and intense colors.



## TYNKOLIT-T 330

Primer for mineral, acrylic and mosaic plasters

---

<b>Application procedure:</b>	Primer; apply with a roller, brush or using spray application The average drying time is 24 hours. Protect against frostbite, precipitation, excessively high temperatures and strong wind during application and drying.
<b>Application conditions:</b>	Apply at temperatures from +5°C to +25°C; these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.
<b>Instructions:</b>	When conducting works in adverse weather conditions, use special covers limiting the effects of external factors. Notice! The primer dye may slightly differ from the plaster dye, a plaster primer does not cover like paint does. Use the entire set of products in the thermal insulation system.
<b>Storage:</b>	The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5°C to +25°C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5°. It is not subject to ADR provisions.

---



---

<b>General information:</b>	This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.
-----------------------------	---

---