

HOW TO SELECT A TYRE

Tyre size and maximum speed of the vehicle.
The maximum load capacity per axle (Load index).
Your style driving and road condition.

MOUNTING & DISMOUNTING

Only get trained people mounting and dismounting your tyres.

TYRE PRESSURE

For safe drive, it is extremely important to drive with the right pressure.

CHECK FOLLOWING ITEMS IN REGULAR WAY

Tread pattern
Unusual wear, tread groove separation, bulges.. etc.

Sidewall
Impact, Bulges, Ozone cracking, vehicle contact damage etc.

Pressure
The inflated pressure will be changed during long driving and changed circumstances temperature.

Printed on June 2018



2018 Products
Manual

www.sd-international.cn



DISTRIBUTED BY

TOLEDO
PREMIUM TRUCK RADIAL TYRES

DRIVING THE FUTURE



Brand Introduction

- Design engineering from Europe, using the most up to date design technology available.
- All types of certificates are available , like ECE, GCC, Soncap,NOM and Smartway etc.
- Exclusive Distribution available to offer.
- Direct factory programme , ensuring continuity of supply and competitive price.
- Full marketing support available.

Size	PR	LI	SI	Pattern	Standard Rim	O.D. (mm)	S.W. (mm)	NSD (mm)	Max Load (kg)		Pressure (kPa)
									S	D	
10.00R20	18PR	149/146	K	DR308	7.5	1054	278	16	3250	3000	930
10.00R20	18PR	149/146	K	DR166	7.5	1054	278	14.5	3250	3000	930
11.00R20	18PR	152/149	K	DR308	8.0	1085	293	16.5	3550	3250	930
11R22.5	16PR	146/143	M	DR116	8.25	1054	279	14.5	3000	2725	830
11R22.5	16PR	146/143	L	DR518	8.25	1065	279	20.5	3000	2725	830
11R22.5	14PR	144/142	L	DR200	8.25	1065	279	20.5	2800	2650	720
11R22.5	16PR	146/143	M	DR176	8.25	1054	279	14.5	3000	2725	830
11R22.5	16PR	146/143	M	DR166	8.25	1054	279	14.5	3000	2725	830
11R22.5	16PR	146/143	L	DR308	8.25	1054	279	14.5	3000	2725	830
11R22.5	16PR	146/143	L	DR528	8.25	1065	279	22	3000	2725	830
11R22.5	16PR	148/145	K	DR528	8.25	1065	279	22	3250	2900	830
11R24.5	14PR	146/143	M	DR200	8.25	1089	268	9.5	3000	2725	720
11R24.5	16PR	149/146	M	DR116	8.25	1099	268	14.5	3250	3000	830
11R24.5	16PR	149/146	L	DR518	8.25	1111	268	20.5	3250	3000	830
11R24.5	16PR	149/146	K	DR308	8.25	1104	279	14.5	3250	3000	830
12.00R20	18PR	154/151	K	DR308	8.5	1125	315	17	3750	3450	830
12R22.5	18PR	152/149	M	DR176	9.00	1085	300	14.5	3550	3250	930
12R22.5	18PR	152/149	L	DR322	9.00	1085	300	16.5	3550	3250	930
12R22.5	18PR	152/149	L	DR526	9.00	1096	300	19.5	3550	3250	930
12R22.5	18PR	152/149	L	DR308	9.00	1085	300	16	3550	3250	930
12R22.5	18PR	152/149	L	DR538	9.00	1096	300	20	3550	3250	930
13R22.5	18PR	154/151	K	DR308	9.75	1124	320	17	3750	3450	830
13R22.5	18PR	154/151	L	DR176	9.75	1124	320	17	3750	3450	830
295/75R22.5	14PR	144/141	M	DR116	9.00	1014	298	14.5	2800	2575	760
295/75R22.5	16PR	146/143	M	DR116	9.00	1014	298	14.5	3000	2725	830
295/75R22.5	14PR	144/141	L	DR518	9.00	1020	298	20.5	2800	2575	760
295/75R22.5	16PR	146/143	L	DR518	9.00	1020	298	20.5	3000	2725	830
295/75R22.5	14PR	144/141	M	DR200	9.00	1014	298	9.5	2800	2575	760
295/75R22.5	16PR	146/143	L	DR520	9.00	1020	298	20.5	3000	2725	830
295/75R22.5	14PR	144/141	L	DR520	9.00	1020	298	20.5	2800	2575	760
295/80R22.5	18PR	152/149	L	DR188	9.00	1044	298	17.5	3550	3250	900
295/80R22.5	18PR	152/149	M	DR176	9.00	1044	298	14.5	3550	3250	900
295/80R22.5	18PR	152/149	J	DR539	9.00	1050	298	19.5	3550	3250	900
315/80R22.5	20PR	156/153	L	DR188	9.00	1076	312	14.5	4000	3650	900
315/80R22.5	20PR	156/153	M	DR176	9.00	1076	312	14.5	4000	3650	900
315/80R22.5	20PR	156/153	L	DR535	9.00	1082	312	21.5	4000	3650	900
315/80R22.5	20PR	156/153	K	DR308	9.00	1076	312	17	4000	3650	900
315/80R22.5	20PR	156/153	K	DR539	9.00	1082	312	22.5	4000	3650	900
385/65R22.5	20PR	160	K	DR303	11.75	1072	389	15.5	4500		900
385/65R22.5	20PR	160	K	DR310	11.75	1072	389	16	4500		900



DR116



DR166



DR176



DR188



DR200



DR303



DR308



DR310



DR322



DR518



DR520



DR526



DR528



DR535



DR538



DR539