

Specificații tehnice (F4.1)

[Acest tabel va fi completat de către ofertant în coloanele 3, 4, 5, 7, iar de către autoritatea contractantă – în coloanele 1, 2, 6, 8]

Numărul licitației:	MD – 1541426674629	Data: „ 22 ” noembrie 2018	Alternativa nr.:
Denumirea licitației:	Sistemului intercom pentru studioul 1 TV	Lot: <u>unic</u>	Pagina: 1 din 3

Cod CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
Lot unic: Sistem intercom pentru studioul 1 TV							
32300000-6	DIRECTOR'S PANEL (8 buttons)	DP-8VM	Moldova	Radiofar & Co SRL	<ul style="list-style-type: none"> - DC POWER +12 - +48 V - include - Ethernet RJ45 - connector for connection to an Ethernet network and a passive PoE - LINE INPUT - line input audio channel. Can be used to connect to external audio signal. - LINE OUT line-out audio channel. Can be used to connect to the input of the external speaker system - Speaker - Applications: Television, broadcast 	<p>Director Panel for 8 subscribers , Microphone – Gooseneck type (XLR 3 PIN) Front Panel Headset – XLR 5PIN, two minijack 3.5mm –microphone and phone, RJ-45 for for connection to local net (Hub, transceiver AP, beltpacks, - LINE INPUT - line input audio channel. Can be used to connect to external audio signal. - LINE OUT - line-out audio channel. Can be used to connect to the input of the external speaker system Power – 12...48 VDC - Speaker - Applications: Television, broadcast</p>	According to Declaration of Conformity
32300000-6	DIRECTOR'S PANEL (16 buttons)	DP-16VM	Moldova	Radiofar & Co SRL	<ul style="list-style-type: none"> - DC POWER +12 - +48 V - include - Ethernet RJ45 - connector for connection to an Ethernet network and a passive PoE - LINE INPUT - line input audio channel. Can be used to connect to external audio signal. - LINE OUT - line-out audio channel. Can be used to connect to the input of the external speaker system - Speaker - Applications: Television, broadcast 	<p>Director Panel for 8 subscribers , Microphone – Gooseneck type (XLR 3 PIN) Front Panel Headset – XLR 5PIN, two minijack 3.5mm –microphone and phone, RJ-45 for for connection to local net (Hub, transceiver AP, beltpacks, - LINE INPUT - line input audio channel. Can be used to connect to external audio signal. - LINE OUT - line-out audio channel. Can be used to connect to the input of the external speaker system</p>	According to Declaration of Conformity

						Power – 12...48 VDC - Speaker - Applications: Television, broadcast	
32300000-6	The transceiver for wireless beltack	AP-VM	Moldova	Radiofar & Co SRL	The access point provides simultaneous connection of up to 8 beltacks - The frequency range: 868MHz, 915MHz, 2.4GHz - DC POWER +12 - +48 V - include - Ethernet RJ45 - connector for connection to an Ethernet network - Range: up to 1 km; typical 150-300 meters - Applications: Television, broadcast	The transceiver provides simultaneous connection of up to 8 wireless beltacks and up to eight devices Tally. Front panel – 8 LED -status wireless beltacks, 8 LED – status Tally Rear panel – RJ-45, DB9 (for signal Tally) , two antenna ports (SMA) Power – 12...48 VDC Diversity reception	According to Declaration of Conformity
32300000-6	Wireless communication device beltack	BPW-V	Moldova	Radiofar & Co SRL	The device is powered by a built-in rechargeable battery Li-polimer - The frequency range: 868MHz, 915MHz, 2.4GHz - Connector minijack 3.5 for microphone of headset - Connector minijack 3.5 for phone of headset - Rechargeable batteries - Charger for battery - Applications: Television, broadcast	Wireless communications devices beltack is intended for communication operator with the director. The front panel: 1. MIC - microphone mini-jack 2. Phone – Phone output mini-jack 3. Tally - Tally signal output terminal 5. Power Toggle 6. Call-button Rear panel- mini USB for charge battery. Diversity reception Built-in antennas - Charger for battery - Applications: Television, broadcast	According to Declaration of Conformity
32300000-6	Wired communication device beltack	BP-V	Moldova	Radiofar & Co SRL	- DC POWER +12 - +48 V - include - Ethernet RJ45 - connector for connection to an Ethernet network and a passive PoE - Connector minijack 3.5 for microphone of headset - Connector minijack 3.5 for phone of headset - Applications: Television, broadcast	Wired communications devices beltack BP is intended for communication operator with the director The front panel: 1. MIC - microphone mini-jack 2. Phone – Phone output mini-jack 4. 3. Tally - Tally signal output terminal 5. Power Toggle 5. Call-button Rear panel - RJ-45 for Ethernet connection and PoE - Applications: Television, broadcast	According to Declaration of Conformity
32300000-6	POE Switcher x8	DGS-1210-10MP	Taiwan	D-LINK	-8-port LAN POE 1000Mbps + 2 Gigabit SFP non combo uplinks -Power Over Ethernet (PoE) -PoE Budget min. 100W -Include 2 x SFP 1Gb Transceiver (TX/RX), Connector Type: LC duplex, Single Mode Fiber ,minimum transfer distance 1km -24 months warranty	-8-port LAN POE 1000Mbps + 2 Gigabit SFP non combo uplinks -Power Over Ethernet (PoE) -PoE Budget min. 100W -Include 2 x SFP 1Gb Transceiver (TX/RX), Connector Type: LC duplex, Single Mode Fiber ,minimum transfer distance 1km -24 months warranty	ISO9001
32300000-6	POE Switcher x16	DGS-1210-28P/ME	Taiwan	D-LINK	-min. 16-port LAN POE 1000Mbps + 2 Gigabit SFP non combo uplinks -Power Over Ethernet (PoE) -PoE Budget min. 170W -Include 2 x SFP 1Gb Transceiver (TX/RX), Connector Type: LC duplex, Single Mode Fiber ,minimum transfer distance 1km -24 months warranty	-min. 16-port LAN POE 1000Mbps + 2 Gigabit SFP non combo uplinks -Power Over Ethernet (PoE) -PoE Budget min. 170W -Include 2 x SFP 1Gb Transceiver (TX/RX), Connector Type: LC duplex, Single Mode Fiber ,minimum transfer distance 1km -24 months warranty	ISO9001

32300000-6	Headset with Microfon	HP-1	Taiwan	Datavideo Technologies Co Ltd.	Single Sided Headset Type-Dynamic Driver Size-50 mm Impedance-min. 24 Ohms Maximum Input Power-min.100 mW Connectors-2 x 3.5 mm Padded Headband & Earcup Microphone Type - Electret condenser Polar Pattern-Unidirectional Impedance-150 Ohms Operating Voltage 1 to 10 VDC -24 months warranty	Single Sided Headset Type-Dynamic Driver Size-50 mm Impedance-min. 24 Ohms Maximum Input Power-min.100 mW Connector- 1 minijack 3.5 mm Padded Headband & Earcup Microphone Type - Electret condenser Polar Pattern-Unidirectional Impedance-2.2kOhms Operating Voltage 1 to 10 VDC -24 months warranty	ISO9001
32300000-6	Acoustic Tube Earpiece Headset:	VT610TC125	Elvetia	Voice Technologies	- Sugical tubing with UV protection - Modular and replaceable clip parts - Made to wear on left or right ear - 3.5mm jack connector	- Sugical tubing with UV protection - Modular and replaceable clip parts - Made to wear on left or right ear - 3.5mm jack connector	ISO9001
32300000-6	Telephone Hybrid (rack mounted)	MACROTEL X2	Italy	AXEL Technology	-Digital Telephone hybrid based on DSP audio process -2 wireless lines managed via GSM Quad Band -Audio controls: AGC Stage, Attenuator, Echo canceller -Integrated DTMF dialer via software with auto-answer and disconnection -Separate send and receive over balanced XLR with Mic/Line software selection -2 pieces GSM Module: Quad-Band GSM 850/900/1800/1900 Mhz -2 lines RJ11 connectors to connect the PSTN telephone line to the telephone Hybrid (LINE socket) and to connect a telephone device in parallel to the hybrid -Dual Line Hybrid functions as 2 separate hybrids or conference system -2 Sim cards support -24 months warranty	-Digital Telephone hybrid based on DSP audio process -2 wireless lines managed via GSM Quad Band -Audio controls: AGC Stage, Attenuator, Echo canceller -Integrated DTMF dialer via software with auto-answer and disconnection -Separate send and receive over balanced XLR with Mic/Line software selection -2 pieces GSM Module: Quad-Band GSM 850/900/1800/1900 Mhz. -2 lines RJ11 connectors to connect the PSTN telephone line to the telephone Hybrid (LINE socket) and to connect a telephone device in parallel to the hybrid -Dual Line Hybrid functions as 2 separate hybrids or conference system -2 Sim cards support -24 months warranty	ISO9001
32300000-6	Instalare, suport		Moldova	Radiofar & Co SRL	Lucrările de montare, precum și operațiunile de instalare, ajustare, testare; Suport tehnic a sistemului - 1 an; Garanția hardware - 1 an; Sistemul va fi predat la cheie împreună cu softul de dirijare a sistemului intercom.	Lucrările de montare, precum și operațiunile de instalare, ajustare, testare; Suport tehnic a sistemului - 1 an; Garanția hardware - 1 an; Sistemul va fi predat la cheie împreună cu softul de dirijare a sistemului intercom	
	TOTAL						

Semnat:  Numele, Prenumele: Brinzari Serghei În calitate de: director

Ofertantul: Radiofar & Co SRL Adresa: Chisinau, str. Alba Iulia 75/6

