

Laboratory Refrigerator



656L



1500L

Technical Parameters

Model		BPR-5V650	BPR-5V1500
External Size(W*D*H) mm		1220*642*1885	1800*748*1965
Capacity		656L	1500L
Temp. Range		2~8℃	
Temp. Accuracy		0.1℃	
Control System		Microprocessor Control & Large Screen LED Display	
Alarm		Audio and visual alarm for: High and low temperature, Thermostat fault, power failure(only for BPR-5V650), Door ajar	
Refrigeration Type		Forced air refrigeration system	
Refrigerant		R600a, CFC Free	R134a, CFC Free
Condenser&Evaporator		High efficiency air-cooled condenser, made of copper	
Defrost		Auto defrost	
Construction	Structure	Unibody design & Mono-assembly foaming (rigid polyurethane insulation material)	
	Internal Material	Cold-rolled steel coated with anti-bacteria powder	SS304
	External Material	Cold-rolled steel coated with anti-bacteria powder	SS304
Shelves		Adjustable shelves made of high quality steel wire	
		10 pcs	12 pcs
Consumption		310W	830W
Power Supply		AC110/220V±10%, 50/60Hz	AC110/220V±10%, 50/60Hz
Standard Accessory		LED lamp, Shelves, Door keys, Testing hole, Battery	
Package Size(W*D*H) mm		1290*695*1940	1940*880*2035
Gross Weight		188kg	190kg

-25℃ Freezer



BDF-25H305

Features

- 1.Digital temperature display.
- 2.The safety lock can prevent random opening.
- 3.Baskets made of steel wire are convenient to store articles.
- 4.Round corner design of doors and the body provides luxury and elegance.
- 5.Delayed start and safe stop interval between restart and being terminated, ensure reliable running.

Technical Parameters

Model		BDF-25H305
External Size(W*D*H) mm		1000*520*665
Capacity		305L
Temp. Range		-10℃~-25℃
Temp. Accuracy		0.1℃
Control System		Microprocessor control&LED display
Alarm		High or low temperature alarm, Temperature sensor failure alarm, over range alarm.
Refrigeration Type		Direct refrigeration
Refrigerant		R600a, CFC free
Condenser&Evaporator		Internal-mounted condenser and coil type evaporator
Construction	Structure	Whole foaming, freon cyclopentane/isopentane high density polyurethane foam
	Internal Material	Aluminum
	External Material	Cold-rolled steel coated with anti-bacteria powder
Basket		none
Consumption		106W
Power Supply		AC220V±10%,50HZ
Package Size(W*D*H)mm		1223*777*1005
Gross Weight		97kg