

MAXIMUM TRANSMAX 80W90 GL-5
Multigrade Automotive Gear Oil**Description and Application**

- **MAXIMUM TRANSMAX 80W90 GL-5** multigrade automotive gear oil is formulated with a special selection of high quality solvent refined and hydrotreated base stocks and ashless, and sulfur phosphorus type additive package.
- **MAXIMUM TRANSMAX 80W90 GL-5** gear oil is developed to lubricate all types of hypoid gear drives in automotive vehicles and industrial applications, operating at high loads and sliding velocities. Product can also be used in manual transmissions of all commercial vehicles and off-highway construction equipment and machines where an API GL-5 performance level lubricants are specified.

Benefits

- Very good protection for all gear drive components
- Very good low temperature properties for easy starts and good low temperature performance
- Very good seal compatibility

Specification

SAE 80W90	
API	GL-5
MB	235.0
MAN	342 Type M-1

MAXIMUM TRANSMAX 80W90 GL-5
Multigrade Automotive Gear Oil**Typical physical and chemical characteristics**

Parameter	Test Method	Typical Value
Density at 20 °C, kg/m ³	ASTM D 4052	891.0
Kinematic viscosity at 100 °C, mm ² /s	ASTM D 445	14.7
Viscosity index	ASTM D 2270	99
Flash point (open cup), °C	ASTM D 92	210
Pour point, °C	ASTM D 97	-30

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by reasonable production tolerances. The right to make modifications is reserved.

Health, safety and product handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

Packing options: