



LUKOIL
OIL COMPANY

LUKOIL LUBRICANTS EAST EUROPE

Romania, 100410 Ploiesti, Str. Mihai Bravu, Nr. 235, Jud. Prahova; Reg. Com. J29/1451/08.10.2015; CUI 19737772; IBAN RO70INGB0001008174598910; ING Bank

LABORATOR LUBRIFIANTII / LUBRICANTS LABORATORY

Ploiesti, Str. Mihai Bravu, Nr. 235, Jud. Prahova; Tel: +40244 504 358; Fax: +40244 504 679;
Laborator@lukoil-lubricants.ro

acreditat pentru
ÎNCERCARE



SR EN ISO/CEI 17025:2005
CERTIFICAT DE ACREDITARE
LI 1200

RAPORT DE INCERCARE (TEST REPORT)

Nr.: 484

Data: 24.04.2020

Client (Customer)		Sectia Amestec/Blending Sector		LUKOIL LUBRICANTS EAST EUROPE		
Produs (Product)		Ulei pentru transmisii LUKOIL TRANSMISSION UNI 80W-90 <i>Transmission oil</i> LUKOIL TRANSMISSION UNI 80W-90				
Document normativ (Normative doc)		ST-10,ed.3/2020				
Numar Comanda (Order number)		428				
Cod proba (Cod sample) / Lot(Batch)		1342 / Lot/Batch 1				
Proba prelevata de (Sampling by)		Client (By customer)				
Data primire proba (Receive date)		23.04.2020				
Nr. crt. No	Caracteristici (Characteristics)	U.M. (U.M.)	Valoare prevazuta (Standard limits)	Valoare determinata (Obtained value)	Metoda de incercare (Test Method)	Incertitudine (Uncertainty) **
1	Densitate la 15°C / <i>Density at 15°C</i>	g/cm ³	se raporteaza/ report	0,8965	ASTM D 7042-16e3	
2	Densitate la 20°C / <i>Density at 20°C</i>			0,8935		
3	Viscozitatea cinematica la 100°C <i>Kinematic viscosity at 100°C</i>	mm ² /s	13,5+18,5	15,68	ASTM D 7042-10(16)	
4	Viscozitatea cinematica la 40°C <i>Kinematic viscosity at 40°C</i>	mm ² /s	se raporteaza report	153,4	ASTM D 7042-16e3	
5	Indice de viscozitate <i>Viscosity index</i>	-	min 95	103	ASTM D 7042-16e3 ASTM D 2270-10(16) SR ISO 2909-12	
6	# Punct de inflamare in vas deschis <i>Flash point, COC</i>	°C	min 200	204	SR EN ISO 2592-18	
7	Punct de curgere <i>Pour point</i>	°C	max. -30	-30	ASTM D 92-18	
8	*Caracteristici de spumare: tendinta-stabilitate <i>Foaming characteristics: tendency-stability</i> - la 24°C / <i>at 24°C</i> - la 93,5°C / <i>at 93,5°C</i> - la 24°C, dupa 93,5°C / <i>at 24°C, after test at 93,5°C</i>	ml ml ml	max 50-0 50-0 50-0	10-0 10-0 10-0	SR 13552-12 ASTM D 97-17b ASTM D 892-18	
9	*Viscozitate dinamica Brookfield la - 26 °C / <i>Brookfield viscosity at -26°C</i>	cP	max 150000	105199	ASTM D 2983-19	
10	*Actiune coroziva pe lama de cupru 3 ore la 120°C <i>Copper strip corrosion at 120°C, 3h</i>	-	max. 1b	1b	SR EN ISO 2160-02 ASTM D 130-19	
	# *Proprietăți de extrema presiune / <i>Extreme pressure properties:</i> - sarcina de sudura / <i>weld load</i>	N	min 3687	3700	ASTM D 2783-14 STAS 8618-79	
	- Diametrul petei de uzura, (40kgf, 60 min)/ <i>mechanical wear spot, (40kgf, 60 min)</i>	mm	se raporteaza/report (la cerere/on request)	0,8		
Observatii (Remarks) :						

Observatii (Remarks):

* Garantate prin tehnologie (Guaranteed by technology).


** Incertitudinea raportata la solicitarea clientului (Uncertainty related to customer demand).

Incercare neacreditata (Test not accredited).

Verificat/Aprobat (Approved by):
Sef Laborator (Laboratory Chief)
Lungu Cristina

Intocmit: (Performed by):

Catargiu Daniela



DECLARATIE DE CONFORMITATE/CONFORMITY STATEMENT
Nr./No: 411 Data/Date. 24.04.2020

Noi,

Numele furnizorului: LUKOIL LUBRICANTS EAST EUROPE S.R.L

Adresa furnizorului: Str. Mihai Bravu, nr. 235, Ploiesti, jud. Prahova, Romania

Nr. de inregistrare la Registrul Comertului: J29/1451/0810.2015

Asiguram, garantam si declaram pe propria raspundere, prin prezentul document, ca produsul la care se refera aceasta declaratie este in conformitate cu cerintele specificate in documentul normativ specificat mai jos:

We,

Supplier Name: LUKOIL LUBRICANTS EAST EUROPE S.R.L

Supplier Address: Ploiesti, 235 Mihai Bravu Street, Prahova County, Romania

Registration number at the Commerce Registry: J29/1451/0810.2015

Assure, guarantee and declare on our own responsibility, in this document, that the product to which this declaration relates is in compliance with the requirements specified in the regulatory document specified below:

Denumire produs Product name	Lot, Rez./Lot, Tank Ambalaj/Pack	Titlul si numarul documentului normativ Title and no. of the normative document
LUKOIL TRANSMISSION UNI 80W-90	Lot 1	Ulei pentru transmisii Transmission oil ST-10, ed.3/2020

Certificat de Valabilitate <i>Certificate of Validity</i>	Perioada de valabilitate a produsului in depozitare este 5 ani de la data fabricatiei, in conditiile respectarii cerintelor de ambalare, depozitare, transport si manipulare. <i>Shelf life of product in storage is 5 years from date of manufacture, in compliance with the requirements for packaging, storage, transport and handling.</i>
---	---

Certificat de Conformitate RAR-OCP <i>Certificate of statement RAR-OCP</i>	Nr. 719, valabil pana la 23.03.2022 <i>No. 719, valid to 23.03.2022</i>
---	--

Raport de Incercare / Test report	484	Data / Date	24.04.2020
Client / Customer			
Data livrarii / Delivery date			
Factura/Aviz expeditie/Scrisoare trasura / Invoice/Delivery note/Car licence plate			
Cantitate / Quantity			
Mijloc de transport / Transport			

LUKOIL LUBRICANTS EAST EUROPE
PANAIT Luminita

