

DS-MH4172I(S) Series Desktop Dock Station



Introduction

Desktop body camera dock station provides a simplified way to access and back up law-enforcement data in Hikvision body camera.

Available Model

DS-MH4172I(S)

Key Feature

- Charge body cameras.
- Simultaneously collect data from up to 8 body cameras.
- Obtain date, serial No., police ID, and remaining data of the body camera.
- (Optional) clear data in body camera after data is successfully collected.
- Log management.
- Data overwriting.
- Lock collected files to prevent it from being overwritten.
- In case data collection is suddenly broken off, dock station will resume data collection from the breakpoint at next collection.
- Search collected data by time, by file type, by device No., etc.
- The body camera cradles on the dock station can be changed according to the body camera model (DS-MH2211/DS-MH2311 by default, also can work with DS-MCW407,DS-MCW405).
- Embedded WEB server.
- Can support AES256
- Support SSD





Specification

| | Model | | DS-MH4172I(S) |
|---------|------------------------|-----------------------------------|--|
| | Data Collection | Average Speed | 8 MB/s |
| | Appearance | Dimension | 400 × 300 × 110 mm (15.7 × 11.8 × 4.3") |
| | | Body Camera | Up to 8 body cameras |
| | | System indicator | 1 × power indicator, 1 × HDD indicator, 1 × network connection indicator, 1 × network transmission indicator, 8 × status indicator |
| | | Button | 1 × power switch, 1 × reset button |
| | Hardware | СРИ | Quad core CPU |
| | | Memory | 4 GB |
| | | HDD | 4×3.5 inch HDD. 2 TB to 6 TB for each HDD |
| | | Charging Duration for Body Camera | 4 to 5.5 hours |
| | | Operation System | Windows 10, 64-bit(trial version) |
| | | Power Consumption | 200 W |
| Distrib | Interface | USB Interface | 2 × USB 3.0 interface, 2 × USB 2.0 interface |
| | | HDMI Interface | 2 |
| | | Audio Input/output | 1/1 |
| | | VGA Interface | 1 |
| | | Network Interface | 2 × 10M/100M/1000M Ethernet interface |
| | | Loudspeaker | 2 |
| | General | Weight | Approx. 9 kg (19.8 lb) |
| | | Working Temperature | -10 °C to +55 °C (+14 °F to +131 °F) |
| | | Working Humidity | 10% to 90% |

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 [216]521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 [10] 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com