

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5.]

Numărul procedurii de achiziție _____ din _____
Obiectul achiziției: _____

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Produ-cătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Servicii de închiriere						
<u>Lotul 2: Servicii de organizare de evenimente culturale – Festivalul Internațional de Muzică Clasică, CRESCENDO</u>						
Sistem profesional de sonorizare line array fara Backline	FBT Muse 210 LA	Italia	FBT	Sistem de sonorizare profesional line array FBT 50 KW Echipament sunet (echivalent FBT Muse 210 LA / FBT Mitus 218 SA) SUB: Subwoofer cu banda aerisita, cu sistem bass-reflex. Echipat cu doua difuzoare de frecventa joasa cu diametrul de 18" si bobina de 3.9". Frecventa de raspuns de la 30Hz la 100Hz. Amplificator clasa D cu putere de 2000W RMS TOP: Woofer: 2 X 10" bobina de 2.5"	Echipament sunet FBT Muse 210 LA/ FBT mitus 218 SA SUB: Subwoofer cu banda aerisita, cu sistem bass-reflex. Echipat cu doua difuzoare de frecventa joasa cu diametrul de 18" si bobina de 3.9". Frecventa de raspuns de la 30Hz la 100Hz. Amplificator clasa D cu putere de 2000W RMS TOP: Woofer: 2 X 10" bobina de 2.5" Driver 2 x 1" cu bobina de 1.7" Putere RMS: 900 W Raspuns frecventa: 55Hz-20000Hz SPL Maxim: 139dB Dispersie driver: 90° x 10° Procesor de semnal digital Frequency response: 30Hz - 100Hz Low frequency woofer: 2x 18" B&C with 4" VCs High frequency driver: 1x 2" (2.5" VC) Maximum SPL cont/peak: 139/145dB Dispersion: Omnidirectional Input impedance: 22 kOhm	

				Driver 2 x 1" cu bobina de 1.7" Putere RMS: 900 W Raspuns frecventa: 55Hz-20000Hz SPL Maxim: 135 dB Dispersie driver: 90° x 10° Procesor de semnal digital	Crossover frequency: Preset Dependant Input connector: XLR with link out Net Dimension (WxHxD): 1000 x 549 x 730mm Net Weight: 90kg Transport Dimension (WxHxD): 1150 x 740 x 900mm Transport Weight: 102kg AC Power requirements: 1840VA Built-in amplifier LF/HF: 2000w Built-in amplifier peak LF/HF: 4000w	
Sistem profesional de lumini artistice pentru spectacole	Fender	SUA	Fender	Amplificator Chitara Fender Twin Amp Features: Type Vintage Reissue Series Tube Amp Output 85 watts into 4 ohms Ohms 4 ohms Speakers 1-15" Custom Eminence® 4 ohm Speaker with Ceramic Magnet, (Based on the Now Collectable JBL® D130F Speaker Used by Fender® in the '60s and '70s) Channels Dual Channels (Normal and Vibrato) Features Reverb Vibrato 2-Button Footswitch Tilt Back Legs Controls Normal Channel: Bright Switch, Volume, Treble, Middle, Bass Vibrato Channel: Bright Switch, Volume, Treble, Middle, Bass Reverb Vibrato: Speed, Intensity Covering Black Textured Vinyl with Silver Grille Cloth Weight 64 lbs. (34kg) Dimensions Height: 22" (55.9 cm) Width: 26.15" (66.4 cm) Depth: 10.5" (26.7 cm) Tube Complement 4 X 12AX7 2 X 12AT7 4 X 6L6 Solid State Rectifier Shipping Weight 70 lbs Cover Included Accessories 2-Button Footswitch for	Amplificator Chitara Fender Twin Amp Features: Type Vintage Reissue Series Tube Amp Output 85 watts into 4 ohms Ohms 4 ohms Speakers 1-15" Custom Eminence® 4 ohm Speaker with Ceramic Magnet, (Based on the Now Collectable JBL® D130F Speaker Used by Fender® in the '60s and '70s) Channels Dual Channels (Normal and Vibrato) Features Reverb Vibrato 2-Button Footswitch Tilt Back Legs Controls Normal Channel: Bright Switch, Volume, Treble, Middle, Bass Vibrato Channel: Bright Switch, Volume, Treble, Middle, Bass Reverb Vibrato: Speed, Intensity Covering Black Textured Vinyl with Silver Grille Cloth Weight 64 lbs. (34kg) Dimensions Height: 22" (55.9 cm) Width: 26.15" (66.4 cm) Depth: 10.5" (26.7 cm) Tube Complement 4 X 12AX7 2 X 12AT7 4 X 6L6 Solid State Rectifier Shipping Weight 70 lbs Cover Included Accessories 2-Button Footswitch for Reverb and Vibrato On/Off Footswitch Uses 2-Button Footswitch Accy	

				Reverb and Vibrato On/Off Footswitch Uses 2-Button Footswitch Accy		
2.3 Servicii de deservire tehnică				DTS Raptor beam opening 3.4° unique 8-facet prism 17 fixed gobos smooth filter and frost filter silent operation color wheel (17 filters) 150,000 lux @ 15 m +/- 24 Moving head/ beam/ spot/ wash Chauvet 140 SR/ DTS Raptor/ Chauvet 375Z/ Showtec Q4 Light output: 382.000 lux @ 5m Light source: Osaram Sirius hri 140w Zoom angle (degrees): beam – 3 to 11 degrees Spot – 7 to 21 Wash – 14 to 28 Colors 12+white Prism: 8-facet round, bidirectional rotation at variable speeds. Effects: pixel control, flower effect, virtual colour wheel, tungsten lamp effect, +/- 24 Par led Future light & Showtec 12x10w, 6 in 1 LWD (RGBWA+UV) 18x8w, RGBW Par (echivalent LED Par 64 Short Q4-18) – 30 buc 18 x 8 W RGBW LED Par 40° fixed beam angle Double bracket for easy floor positioning DMX and manual control in Auto run and Sound- controlled mode RGBW colour mixing, dimmer and strobe function	DTS Raptor beam opening 3.4° unique 8-facet prism 17 fixed gobos smooth filter and frost filter silent operation color wheel (17 filters) 150,000 lux @ 15 m +/- 24 Moving head/ beam/ spot/ wash Chauvet 140 SR/ DTS Raptor/ Chauvet 375Z/ Showtec Q4 Light output: 382.000 lux @ 5m Light source: Osaram Sirius hri 140w Zoom angle (degrees): beam – 3 to 11 degrees Spot – 7 to 21 Wash – 14 to 28 Colors 12+white Prism: 8-facet round, bidirectional rotation at variable speeds. Effects: pixel control, flower effect, virtual colour wheel, tungsten lamp effect, +/- 24 Par led Future light & Showtec 12x10w, 6 in 1 LWD (RGBWA+UV) 18x8w, RGBW Par (echivalent LED Par 64 Short Q4-18) – 30 buc 18 x 8 W RGBW LED Par 40° fixed beam angle Double bracket for easy floor positioning DMX and manual control in Auto run and Sound-controlled mode RGBW colour mixing, dimmer and strobe function +/- 12 Futurelight par led 12x10 Slim Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV Flat housing form requires minimal space when rigging Extremely compact housing in a beautiful design Second mounting bracket for safe standing installation Locking possibility at the brackets with large metal butterfly screws Functions: static colors, RGBAW+UV color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation Addressing and setting via Control Board with four operating buttons and LED display	

				+/- 12 Futurelight par led 12x10 Slim Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV Flat housing form requires minimal space when rigging Extremely compact housing in a beautiful design Second mounting bracket for safe standing installation Locking possibility at the brackets with large metal butterfly screws Functions: static colors, RGBAW+UV color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation Addressing and setting via Control Board with four operating buttons and LED display Switch-mode power supply for operation between 100 and 240 volts P-Con terminals for power linking up to 8 units 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color) Can be operated in 6; 10 CH mode The device is cooled by passive convection cooling Controlling by stand-alone; DMX; Sound to light via Microphone Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE	Switch-mode power supply for operation between 100 and 240 volts P-Con terminals for power linking up to 8 units 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color) Can be operated in 6; 10 CH mode The device is cooled by passive convection cooling Controlling by stand-alone; DMX; Sound to light via Microphone Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE Flicker-free Effect: Strobe effect; UV effect Moving Head Spot, Echivalent Clay Paky 1200 W – 4 buc Mașină de fum Hazer Lichid de fum Hazer Moving Head (echivalent Chauvet 140 SR) – 8 buc functie SPOT, BEAM, WASH doua roti cu gobos-uri controlabile independent zoom motorizat ce functioneaza in toate functiile(Spot, Beam sau Wash) Aimentare intrare/iesire PowerCON® pentru inseriere usoara optica superioara din sticla de foarte buna calitate pentru proiectii bine definite si culori stralucitoare compatibil si cu lampi Osram 132 W Afisaj full-color comptibil cu telecomanda de control IRC-6, functia "totem"(caracteristica unica Chauvet) compatibil cu geanta Chauvet CHS-50 VIP functionare DMX in: 13 sau 19 canale, conexiune XLR 3 pini Pan/Tilt: 540°/270° Pan/Tilt controlabil: 180°, 360°, 540° pan/90°, 180°, 270° tilt culori: 12 + white, split, scroll continuu la diferite viteze Sirius HRI 132 W lampa cu descarcare (6000 ore) Strobe Rate: 0-20 Hz putere luminoasa: (3° beam): 382000 lux la 5 m; (7° spot): 104700 lux la 5 m; (14° wash): 4680 lux la 5 m inseriere putere:6 unitati la 230 V alimentare: 240 VAC, 50/60 Hz putere si consum: 254 W, 1.3 A la 230 V, 50 Hz dimensiuni gobo: (rotating): 13.7 mm exterior, 11 mm imagine, 1 mm max grosime unghi de deschidere si zoom: (beam):	
--	--	--	--	--	--	--

				Flicker-free Effect: Strobe effect; UV effect Moving Head Spot, Echivalent Clay Paky 1200 W – 4 buc Mașină de fum Hazer Lichid de fum Hazer Moving Head (echivalent Chauvet 140 SR) – 8 buc functie SPOT, BEAM, WASH doua roti cu gobos-uri controlabile independent zoom motorizat ce functioneaza in toate functiile(Spot, Beam sau Wash) Aimentare intrare/iesire PowerCON® pentru inseriere usoara optica superioara din sticla de foarte buna calitate pentru proiectii bine definite si culori stralucitoare compatibil si cu lampi Osram 132 W Afisaj full-color comptibil cu telecomanda de control IRC-6, functia "totem"(caracteristica unica Chauvet) compatibil cu geanta Chauvet CHS-50 VIP functionare DMX in: 13 sau 19 canale, conexiune XLR 3 pini Pan/Tilt: 540°/270° Pan/Tilt controlabil: 180°, 360°, 540° pan/90°, 180°, 270° tilt culori: 12 + white, split, scroll continuu la diferite viteze Sirius HRI 132 W lampa cu descarcare (6000 ore) Strobe Rate: 0-20 Hz putere luminoasa: (3° beam): 382000 lux la 5 m;	
--	--	--	--	---	--

				(7° spot): 104700 lux la 5 m; (14° wash): 4680 lux la 5 m inseriere putere:6 unitati la 230 V alimentare: 240 VAC, 50/60 Hz putere si consum: 254 W, 1.3 A la 230 V, 50 Hz dimensiuni gobo: (rotating): 13.7 mm exterior, 11 mm imagine, 1 mm max grosime unghi de deschidere si zoom: (beam):		
Trasport				Tur – retur Chişinau-Cahul	Tur – retur Chişinau-Cahul	
Back line				Consola DiGico SD 11 48 Input Channels with full processing 24 Aux/Sub-Group busses with full processing 8 x 8 Matrix with full processing Assignable channel layout User programmable macros Capable of redundantly mirroring with another SD11 console Snapshots for seamlessly changing many parameters at once Offline software iPad control Broadcast software option i software option 12 x 100mm touch-sensitive, motorised faders 1 x 15” LCD high-resolution touchscreen 12 x 8-Segment LED bargraph meters 1 x 1/4” Headphone socket 1 x USB 2.0 slot 1 x PSU 1 x XLR3 1.2 – 12V Light connection 1 x Waves port (Optional)	Consola DiGico SD 11 48 Input Channels with full processing 24 Aux/Sub-Group busses with full processing 8 x 8 Matrix with full processing Assignable channel layout User programmable macros Capable of redundantly mirroring with another SD11 console Snapshots for seamlessly changing many parameters at once Offline software iPad control Broadcast software option i software option 12 x 100mm touch-sensitive, motorised faders 1 x 15” LCD high-resolution touchscreen 12 x 8-Segment LED bargraph meters 1 x 1/4” Headphone socket 1 x USB 2.0 slot 1 x PSU 1 x XLR3 1.2 – 12V Light connection 1 x Waves port (Optional) 16 x XLR Mic/Line Inputs 8 x XLR Line Outputs 1 x XLR AES/EBU Input (2 x channels) 1 x XLR AES/EBU Output (2 x channels) 2 x GPI 1/4” Jack 2 x GPO 1/4” Jack 1 x MIDI In/Thru/Out (5 pin DIN) 1 x Word Clock I/O BNC Rack is a 32 input, 16 output	

				16 x XLR Mic/Line Inputs 8 x XLR Line Outputs 1 x XLR AES/EBU Input (2 x channels) 1 x XLR AES/EBU Output (2 x channels) 2 x GPI 1/4" Jack 2 x GPO 1/4" Jack 1 x MIDI In/Thru/Out (5 pin DIN) 1 x Word Clock I/O BNC Rack is a 32 input, 16 output 32 Mic/Line Inputs at 48kHz or 28 Mic/Line inputs at 96kHz 8 Line Outputs 1 Output expansion card slot for adding 8 outputs MADI RJ45 Connectivity Optional Optics 7U Rack Mountable with supplied rackmount kit Gain Tracking™ Optional Redundant PSUs Can be used as a standalone rack Monitoare de podea echivalent FBT mitus 210LA MONITOR DE ETAPE ACTIVE 600W + 00W RMS - 134DB SPL • 2-bi-amplificare, design-bass-reflex cu driver coaxial • 2 x 250 mm (2 x 10 ...) ieșiți driverul de compresie din titan și bobina vocală de 64 mm • Răspuns în frecvență de la 60Hz la 20KHz • Amplificatoare încorporate de clasa D, 600WRMS la LF și 300WRMS la HF cu alimentare în modul switch • DSP cu 8 presetări ec Panou de control cu intrare XLR și legătură, volum,	32 Mic/Line Inputs at 48kHz or 28 Mic/Line inputs at 96kHz 8 Line Outputs 1 Output expansion card slot for adding 8 outputs MADI RJ45 Connectivity Optional Optics 7U Rack Mountable with supplied rackmount kit Gain Tracking™ Optional Redundant PSUs Can be used as a standalone rack Monitoare de podea echivalent FBT mitus 210LA MONITOR DE ETAPE ACTIVE 600W + 00W RMS - 134DB SPL • 2-bi-amplificare, design-bass-reflex cu driver coaxial • 2 x 250 mm (2 x 10 ...) ieșiți driverul de compresie din titan și bobina vocală de 64 mm • Răspuns în frecvență de la 60Hz la 20KHz • Amplificatoare încorporate de clasa D, 600WRMS la LF și 300WRMS la HF cu alimentare în modul switch • DSP cu 8 presetări ec • Panou de control cu intrare XLR și legătură, volum, presetări, filtru HP, elevator la sol Dispersie conică 70 ° • Carcasă de placaj de mestecăan de 15 mm, finisaj vopsea neagră rezistentă la zgârieturi tru aplicații de monitorizare a sunetului în direct, precum și pentru o față a difuzorului principal Configurare: 2 cale Amplificator încorporat LF / HF: 600/300 W RMS Amplificator încorporat LF / HF: 1200/600 W Răspuns la frecvență: 60Hz - 20KHz -6dB Woofer cu frecvență joasă: 2x10 - 2,5 bobină neodim inch Driver de înaltă frecvență: 1x1.4 - 2.5 colil neodim-cox inch SPL cont / vârf maxim: 127/134 dB Dispersia: 70 ° Hx conic Impedanta de intrare: 22 Kohm Frecvența de recrutare: 1,2 KHz Tobe Tama Starclasic Set(22X20, 16, 14, 12,10) In Ear G4 In Ear PSM 900 Combiu MarckBass Combiu VOX Microfoane OVID	
--	--	--	--	--	---	--


				presetări, filtru HP, elevator la sol Dispersie conică 70 ° • Carcasă de placaj de mesteacăn de 15 mm, finisaj vopsea neagră rezistentă la zgârieturi tru aplicații de monitorizare a sunetului în direct, precum și pentru o față a difuzorului principal Configurare: 2 cale Amplificator încorporat LF / HF: 600/300 W RMS Amplificator încorporat LF / HF: 1200/600 W Răspuns la frecvență: 60Hz - 20KHz -6dB Woofer cu frecvență joasă: 2x10 - 2,5 bobină neodim inch Driver de înaltă frecvență: 1x1.4 - 2.5 colil neodim-cox inch SPL cont / vârf maxim: 127/134 dB Dispersia: 70 ° Hx conic Impedanta de intrare: 22 Kohm Frecvența de recrutare: 1,2 KHz Tobe Tama Starclasic Set(22X20, 16, 14, 12,10) In Ear G4 In Ear PSM 900 Combiu MarckBass Combiu VOX Microfoane OVID		
Ecran LED	Ecran	China	Lightking	Ecran LED de 24 mp pe spatele scenei 2 Ecrane LED de 12 mp pentru extensii 3 procesoare video, si toate sistemele de comunicare LED DISPLAY 640 mm x 640 mm / cabinet	Ecran LED de 24 mp pe spatele scenei 2 Ecrane LED de 12 mp pentru extensii 3 procesoare video, si toate sistemele de comunicare LED DISPLAY 640 mm x 640 mm / cabinet - SMD2727 (WHITE) - 750 W/m2 - 250 W/m2	

				- SMD2727 (WHITE) - 750 W/m2 - 250 W/m2 - Lux 16.7 mln. - 1920 Hz Mediaserver V-Dj (regizor Video) pentru grafica	- Lux 16.7 mln. - 1920 Hz Mediaserver V-Dj (regizor Video) pentru grafica	
Filmare si translare pe Ecrane				Min. 3 camere si 3 operatori	Min. 3 camere si 3 operatori	

Numele, Prenumele: Țăruș Radu, În calitate de: director

Ofertantul: Țăruș – Stil SRL

Adresa: mun. Chișinău, str. L. Dimitriu 39



din “ ____ ” _____ 20__

Specificații de preț

[Acest tabel va fi completat de către ofertant în coloanele 5,6,7,8 și 11 la necesitate, iar de către autoritatea contractantă – în coloanele 1,2,3,4,9,10]

	Numărul procedurii de achiziție _____ din _____
	Obiectul de achiziției: _____

Cod CPV	Denumirea bunurilor/serviciilor	Unitatea de măsură	Cantitatea	Preț unitar (fără TVA)	Preț unitar (cu TVA)	Suma fără TVA	Suma cu TVA	Termenul de livrare/prestare	Clasificație bugetară (IBAN)	Discount %
1	2	3	4	5	6	7	8	9	10	11
	Servicii de închiriere									
	<u>Lotul 1:</u>					328000	393600			
	<i>Sistem profesional de sonorizare line array fara Backline</i>	buc	1	40000	48000	40000	48000	prestarea până la data de 31.12.23		
	<i>Sistem profesional de lumini artistice pentru spectacole</i>	buc	1	50000	60000	50000	60000	prestarea până la data de 31.12.23		
	<i>Transport</i>	buc	1	30000	36000	30000	36000	prestarea până la data de 31.12.23		
	<i>Back line</i>	buc	1	40000	48000	40000	48000	prestarea până la data de 31.12.23		
	<i>Ecran LED</i>	buc	1	115200	138240	115200	138240	prestarea până la data de 31.12.23		
	<i>Filmare si translare pe Ecrane</i>	buc	1	52800	63360	52800	63360	prestarea până la data de 31.12.23		
	TOTAL									

Numele, Prenumele: Țăruș Radu, În calitate de: director

Ofertantul: Țăruș – Stil SRL Adresa: mun. Chișinău, str. L. Dimitriu 39

Termenul de valabilitate a ofertei: 30 zile
