

Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție_ ocds-b3wdp1-MD-1658321737546 din_28/07/2022
Obiectul achiziției:Tehnica de calcul și accesorii IT pentru anul 2022

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Bunuri/servicii						
SSD 256 GB	CX400	Polonia	GOODRAM	2.5" SSD 256GB , SATAIII, Sequential Reads: 550 MB/s, Sequential Writes: 480 MB/s, Maximum Random 4k: Read: 65,000 IOPS / Write: 61,440 IOPS, Thickness- 7mm, Controller Phison PS3111-S11, 3D NAND TLC	2.5" SSD 256GB , SATAIII, Sequential Reads: 550 MB/s, Sequential Writes: 480 MB/s, Maximum Random 4k: Read: 65,000 IOPS / Write: 61,440 IOPS, Thickness- 7mm, Controller Phison PS3111-S11, 3D NAND TLC	
Mouse	SP-GM-01	China	Spacer	Optical Mouse, 800/1200/1600 dpi, USB, Black	MOUSE Spacer – gaming, gaming, cu fir, USB, optic, 2400 dpi, butoane/scroll 6/1, iluminare, negru, „SP-GM-01”	
Tastiere	K280e	China	Logitech	Keyboard, Waterproof design, Traditional layout, Comfortable, 12 Media (FN) Keys, USB, 1.5m, Black	Keyboard Logitech K280e, Low-profile, Quiet typing, Spill-resistant, Palm rest, 12 FN key, Black, USB	

Prelungitor	ES5/5	China	Defender	Surge Protector , 5 Sockets, 5.0m, Black	Prelungitor cu protectie Defender ES black 5m, 5 sockets	
Network Interface Card	TG-3468	China	TP-Link	Gigabit PCIe Network Interface Card, Realtek RTL8168B, 10/100/1000Mbps Auto-Negotiation RJ45 port, Auto MDI/MDIX	Adaptor rețea Gigabit PCI Express TG-3468,10/100/1000Mbps, Interfață PCIe 32-bit,Wake-on-LAN	
Network Interface Card	Archer T2U Nano	China	TP-Link	USB2.0 Mini Wireless AC Dual Band LAN Adapter , 600Mbps Advanced Security: Supports 64/128 WEP, WPA, PA2/WPA-PSK/WPA2-PSK (TKIP/AES) Supports Windows 10/8.1/8/7/XP and Mac OS	"USB2.0 Nano Wireless AC Dual Band LAN Adapter TP-LINK ""Archer T2U Nano"", 600Mbps // Advanced Security – Supports 64/128-bit WEP, WPA/WPA2, and WPA-PSK/WPA2-PSK encryption standards"	
Swich 16 port	TL-SG2218	China	TP-Link	16-port Pure-Gigabit L2 Managed Switch, 16 10/100/1000Mbps LAN ports including 2 combo SFP slots, Port/Tag/MAC/Voice/Protocol-based VLAN, GVRP, STP/RSTP/MSTP, IGMP V1/V2/V3 Snooping, L2/L3/L4 Traffic Classification/ Priority	SWITCH TP-LINK L2+ cu management 16 porturi Gigabit + 2 sloturi SFP, carcasa metalica, rackabil „TL-SG2218"	
Switch 24 port	CRS326-24G-2S + RM	LT	MIKROTIK	Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Dimensions 443 x 144 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -40°C to 60°C	Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Dimensions 443 x 144 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -40°C to 60°C	

Swich 8 port	DGS-1100-08V2/A1A	China	D-Link	8-port 10/100/1000 Base-T SMART, // Настраиваемый L2 коммутатор с 8 портами 10/100/1000Base-T	"8-port 10/100/1000 Base-T SMART, D-Link DGS-1100- 08V2/A1A // Настраиваемый L2 коммутатор с 8 портами 10/100/1000Base-T"	
Monitor	24E1Q	China	AOC	23.8" IPS LED 24E1Q Borderless Matte Black (5ms, 50M:1, 250cd, 1920x1080, 178°/178°, VGA, HDMI, DisplayPort, Speakers 2 x 2W, Audio Line-out, VESA)	23.8" AOC IPS LED 24E1Q Borderless Matte Black (5ms, 50M:1, 250cd, 1920x1080, 178°/178°, VGA, HDMI, DisplayPort, Speakers 2 x 2W, Audio Line-out, VESA)	
Memorie RAM DDR4	GR2666D464L19S/8G	Polonia	GOODRAM	8GB DDR4- 2666MHz, CL19, 288pin DIMM 1.2V Capacitatea Memoriei (Total): 8GB Tip Memorie: DDR4 SDRAM Frecvență memorie: 2666 MHz Viteza de memorie nominală: PC4- 21300 Latență CAS: CL19 Tensiune RAM: 1.2V	8GB DDR4-2666 GOODRAM, PC21300, CL19, 1.2V GR2666D464L19S/8G	
TOTAL						

Semnat: _____ Numele, Prenumele: Constantin Alexandru În calitate de: director
Ofertantul: Triomac SRL Adresa: Orhei, str Stefan cel Mare 3, of 16