

Formularul ofertei (F3.1)

Data depunerii ofertei: 09.10.2019

Procedura de achiziție Nr.: ocds-b3wdp1-MD-1568811783946

Anunț/Invitația de participare Nr.:

Către: Aparatul Președintelui Republicii Moldova

„BTS Pro” S.R.L. declară că: declară că:

- a) Au fost examinate și nu există rezervări față de documentele de atribuire, inclusiv modificările nr. _____.
- b) „BTS Pro” S.R.L. se angajează să presteze, în conformitate cu documentele de atribuire și condițiile stipulate în specificațiile tehnice și preț, următoarele bunuri/servicii: **Tehnică de calcul și rețea.**
- c) Suma totală a ofertei fără TVA constituie:
602 110,00 MDL fără TVA.
- d) Suma totală a ofertei cu TVA constituie:
722 532,00 MDL cu TVA.
- e) Prezenta ofertă va rămâne valabilă pentru perioada de timp specificată în **FDA3.8.**, începînd cu data-limită pentru depunerea ofertei, în conformitate cu **FDA4.2.**, va rămîne obligatorie și va putea fi acceptată în orice moment pînă la expirarea acestei perioade;
- f) În cazul acceptării prezentei oferte, „BTS Pro” S.R.L. se angajează să obțină o Garanție de bună execuție în conformitate cu **FDA6**, pentru executarea corespunzătoare a contractului de achiziție publică.
- g) Nu sîntem în nici un conflict de interese, în conformitate cu art. 74 din Legea nr. 131 din 03.07.2015 privind achizițiile publice.
- h) Compania semnatară, afiliații sau sucursalele sale, inclusiv fiecare partener sau subcontractor ce fac parte din contract, nu au fost declarate neeligibile în baza prevederilor legislației în vigoare sau a regulamentelor cu incidență în domeniul achizițiilor publice.

Semnat:

Nume: Gnidaș Bogdan

În calitate de: Manager în comerț

Ofertantul: „BTS Pro” S.R.L.

Adresa: Republica Moldova, mun. Chisinau, str. Ion Creangă, 6V



Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_2_din_9_

SPECIFICAȚII TEHNICE (F4.1)

Nr. CPV 1	Denumirea bunurilor 2	Modelul 3	Tara de orig 4	Produ- catorul 5	Specificatia din FDA 6	Specificatia propusa 7	Stand- arde 8
LOT 6							
6 1	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	SMT1500I + AP9630	PRC	APC	<p>Cerințe minime Echivalent APC Smart-UPS C 1500VA LCD 230V with SmartConnect (SMC1500IC): Output-Output power capacity 900Watts / 1.5kVA; Max Configurable Power (Watts) 900Watts / 1.5kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 5%; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 240; Topology Line Interactive; Waveform type Sine wave; Output Connections (8) IEC 320 C13 (Battery Backup) (2) IEC Jumpers (Battery Backup); Transfer Time 6ms typical : 10ms maximum. Input -Nominal Input Voltage - 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C14; Input voltage range for main operations 180 - 287V; Input voltage adjustable range for mains operation 170 - 300V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45, USB Control panel Multi-function LCD status and control console Audible Alarm Alarm when on battery : distinctive low battery alarm: configurable delays Availability Boost and Trim Automatic Voltage Regulation (AVR); Intelligent battery management; Power conditioning Automatic restart of loads after UPS shutdown; Automatic self-test; Temperature-compensated battery charging; Disconnected battery notification Serviceability Battery failure notification; Predictive failure notification; User-replaceable batteries; Resettable circuit breakers; Hot-swappable batteries Manageability Network manageable; Disconnected battery notification; Audible</p>	<p>Cerințe minime Echivalent APC Smart-UPS C 1500VA LCD 230V with SmartConnect (SMT1500I + AP9630): Output-Output power capacity 1000Watts / 1.5kVA; Max Configurable Power (Watts) 1000Watts / 1.5kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 5%; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 230, 240; Topology Line Interactive; Waveform type Sine wave; Output Connections (8) IEC 320 C13 (Battery Backup) (2) IEC Jumpers (Battery Backup); Transfer Time 2ms typical : 10ms maximum. Input -Nominal Input Voltage - 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C14; Input voltage range for main operations 160 - 286V; Input voltage adjustable range for mains operation 151 - 302V; Other Input Voltages 220, 230, 240 Communications & Management Interface Port(s) RJ-45, USB Control panel Multi-function LCD status and control console Audible Alarm Alarm when on battery : distinctive low battery alarm: configurable delays Availability Boost and Trim Automatic Voltage Regulation (AVR); Intelligent battery management; Power conditioning Automatic restart of loads after UPS shutdown; Automatic self-test; Temperature-compensated battery charging; Disconnected battery notification Serviceability Battery failure notification; Predictive failure notification; User-replaceable batteries; Resettable circuit</p>	ISO



Semnat: Gritaș Bogdan, manager în comert, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 100860061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_3_din_9_

Nr. CPV 1	Denumirea bunurilor 2	Modelul 3	Tara de orig 4	Producatorului 5	Specificatia din FDA 6	Specificatia propusa 7	Stand-arde 8
					alarms; LED status indicators; Serial connectivity; USB connectivity Garanție: 12 luni	breakers; Hot-swappable batteries Manageability Network manageable; Disconnected battery notification; Audible alarms; LED status indicators; Serial connectivity; USB connectivity Garanție: 12 luni	
6 2	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	SMT1000I + AP9630	PRC	APC	<p>Cerințe minime Echivalent APC Smart-UPS C 1000VA LCD 230V with SmartConnect (SMC1000IC): Output Output power capacity 600Watts / 1.0kVA; Max Configurable Power (Watts) 600Watts / 1.0kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 5%; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 240 Topology Line Interactive Waveform type Sine wave Output Connections (8) IEC 320 C13 (Battery Backup); (2) IEC Jumpers (Battery Backup) Input Nominal Input Voltage 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C14; Input voltage range for main operations 180 - 287V; Input voltage adjustable range for mains operation 170 - 300V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45, USB; Control panel; Multi-function LCD status and control console; Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays; Availability Boost and Trim Automatic Voltage Regulation (AVR); Intelligent battery management; Power conditioning; Automatic restart of loads after UPS shutdown; Automatic self-test; Temperature-compensated battery charging; Disconnected battery notification Serviceability Battery failure notification; Predictive failure</p>	<p>Cerințe minime Echivalent APC Smart-UPS C 1000VA LCD 230V with SmartConnect (SMT1000I + AP9630): Output Output power capacity 700Watts / 1.0kVA; Max Configurable Power (Watts) 700Watts / 1.0kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 5%; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 230, 240 Topology Line Interactive Waveform type Sine wave Output Connections (8) IEC 320 C13 (Battery Backup); (2) IEC Jumpers (Battery Backup) Input Nominal Input Voltage 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C14; Input voltage range for main operations 160 - 286V; Input voltage adjustable range for mains operation 151 - 302V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45, USB; Control panel; Multi-function LCD status and control console; Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays; Availability Boost and Trim Automatic Voltage Regulation (AVR); Intelligent battery management; Power conditioning; Automatic restart of loads after UPS shutdown; Automatic self-test; Temperature-compensated battery</p>	ISO



Semnat: Grigoraș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_4_din_9_

Nr. CPV 1	Denumirea bunurilor 2	Modelul 3	Tara de orig 4	Producatorului 5	Specificatia din FDA 6	Specificatia propusa 7	Stand-arde 8
6 3	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	SRT2200RMXLI-NC	PRC	APC	<p>notification; User-replaceable batteries; Resettable circuit breakers; Hot-swappable batteries Manageability Network manageable; Disconnected battery notification; Audible alarms; LED status indicators; Serial connectivity; USB connectivity Garanție: 12 luni</p> <p>Cerințe minime Echivalent APC Smart-UPS SRT 2200VA RM 230V Network Card (SRT2200RMXLI-NC): Output power capacity 1.98kWatts / 2.2kVA; Max Configurable Power (Watts) 1.98kWatts / 2.2kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 2% Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 240; Load Crest Factor 3 : 1 Topology Double Conversion Online Waveform type Sine wave Output Connections (2) IEC 320 C19 (Battery Backup); (8) IEC 320 C13 (Battery Backup); (2) IEC Jumpers (Battery Backup) Bypass Built-in Bypass Input Nominal Input Voltage 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C20; Input voltage range for main operations 160 - 275V; Input voltage adjustable range for mains operation 100 - 275 (half load)V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB; Pre-Installed SmartSlot™ Cards Serviceability Automatic self-test; Disconnected battery notification; Audible alarms; Predictive failure</p>	<p>charging; Disconnected battery notification Serviceability Battery failure notification; Predictive failure notification; User-replaceable batteries; Resettable circuit breakers; Hot-swappable batteries Manageability Network manageable; Disconnected battery notification; Audible alarms; LED status indicators; Serial connectivity; USB connectivity Garanție: 12 luni</p> <p>Cerințe minime Echivalent APC Smart-UPS SRT 2200VA RM 230V Network Card (SRT2200RMXLI-NC): Output power capacity 1.98kWatts / 2.2kVA; Max Configurable Power (Watts) 1.98kWatts / 2.2kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 2% Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 240; Load Crest Factor 3 : 1 Topology Double Conversion Online Waveform type Sine wave Output Connections (2) IEC 320 C19 (Battery Backup); (8) IEC 320 C13 (Battery Backup); (2) IEC Jumpers (Battery Backup) Bypass Built-in Bypass Input Nominal Input Voltage 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C20; Input voltage range for main operations 160 - 275V; Input voltage adjustable range for mains operation 100 - 275 (half load)V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB; Pre-Installed SmartSlot™ Cards</p>	ISO



Semnat: Gritaș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_5_din_9_

Nr. CPV 1	Denumirea bunurilor 2	Modelul 3	Tara de orig 4	Produ- catrorul 5	Specificatia din FDA 6	Specificatia propusa 7	Stand- arde 8
					notification Protection Frequency and voltage regulation; Power conditioning Input power factor correction; Generator compatible Cold-start capable; Resettable circuit breaker; Safety-agency approved Manageability LED status indicators; SmartSlot; Network manageable Serial connectivity Adaptability Flash upgradeable firmware; Rack/Tower convertible; Plug-and-Play external batteries Availability Automatic restart of loads after UPS shutdown Garanție: 12 luni	Serviceability Automatic self-test; Disconnected battery notification; Audible alarms; Predictive failure notification Protection Frequency and voltage regulation; Power conditioning Input power factor correction; Generator compatible Cold-start capable; Resettable circuit breaker; Safety-agency approved Manageability LED status indicators; SmartSlot; Network manageable Serial connectivity Adaptability Flash upgradeable firmware; Rack/Tower convertible; Plug-and-Play external batteries Availability Automatic restart of loads after UPS shutdown Garanție: 12 luni	
6 4	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	SMT1500RMI2U + AP9630	PRC	APC	Cerințe minime Echivalent APC Smart-UPS C 1500VA LCD RM 2U 230V with SmartConnect (SMC1500I-2UC): Output Output power capacity 900Watts / 1.5kVA; Max Configurable Power (Watts) 900Watts / 1.5kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 5% ; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 240; Topology Line Interactive; Waveform type Sine wave; Output Connections (4) IEC 320 C13 (Battery Backup); (2) IEC Jumpers (Battery Backup) Transfer Time 6ms typical : 10ms maximum Input Nominal Input Voltage 230V; Input frequency 50/60 Hz +/- 3 Hz (auto sensing); Input Connections IEC-320 C14; Input voltage range for main operations 180 -	Cerințe minime Echivalent APC Smart-UPS C 1500VA LCD RM 2U 230V with SmartConnect (SMT1500RMI2U + AP9630): Output Output power capacity 1.0kWatts / 1.5kVA; Max Configurable Power (Watts) 1.0kWatts / 1.5kVA; Nominal Output Voltage 230V; Output Voltage Distortion Less than 5% ; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz; Other Output Voltages 220, 240; Topology Line Interactive; Waveform type Sine wave; Output Connections (4) IEC 320 C13 (Battery Backup); (2) IEC Jumpers (Battery Backup) Transfer Time 2ms typical : 10ms maximum Input Nominal Input Voltage 230V; Input frequency 50/60 Hz +/- 3 Hz (auto	ISO



Semnat: Grigoraș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_6_din_9_


Nr. CPV	Denumirea bunurilor	Modelul	Tara de orig	Producatorul	Specificatia din FDA	Specificatia propusa	Stand-arde
1	2	3	4	5	6	7	8
					287V; Input voltage adjustable range for mains operation 170 - 300V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45, USB Control panel Multi-function LCD status and control console Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays Availability Boost and Trim Automatic Voltage Regulation (AVR); Intelligent battery management; Power conditioning Automatic restart of loads after UPS shutdown; Automatic self-test; Temperature-compensated battery charging; Disconnected battery notification Serviceability Battery failure notification; Predictive failure notification; Resettable circuit breakers; User-replaceable batteries; Hot-swappable batteries Manageability Network manageable; Disconnected battery notification; Audible alarms; LED status indicators; Serial connectivity; USB connectivity Garanție: 12 luni	sensing); Input Connections IEC-320 C14; Input voltage range for main operations 160 - 286V; Input voltage adjustable range for mains operation 151 - 302V; Other Input Voltages 220, 240 Communications & Management Interface Port(s) RJ-45, USB Control panel Multi-function LCD status and control console Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays Availability Boost and Trim Automatic Voltage Regulation (AVR); Intelligent battery management; Power conditioning Automatic restart of loads after UPS shutdown; Automatic self-test; Temperature-compensated battery charging; Disconnected battery notification Serviceability Battery failure notification; Predictive failure notification; Resettable circuit breakers; User-replaceable batteries; Hot-swappable batteries Manageability Network manageable; Disconnected battery notification; Audible alarms; LED status indicators; Serial connectivity; USB connectivity Garanție: 12 luni	
6 5	Acumulator 7,2AH	Baterie UPS 12V/ 7.2AH CSB GP 1272F2	PRC	CSB	Cerințe minime Acumulator pentru UPS 12V/7.2AH Garanție - 12 luni	Baterie UPS 12V/ 7.2AH CSB GP 1272F2	ISO
6 6	Acumulator 12AH	Baterie UPS 12V/ 12AH Ultra Power	PRC	UltraPower	Cerințe minime Acumulator pentru UPS 12V/12AH Garanție - 12 luni	Baterie UPS 12V/ 12AH Ultra Power	ISO
6 7	Acumulator 17AH	Baterie UPS 12V/ 17AH Ultra Power	PRC	UltraPower	Cerințe minime Acumulator pentru UPS 12V/17AH Garanție - 12 luni	Baterie UPS 12V/ 17AH Ultra Power	ISO
LOT 7							
7 1	Aparat de telefon staționar	Telephone Panasonic KX-TS2388UAB, Black, LCD,	Malaysia	Panasonic	Cerințe minime Aparat de Telefon staționar (echivalent Panasonic KX-TS2365RUB)	Telephone Panasonic KX-TS2388UAB, Black, LCD, AOH, Caller ID, Sp-phone	ISO

Semnat: Gritaș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_7_din_9_

Nr. CPV	Denumirea bunurilor	Modelul	Tara de orig	Producatorul	Specificatia din FDA	Specificatia propusa	Stand-arde
1	2	3	4	5	6	7	8
7 2	Aparat de telefon staționar	AOH, Caller ID, Sp-phone Dect Panasonic KX-TG1612UAH, Grey, AOH, Caller ID, TG1611+ optional handset	Vietnam	Panasonic	Culoare – Neagră Garanție - 36 luni Cerințe minime Aparat de Telefon fără fir (echivalent Panasonic KX-TG1612UAH) distanță de operare maximă 300m Culoare – Neagră Garanție - 36 luni	Dect Panasonic KX-TG1612UAH, Grey, AOH, Caller ID, TG1611+ optional handset	ISO
8 1	Calculator	ESPRIMO K558/24	PRC	Fujitsu	Cerințe minime Product number" sau "service tag" Form factor: 23.8" All-in-One PC Panel: 23.8" IPS Wide Viewing Angle WLED, Full HD 1920x 1080 resolution Processor: echivalentul Intel® Core™ i5-8500 Processor (up to 4.1 GHz, 9 MB cache, 6 cores) Memory: 8 GB DDR4 -2666 Mhz Graphics: Integrated SSD: 256 GB Ports: USB 3.0, Ethernet, audio Pointing device: Wireless Business Slim Keyboard (Eng/Rus/Rom) and Mouse with mouse pad Speakers: Integrated Sistemul de Operare: Pre installed licensed operating system with Active Directory domain support (Eng), 64 bit /MS Windows 10 Pro OEM license; MS Office 2019 (Classic 2019 versions of Word, Excel, PowerPoint, and Outlook) English Termen Garanție: 60 luni warranty;	Form factor: 23.8" All-in-One PC Panel: All-in-One 23.8 inch (60.5 cm, FHD) Processor: Intel® Core i5-8500 Memory: 8 GB DDR4 -2666 Mhz Graphics: Integrated Intel® UHD Graphics SSD: SSD SATA III 256GB Ports: Front: 1x Audio headphone, 1x Audio microphone, 2x USB 3.0; Rear: 1x DisplayPort, 3x USB 2.0, 2x USB 3.0, 1x LAN(RJ45), 2x PS2; 1x Audio line-in, 1x Audio line-out Pointing device: Wireless KB Mouse Set LX410 RU/US with mouse pad Speakers: Multimedia speaker Integrated Sistemul de Operare: Lic Win10 Pro OEM Office Home and Business 2019 Termen Garanție: 60 luni	ISO
9 1	Stick-uri memorie USB	32GB USB3.1 Flash Drive Transcend "JetFlash 820"	PRC	Transcend	Cerințe minime Capacitate – 32 GB Interfața – minim USB 3,0 LED indicator transfer de date Tip carcasă – clasică cu capac Material carcasă – metal Termen de garanție – 24 luni	32GB USB3.1 Flash Drive Transcend "JetFlash 820", Gold, Metal Case, Luxury Design (R/W:90/25MB/s) With back indicator	ISO
10 1	Imprimanta	Printer Epson LQ-690, A4	China	Epson	Cerințe minime Echivalent cu EPSON LQ 690 Printing Technology - dot-matrix Printing Output Type - monochrome	EPSON LQ 690 Printing Technology - dot-matrix Printing Output Type - monochrome Number of Pins - 24 pins	ISO



Semnat: Gritaș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației: Tehnică de calcul și rețea		Lot: 1-11	Pagina_8_din_9_

Nr. CPV 1	Denumirea bunurilor 2	Modelul 3	Tara de orig 4	Producatorul 5	Specificatia din FDA 6	Specificatia propusa 7	Stand-arde 8
					<p>Number of Pins - 24 pins Number of columns - 106 columns Print speed- at 10 cpi; at 12 cpi; High speed draft - 440 cps; 529 cps; Draft - 330 cps; 396 cps; LQ - 110 cps; 132 cps Paper/media - Cut sheet (single sheet, multi part); Continuous paper (single and multi part); Roll paper; Envelope; Card; Label (cut sheet and fan fold); Paper Thickness Continuous - 0.065 mm - 0.49 mm Paper Thickness Label Base - 0.16 mm - 0.19 mm Paper Thickness Label Total - 0.16 mm - 0.19 mm Paper Thickness Multi Part - 0.12 mm - 0.49 mm Paper Thickness Single Sheet - 0.065 mm - 0.19 mm Paper feeding - Manual insertion - Front in, front out; Roll paper holder - Rear in, front out; Fonts - 9 LQ and 1 draft bitmap; 4 scalable typefaces; 8 barcode fonts Interface - USB, parallel Copy capability - 1 original + 6 copies Ribbon yield - 10 million characters Reliability - MTBF (20,000 power on hours), MVBF (40 million lines), print head life (400 million strokes/wire) Consumables - Black ribbon (10 million characters)</p>	<p>Number of columns - 106 columns Print speed- at 10 cpi; at 12 cpi; High speed draft - 440 cps; 529 cps; Draft - 330 cps; 396 cps; LQ - 110 cps; 132 cps Paper/media - Cut sheet (single sheet, multi part); Continuous paper (single and multi part); Roll paper; Envelope; Card; Label (cut sheet and fan fold); Paper Thickness Continuous - 0.065 mm - 0.49 mm Paper Thickness Label Base - 0.16 mm - 0.19 mm Paper Thickness Label Total - 0.16 mm - 0.19 mm Paper Thickness Multi Part - 0.12 mm - 0.49 mm Paper Thickness Single Sheet - 0.065 mm - 0.19 mm Paper feeding - Manual insertion - Front in, front out; Roll paper holder - Rear in, front out; Fonts - 9 LQ and 1 draft bitmap; 4 scalable typefaces; 8 barcode fonts Interface - USB, parallel Copy capability - 1 original + 6 copies Ribbon yield - 10 million characters Reliability - MTBF (20,000 power on hours), MVBF (40 million lines), print head life (400 million strokes/wire) Consumables - Black ribbon (10 million characters)</p>	



Semnat: Grigăș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858


C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău

Numărul licitației: nr. ocds-b3wdp1-MD-1568811783946	Aparatul Președintelui Republicii Moldova	Data: 09.10.2019	Alternativa nr.: -
Denumirea licitației:	Tehnică de calcul și rețea	Lot: 1-11	Pagina_9_din_9_

SPECIFICAȚII DE PREȚ (F4.2)

Nr. CPV	Denumirea bunurilor	U.M.	Cant	Pret unitar f/TVA MDL	Pret unitar cu TVA MDL	Suma f/TVA MDL	Suma cu TVA MDL	Garantie Luni	Termen de livrare
1	2	3	4	5	6	7	8	9	10
LOT 6									
6 1	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	Buc.	2	14065,00	16878,00	28130,00	33756,00	12 luni	30 zile din momentul semnării și înregistrării contractului
6 2	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	Buc.	8	11970,00	14364,00	95760,00	114912,00	12 luni	30 zile din momentul semnării și înregistrării contractului
6 3	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	Buc.	1	29982,50	35979,00	29982,50	35979,00	12 luni	30 zile din momentul semnării și înregistrării contractului
6 4	Sursă de alimentare cu energie electrică neîntreruptibilă (UPS)	Buc.	2	17167,50	20601,00	34335,00	41202,00	12 luni	30 zile din momentul semnării și înregistrării contractului
6 5	Acumulator 7,2AH	Buc.	30	250,00	300,00	7500,00	9000,00	12 luni	30 zile din momentul semnării și înregistrării contractului
6 6	Acumulator 12AH	Buc.	4	327,50	393,00	1310,00	1572,00	12 luni	30 zile din momentul semnării și înregistrării contractului
6 7	Acumulator 17AH	Buc.	2	477,50	573,00	955,00	1146,00	12 luni	30 zile din momentul semnării și înregistrării contractului
TOTAL LOT 6:						197972,50	237567,00		
LOT 7									
7 1	Aparat de telefon staționar	Buc.	20	622,50	747,00	12450,00	14940,00	36 luni	30 zile din momentul semnării și înregistrării contractului
7 2	Aparat de telefon staționar	Buc.	2	622,50	747,00	1245,00	1494,00	36 luni	30 zile din momentul semnării și înregistrării contractului
TOTAL LOT 7:						13695,00	16434,00		
8 1	Calculator	Buc.	20	18987,50	22785,00	379750,00	455700,00	60 luni	30 zile din momentul semnării și înregistrării contractului
9 1	Stick-uri memorie USB	Buc.	20	195,00	234,00	3900,00	4680,00	24 luni	30 zile din momentul semnării și înregistrării contractului
10 1	Imprimantă	Buc.	1	6792,50	8151,00	6792,50	8151,00	12 luni	30 zile din momentul semnării și înregistrării contractului
TOTAL:						602110,00	722532,00		

Valabilitatea ofertei: 30 zile



Semnat: Grigăș Bogdan, manager în comerț, bg@bts.md. Ofertantul: BTS PRO SRL, adresa: mun. Chișinău, str. I. Creangă, 6-V, tel.: 022 870 244, fax.: 022 595 858

C/F 1008600061565; C/D MD23EN00000222415793845; C/B ENEGMD22; B.C. „Energbank” S.A. filiala Centru, Chișinău