











BLITAR FAST

Description	Harness with ergonomic belt equipped with quick release buckles.		
Standard	EN361:2002		
	EN358:2018		
Attachment Points		Device with four attachment points, one on the rear and one on the front (obtained by connecting two semi-attachment points A/2) for fall arrest, and two on the side for restraint and work positioning. The large, functional dorsal and lateral hooks are made of forged steel.	
Adjustment	TRIPLE - on the upper and lower parts of the harness - on the central part of the positioning belt		
Metal components	Zinc-plated steel		
Straps	45 mm and 30 mm wide polyester		
Plus		EXTREME LOAD 150 kg The additional test certifies the resistance of COFRA devices against a maximum nominal load of 150 kg, compared with the 100 kg of the normal devices on the market.	
		REVERSE-D Thanks to REVERSE-D technology, attachment points can be folded away and closed at any time, and whenever they are not needed. The ability to shut away attachment points prevents the user from remaining accidentally stuck or caught on protrusions and dangerous snags.	
		LOOP TOOL CARRIER The loop tool carrier offers the user easy and accessible storage of work tools when they are not in use.	
		3D-PERSPIREX 3D-Perspirex technology takes advantage from three-dimensional weave of the coating sponge to increase total breathability and comfort for the end user.	
		QUICK-RELEASE BUCKLES Quick-release buckles offer the user fast and easy locking while maintaining high resistance to stresses.	

Plus	<p>HIGH-TENACITY POLYESTER STRAP</p> 	The strap is made of high-tenacity polyester making it highly resistant to tear and abrasion.		
	<p>STEEL COMPONENTS</p> 	Steel resists perfectly to the considerable stresses which develop during a fall. All steel components have undergone anticorrosive galvanisation treatment with zinc or chrome.		
Packaging	Code	Size	Quantity	Weight (pc.)
	A001-1106.I1	S-2XL	1 pc.	1765 g
	A001-K106.I1		10 pcs.	
	A001-1106.I3	L-3XL	1 pc.	1870 g
	A001-K106.I3		10 pcs.	

SIZE CHART

SIZE					
	HARNESS				BELTS
	A (cm)	B (cm)	C (cm)	H (cm)	B (cm)
S-2XL	88/116	70/104	48/70	160/187	70/120
L-3XL	100/124	96/130	56/78	181/200	96/150

STOCKING CONDITIONS AND MAINTENANCE

Lifetime	The lifetime of the unused metal products is unlimited. The lifetime of the unused not metal products is 10 years under normal conditions. Once the product is used, its lifetime cannot be estimated since there are factors which could considerably reduce its lifetime such as: intense use; damage to product components; contact with chemical substances; high temperatures, abrasions, cuts, violent impacts, wrong use and stockage.
Cleaning	<p>Cleaning the textile and plastic parts: wash only with cold fresh water and neutral soap and allow to air dry, away from direct sources of heat.</p> <p>Cleaning the metallic parts: wash with cold fresh water and dry.</p> <p>If the equipment becomes wet either during use or after cleaning, it must be left to air dry and kept away from direct heat.</p>
Transport and stocking	Keep the device in its original packaging. During transport and storage, keep this product away from light and sources of heat, from high humidity, from sharp edges or objects, from corrosive substances and from any other possible cause of damage or deterioration, in order to preserve the performance and safety of the product. Keep this product in a cool, dry place to preserve the performance and safety of the product.