# SPARK-L **LED** Lightbar

# **General Specs**

(all an

- Light strength powered by special designed lenses
- UV and impact resistanced optical polycarbonate lenses with different colours
- Powerful speakers with low impedance neodymium magnets The LED light strength contrast opportunity (optional)
- Multiple flash pattern

nrmg

ELEKTRONİK

ARMAS Bektro Inönü Mah.17


Tel +90 (312)

The feature to shut down the back warning LEDs (optional)

# **Technical Specs**

Model	SPARK-L
Voltage	12VDC and 24VDC together
Lights	Power LED (1W or 3W options)
Speaker	Neodymium (N35 or N42)
Speaker power	100WRMS (8 ohm or 11ohm options)
Plastic parts	Polycarbonate(UV and shock resistant)
LED color	White, Blue, Red, Green, Amber
Lens color	Transparent, Blue, Red, Green, Amber
Standards	ECER65, SAE (with correct configurations)
Dimensions	Lenght :114cm (123cm, 145cm, 167cm options) Width: 37,5cm Height : 8,5cm(general) / 10,4cm searchlight area:





**Related Products** 

EXPERT-100 Siren&PA System





Front and Rear Searchlight

Left-right Alley light



#### Extended lightbar pictures;



ARMAS Elektronik Sanayi Ve Ticaret Limited Şirketi www.armaselektronik.com Tel : +90.312.397 79 21 Faks : +90.312.397 79 25



# EXPERT-100 Siren and PA Device

#### General

- Siren functions, PA(public address) and lightbar controls
- Wail, Yelp, Hi-Lo(or Phaser), Manuel and Horn siren kinds
- Remote control unit with PU type spiral cable easy to plug in and off
- Microphone volume control for PA
- Working in accordance with the lightbars and lightbars control feature
- Siren warning, announcing and lighting warning systems with hand control unit
- Displaying light system flash mode with lightbar simulation LEDs
- Automatical activation of lightbars in case of wail, yelp and manuel siren warnings
- Siren warning with double click of PTT
- External AUX signal input (external audio)

# **Related Products**

Alternative-1 SPARK-L lightbar

## **Technical Specs**

Model	EXPERT-100
Voltage	12VDC or 24VDC
Siren Output Power	100WRMS (at 8 ohm or 11 ohm)
Frequency Response	300Hz-10000Hz , maximum ±3dB
Siren kinds	Wail, Yelp, Hi-Lo(or Phaser), Manuel, Horn
Functions	Siren, PA, Light control, External AUX, volume control
Standards	SAE J1849

Alternative-2 FLARE lightbar



HP-1110 Speaker (Neodymium)



HP-1110F Speaker (Ferrite)







ARMAS Elektronik Sanayi Ve Ticaret Limited Sirketi www.armaselektronik.com Tel : +90.312.397 79 21 Faks : +90.312.397 79 25