



Test Report issued under the responsibility of:



**TEST REPORT**  
**IEC 60598-2-3**  
**Luminaires**  
**Part 2: Particular requirements**  
**Section 3: Luminaires for road and street lighting**

**Report Number.** .....: **TGM-VA EE 36464 SFT-1**  
**Date of issue** .....: **2016-01-21**  
**Total number of pages**.....: **40**

**Name of Testing Laboratory** .....: Staatliche Versuchsanstalt – TGM  
**preparing the Report**.....: Elektrotechnik und Elektronik

**Applicant's name**.....: Schröder SA  
**Address** .....: Rue de Lusambo 67, 1190 Brussels , Belgium

**Test specification:**

**Standard**.....: IEC 60598-2-3:2002 (Third Edition) + A1:2011 used in conjunction with IEC 60598-1:2014 (Eighth Edition)  
**Test procedure** .....: CB Scheme , ENEC  
**Non-standard test method**.....: N/A

**Test Report Form No**.....: IEC60598\_2\_3J  
**Test Report Form(s) Originator**.....: Intertek Semko AB  
**Master TRF** .....: 2014-09

**Copyright © 2014 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.**





This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

**This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.**

**General disclaimer:**

The test results presented in this report relate only to the object tested.  
This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

<b>Test item description .....</b>	Luminaire for road and street lighting		
<b>Trade Mark .....</b>	<b>Schröder</b> 		
<b>Manufacturer .....</b>	Tungsram-Schreder ZRT Topart 2, 2084 Pilisszentivan-Hungary		
<b>Model/Type reference .....</b>	SKIDO		
<b>Ratings .....</b>	100-240V, 50/60Hz, Cl.I, IP65, IK08, Ta 50°C		
<b>Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):</b>			
<input checked="" type="checkbox"/>	<b>CB Testing Laboratory:</b>	Staatliche Versuchsanstalt – TGM Elektrotechnik und Elektronik 	
<b>Testing location/ address .....</b>		A-1200 Wien, Wexstrasse 19-23	
<input type="checkbox"/>	<b>Associated CB Testing Laboratory:</b>		
<b>Testing location/ address .....</b>			
<b>Tested by (name, function, signature) .....</b>		Ing. Jahangir NOORI	
<b>Approved by (name, function, signature) ..</b>		Mag. Thomas THUN	
<input type="checkbox"/>	<b>Testing procedure: TMP/CTF Stage 1:</b>		
<b>Testing location/ address .....</b>			
<b>Tested by (name, function, signature) .....</b>			
<b>Approved by (name, function, signature) ..</b>			
<input type="checkbox"/>	<b>Testing procedure: WMT/CTF Stage 2:</b>		
<b>Testing location/ address .....</b>			
<b>Tested by (name + signature) .....</b>			
<b>Witnessed by (name, function, signature) . :</b>			
<b>Approved by (name, function, signature) .. :</b>			
<input type="checkbox"/>	<b>Testing procedure: SMT/CTF Stage 3 or 4:</b>		
<b>Testing location/ address .....</b>			
<b>Tested by (name, function, signature) .....</b>			
<b>Witnessed by (name, function, signature) . :</b>			
<b>Approved by (name, function, signature) .. :</b>			
<b>Supervised by (name, function, signature) :</b>			

<b>List of Attachments (including a total number of pages in each attachment):</b>  EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES see pages 35-36 /40	
<b>Summary of testing:</b>  Full test performed on type SKIDO representing also for the other types pictures see pages 37-40	
<b>Tests performed (name of test and test clause):</b>  all clause	<b>Testing location:</b>  Staatliche Versuchsanstalt – TGM Elektrotechnik und Elektronik A-1200 Wien, Wexstrasse 19-23
<b>Summary of compliance with National Differences:</b> <b>List of countries addressed</b>  EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES see pages 35-36 /40  <input checked="" type="checkbox"/> The product fulfils the requirements of EN 60598-1:2015 and EN 60598-2-3: 2003+A1:2011	

**Copy of marking plate:**

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



<b>Test item particulars.....:</b>	
<b>Classification of installation and use.....:</b> Cl.I	
<b>Supply Connection .....</b> screw terminal	
<b>Possible test case verdicts:</b>	
- test case does not apply to the test object..... : N/A	
- test object does meet the requirement..... : P (Pass)	
- test object does not meet the requirement..... : F (Fail)	
<b>Testing.....:</b>	
<b>Date of receipt of test item .....</b> 2015-09-14	
<b>Date (s) of performance of tests .....</b> cw-41-51/2015	
<b>General remarks:</b>	
Distance d = 200mm: RG2, • Distance d ≥ 1,27m: RG1, • Distance d = „500Lux“ ≈ 2m: RG0	
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.	
Throughout this report a <input checked="" type="checkbox"/> comma / <input type="checkbox"/> point is used as the decimal separator.	
<b>Manufacturer's Declaration per sub-clause 4.2.5 of IEC60598-2:</b>	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided ..... :	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> Not applicable
<b>When differences exist; they shall be identified in the General product information section.</b>	
<b>Name and address of factory (ies)..... :</b> Schreder TOV Vul.Mykulynetska 468, 46000 Ternopil UKRAINE	
<b>General product information:</b> Luminaires for road and street lighting for installation on a pipe or on a mast arm. Body aluminium, protector Polycarbonate. LED Module and LED Driver. Means of connection: screw terminal	
<b>Power ratings ±5%</b>  The luminaire should be positioned so that prolonged staring into the luminaire at a distance closer than 1,27 m is not expected.	

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

<b>3.2 (0)</b>	<b>GENERAL TEST REQUIREMENTS</b>		<b>P</b>
3.2 (0.1)	Information for luminaire design considered .....	Standard Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
3.2 (0.3)	More sections applicable.....	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—

<b>3.4 (2)</b>	<b>CLASSIFICATION</b>		<b>P</b>
3.4 (2.2)	Type of protection .....	Class I	—
3.4 (2.3)	Degree of protection.....	IP 65	—
3.4 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces .....	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
3.4 (2.5)	Luminaire for normal use .....	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
	Luminaire for rough service .....	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—
3.4 (-)	Modes of installation of road or street lighting		—
	a) on a pipe	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
	b) on a mast arm	Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/>	—
	c) on a post top	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—
	d) on span or suspension wires	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—
	e) on a wall	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—

<b>3.5 (3)</b>	<b>MARKING</b>		<b>P</b>
3.5 (3.2)	Mandatory markings		<b>P</b>
	Position of the marking		<b>P</b>
	Format of symbols/text		<b>P</b>
3.5 (3.3)	Additional information		<b>P</b>
	Language of instructions		<b>P</b>
3.5 (3.3.1)	Combination luminaires		<b>N/A</b>
3.5 (3.3.2)	Nominal frequency in Hz		<b>P</b>
3.5 (3.3.3)	Operating temperature		<b>P</b>
3.5 (3.3.4)	Symbol or warning notice		<b>P</b>
3.5 (3.3.5)	Wiring diagram		<b>P</b>
3.5 (3.3.6)	Special conditions		<b>N/A</b>
3.5 (3.3.7)	Metal halide lamp luminaire – warning		<b>N/A</b>
3.5 (3.3.8)	Limitation for semi-luminaires		<b>N/A</b>
3.5 (3.3.9)	Power factor and supply current		<b>N/A</b>

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.5 (3.3.10)	Suitability for use indoors		N/A
3.5 (3.3.11)	Luminaires with remote control		N/A
3.5 (3.3.12)	Clip-mounted luminaire – warning		N/A
3.5 (3.3.13)	Specifications of protective shields		N/A
3.5 (3.3.14)	Symbol for nature of supply		N/A
3.5 (3.3.15)	Rated current of socket outlet		N/A
3.5 (3.3.16)	Rough service luminaire		N/A
3.5 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments	X	P
3.5 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
3.5 (3.3.19)	Protective conductor current in instruction if applicable		N/A
3.5 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
3.5 (3.3.21)	Non-replaceable and non-user replaceable light sources information provided		P
	Cautionary symbol		P
3.5 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
3.5 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P
3.5 (-)	Additional information in instruction leaflet		P
	a) Design attitude		P
	b) Weight		P
	c) Overall dimensions		P
	d) Maximum projected area if applicable		P
	e) Cross-sectional area of wires if applicable		P
	f) Suitability for indoors use		N/A
	g) Dimensions of the compartment		N/A
	h) Torque setting to be applied to bolts or screws		N/A
	i) Maximum mounting height		P
<b>3.6 (4)</b>	<b>CONSTRUCTION</b>		P
3.6 (4.2)	Components replaceable without difficulty		P

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.6 (4.3)	Wireways smooth and free from sharp edges		P
<b>3.6 (4.4)</b>	<b>Lampholders</b>	LED-MODULE	N/A
3.6 (4.4.1)	Integral lampholder		N/A
3.6 (4.4.2)	Wiring connection		P
3.6 (4.4.3)	Lampholder for end-to-end mounting		N/A
3.6 (4.4.4)	Positioning		N/A
	- pressure test (N) .....		—
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N) .....		—
	After test the lampholder have not moved from its position and show no permanent deformation		N/A
3.6 (4.4.5)	Peak pulse voltage		N/A
3.6 (4.4.6)	Centre contact		N/A
3.6 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
3.6 (4.4.8)	Lamp connectors		N/A
3.6 (4.4.9)	Caps and bases correctly used		N/A
3.6 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
<b>3.6 (4.5)</b>	<b>Starter holders</b>		N/A
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A
<b>3.6 (4.6)</b>	<b>Terminal blocks</b>		<b>N/A</b>
	Tails		N/A
	Unsecured blocks		N/A
<b>3.6 (4.7)</b>	<b>Terminals and supply connections</b>		P
3.6 (4.7.1)	Contact to metal parts		P
3.6 (4.7.2)	Test 8 mm live conductor		P
	Test 8 mm earth conductor		P
3.6 (4.7.3)	Terminals for supply conductors		N/A
3.6 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A



IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.8.2		N/A
	- electrical test according to 15.9		N/A
	- heat test according to 15.9.2.3 and 15.9.2.4		N/A
3.6 (4.7.4)	Terminals other than supply connection		P
3.6 (4.7.5)	Heat-resistant wiring/sleeves		N/A
3.6 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
<b>3.6 (4.8)</b>	<b>Switches</b>		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
<b>3.6 (4.9)</b>	<b>Insulating lining and sleeves</b>		N/A
3.6 (4.9.1)	Retainment		N/A
	Method of fixing .....		—
3.6 (4.9.2)	Insulated linings and sleeves:		N/A
	Resistant to a temperature > 20 °C to the wire temperature or		N/A
	a) & c) Insulation resistance and electric strength		N/A
	b) Ageing test. Temperature (°C).....		N/A
<b>3.6 (4.10)</b>	<b>Double or reinforced insulation</b>		N/A
3.6 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		N/A
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
	Interference suppression capacitors according to IEC 60384-14		N/A
3.6 (4.10.2)	Assembly gaps:		N/A
	- not coincidental		N/A
	- no straight access with test probe		N/A
3.6 (4.10.3)	Retainment of insulation:		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	- fixed		N/A
	- unable to be replaced; luminaire inoperative		N/A
	- sleeves retained in position		N/A
	- lining in lampholder		N/A
<b>3.6 (4.11)</b>	<b>Electrical connections and current-carrying parts</b>		<b>P</b>
3.6 (4.11.1)	Contact pressure		P
3.6 (4.11.2)	Screws:		P
	- self-tapping screws		N/A
	- thread-cutting screws		N/A
3.6 (4.11.3)	Screw locking:		P
	- spring washer		P
	- rivets		N/A
3.6 (4.11.4)	Material of current-carrying parts		P
3.6 (4.11.5)	No contact to wood or mounting surface		N/A
3.6 (4.11.6)	Electro-mechanical contact systems		N/A
<b>3.6 (4.12)</b>	<b>Screws and connections (mechanical) and glands</b>		<b>P</b>
3.6 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		N/A
	Torque test: torque (Nm); part..... :	1,8 Nm housing	P
	Torque test: torque (Nm); part..... :	0,5 Nm terminal	P
	Torque test: torque (Nm); part..... :	1,2 Nm earth terminal	P
	Torque test: torque (Nm); part..... :	0,5 Nm LED-Driver	P
	Torque test: torque (Nm); part..... :	1,2 Nm LED-Module	P
	Torque test: torque (Nm); part..... :	1,2 Nm housing	P
3.6 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
3.6 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm) .....		N/A
	- lampholder; torque (Nm) .....		N/A
	- push-button switches; torque 0,8 Nm .....		N/A
3.6 (4.12.5)	Screwed glands; force (Nm)..... :		N/A
<b>3.6 (4.13)</b>	<b>Mechanical strength</b>		<b>P</b>
3.6 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm) .....	0,5 Nm	P
	- other parts; energy (Nm)..... :	0,7 Nm	P

IEC 60598-2-3			
Clause	Requirement + Test		Verdict
	1) live parts		P
	2) linings		P
	3) protection		P
	4) covers		P
3.6 (4.13.3)	Straight test finger		P
3.6 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
3.6 (4.13.6)	Tumbling barrel		N/A
<b>3.6 (4.14)</b>	<b>Suspensions, fixings and means of adjusting</b>		<b>P</b>
3.6 (4.14.1)	Mechanical load:		P
	A) four times the weight	1,378kg + 4x1,378=6,890kg	P
	B) torque 2,5 Nm		P
	C) bracket arm; bending moment (Nm)..... :		N/A
	D) load track-mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm) .....		N/A
	Metal rod. diameter (mm) .....		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
3.6 (4.14.2)	Load to flexible cables		N/A
	Mass (kg) .....		—
	Stress in conductors (N/mm <sup>2</sup> ) .....		N/A
	Mass (kg) of semi-luminaire .....		—
	Bending moment (Nm) of semi-luminaire .....		N/A
3.6 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles..... :		N/A
	- strands broken .....		N/A
	- electric strength test afterwards		N/A
3.6 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
3.6 (4.14.5)	Guide pulleys		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.6 (4.14.6)	Strain on socket-outlets		N/A
<b>3.6 (4.15)</b>	<b>Flammable materials</b>		<b>P</b>
	- glow-wire test 650°C .....	See Test Table 3.15 (13.3.2)	P
	- spacing $\geq 30$ mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A
	- no fiercely burning material		P
	- thermal protection		N/A
	- electronic circuits exempted		N/A
3.6 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A
<b>3.6 (4.16)</b>	<b>Luminaires for mounting on normally flammable surfaces</b>		<b>P</b>
	No lamp control gear .....	(compliance with Section 12)	N/A
3.6 (4.16.1)	Lamp control gear spacing:		P
	- spacing 35 mm		P
	- spacing 10 mm		N/A
3.6 (4.16.2)	Thermal protection:		P
	- in lamp control gear		P
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
3.6 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
<b>3.6 (4.17)</b>	<b>Drain holes</b>		<b>N/A</b>
	Clearance at least 5 mm		N/A
<b>3.6 (4.18)</b>	<b>Resistance to corrosion</b>		<b>P</b>
3.6 (4.18.1)	- rust-resistance		P
3.6 (4.18.2)	- season cracking in copper		P
3.6 (4.18.3)	- corrosion of aluminium		P
3.6 (4.19)	Igniters compatible with ballast		N/A
3.6 (4.20)	Rough service vibration		N/A
<b>3.6 (4.21)</b>	<b>Protective shield</b>		<b>N/A</b>

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.6 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
3.6 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
3.6 (4.21.3)	No direct path		N/A
3.6 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment..... :	See Test Table 3.15 (13.3.2)	N/A
3.6 (4.22)	Attachments to lamps not cause overheating or damage		N/A
3.6 (4.23)	Semi-luminaires comply Class II		N/A
<b>3.6 (4.24)</b>	<b>Photobiological hazards</b>		<b>P</b>
3.6 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)	See Test Report MA 39-VFA 2016-0209.01/B2	P
3.6 (4.24.2)	Retinal blue light hazard RG0 with minimum distance "500Lux" 2,0m		P
	Luminaires with $E_{thr}$ :		P
	a) Fixed luminaires		P
	- distance x m, borderline between RG1 and RG2 .....	For RG2 distance 0,2m For RG1 minimum distance 1,27m	P
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
<b>3.6 (4.25)</b>	<b>Mechanical hazard</b>		<b>P</b>
	No sharp point or edges		P
<b>3.6 (4.26)</b>	<b>Short-circuit protection</b>		<b>N/A</b>
3.6 (4.26.1)	Adequate means of uninsulated accessible SELV parts		N/A
3.6 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
<b>3.6 (4.27)</b>	<b>Terminal blocks with integrated screwless earthing contacts</b>		<b>N/A</b>
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	After test, resistance < 0,05 $\Omega$		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 $\Omega$		N/A
	Voltage drop test, resistance < 0,05 $\Omega$		N/A
<b>3.6 (4.28)</b>	<b>Fixing of thermal sensing control</b>		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material (°C) ..... :		—
	100 cycles between t min and t max		N/A
	Temperature sensing control still in position		N/A
<b>3.6 (4.29)</b>	<b>Luminaires with non-replaceable light source</b>		<b>N/A</b>
	Not possible to replace light source		N/A
	Live part not accessible after parts have been opened by hand or tools		N/A
<b>3.6 (4.30)</b>	<b>Luminaires with non-user replaceable light source</b>		<b>P</b>
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		P
	Minimum two fixing means		P
<b>3.6 (4.31)</b>	<b>Insulation between circuits</b>		<b>P</b>
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
<b>3.6 (4.31.1)</b>	<b>SELV circuits</b>		<b>P</b>
	Used SELV source		P
	Voltage $\leq$ ELV		P
	Insulating of SELV circuits from LV supply		N/A
	Insulating of SELV circuits from other non SELV circuits		P
	Insulating of SELV circuits from FELV		N/A
	Insulating of SELV circuits from other SELV circuits		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	SELV circuits insulated from accessible parts according Table X.1		P
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
3.6 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage $\leq$ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets does not have protective conductor contact		N/A
3.6 (4.31.3)	Other circuits		P
	Other circuits insulated from accessible parts according Table X.1		P
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		P
	- test according 7.2.3 of above		P
	- conductive part not cause an electric shock in case of an insulation fault		P
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
3.6 (4.32)	<b>Overvoltage protective devices</b>		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.6.1 (-)	At least IP X3 or X5 respectively. IP .....	IP65	P
	Column-integrated luminaires:		P
	- parts below 2,5 m. IP .....		N/A
	- parts above 2,5 m. IP .....	IP65	P
3.6.2 (-)	Suspension on span wires		N/A
3.6.3 (-)	Means for attaching the luminaire or external parts to its support appropriate to the weight		N/A
3.6.3.1 (-)	Static load test		P
	- drag coefficient.....	1,225kg/m <sup>3</sup>	P
	- loaded area (m <sup>2</sup> ).....	0,0398m <sup>2</sup>	P
	- used load (N).....	59,237N	P
	- measured deformation (cm/m) .....	0,9cm/m	P
	- no rotation		P
3.6.4 (-)	Adjustable lampholders		N/A
3.6.5 (-)	Luminaires installed above 5 m, glass covers shall be:		N/A
	a) glass that fractures into small pieces (test according to 3.6.5.1), or		N/A
	b) glass having a high impact shock resistance (test according to 3.6.5.2), or		N/A
	c) protected by any means to retain glass fragments		N/A
	For tunnel luminaires 3.6.5.1 apply		N/A
	Method of protection declared by the manufacturer		N/A
3.6.5.1 (-)	Protection by the use of glass that fractures into small pieces		N/A
	- number of particles is more than 40.....		N/A
3.6.5.2 (-)	Protection by the use of high impact resistant glass		P
3.6.5.2.1 (-)	Glass covers have high mechanical strength	protector Polycarbonate	P
	Test according IEC 62262 with test apparatus according IEC 60068-2-75 with impact energy of 5J on preconditioned sample	IK08	P
3.6.5.2.2 (-)	Glass covers not break into large pieces		N/A
	- test according 3.6.5.1, number of particles is more than 20 .....		N/A
3.6.6 (-)	Connection compartment of column-integrated luminaire		N/A
	- provides adequate space		N/A
	- means for attachment		N/A
	- means for attachment of metal corrosion-resistant		N/A



IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.6.7 (-)	Compliance with ISO standard or other .....		N/A
3.6.8 (-)	Doors of column-integrated luminaires:		N/A
	- corrosion-resistant		N/A
	- opening only possible for an authorized person		N/A
	- impact test 5 Nm		N/A
	- sample show no damage		N/A
3.6.9 (-)	Column-integrated luminaire:		N/A
	- dimension of the cable entry slot (mm) .....		N/A
	- cable path from the slot to the connection compartment (mm) .....		N/A
	- cable path free from obstruction that might cause abrasion of the cable		N/A

<b>3.7 (11)</b>	<b>CREEPAGE DISTANCES AND CLEARANCES</b>		<b>P</b>
3.7 (11.2)	Creepage distances and clearances .....	See Table 3.7 (11.2)	P
	Working voltage (V) .....	100-240V	—
	Rated pulse voltage (kV) .....	2,5 kV	—
	Voltage form .....	Sinusoidal <input checked="" type="checkbox"/> Non-sinusoidal <input type="checkbox"/>	—
	PTI .....	< 600 <input checked="" type="checkbox"/> ≥ 600 <input type="checkbox"/>	—
	Impulse withstand category (Normal category II) (Category III Annex U)	Category II <input checked="" type="checkbox"/> Category III <input type="checkbox"/>	—

<b>3.8 (7)</b>	<b>PROVISION FOR EARTHING</b>		<b>P</b>
3.8 (7.2.1 + 7.2.3)	Accessible metal parts		P
	Metal parts in contact with supporting surface		P
	Resistance < 0,5 Ω .....	< 0,3 Ω	P
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a groove		N/A
	Earth makes contact first		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		P

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.8 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		P
3.8 (7.2.4)	Locking of clamping means		P
	Compliance with 4.7.3		P
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
3.8 (7.2.5)	Earth terminal integral part of connector socket		N/A
3.8 (7.2.6)	Earth terminal adjacent to mains terminals		P
3.8 (7.2.7)	Electrolytic corrosion of the earth terminal		N/A
3.8 (7.2.8)	Material of earth terminal		P
	Contact surface bare metal		P
3.8 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
3.8 (7.2.11)	Earthing core coloured green-yellow		P
	Length of earth conductor		N/A
3.8.1 (-)	Attachment prevented from rotation		N/A

<b>3.9 (14)</b>	<b>SCREW TERMINALS</b>		P
	Separately approved; component list..... :	(see Annex 1)	P
	Part of the luminaire .....	(see Annex 3)	N/A

<b>3.9 (15)</b>	<b>SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS</b>		N/A
	Separately approved; component list..... :	(see Annex 1)	N/A
	Part of the luminaire .....	(see Annex 4)	N/A

<b>3.10 (5)</b>	<b>EXTERNAL AND INTERNAL WIRING</b>		P
<b>3.10 (5.2)</b>	<b>Supply connection and external wiring</b>		<b>P</b>
3.10 (5.2.1)	Means of connection .....	screw terminal	P
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV $\leq 25$ V a.c./60 V d.c. or protected from outdoor environment		N/A
3.10 (5.2.2)	Type of cable..... :		N/A
	Nominal cross-sectional area (mm <sup>2</sup> ) .....		N/A
	Cables equal to IEC 60227 or IEC 60245		N/A
3.10 (5.2.3)	Type of attachment, X, Y or Z		N/A
3.10 (5.2.5)	Type Z not connected to screws		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.10 (5.2.6)	Cable entries:		P
	- suitable for introduction		P
	- adequate degree of protection		P
3.10 (5.2.7)	Cable entries through rigid material have rounded edges		P
3.10 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
3.10 (5.2.9)	Locking of screwed bushings		N/A
3.10 (5.2.10)	Cord anchorage:		P
	- covering protected from abrasion		P
	- clear how to be effective		P
	- no mechanical or thermal stress		P
	- no tying of cables into knots etc.		P
	- insulating material or lining		P
3.10 (5.2.10.1)	Cord anchorage for type X attachment:		P
	a) at least one part fixed		P
	b) types of cable		P
	c) no damaging of the cable		P
	d) whole cable can be mounted		P
	e) no touching of clamping screws		P
	f) metal screw not directly on cable		P
	g) replacement without special tool		P
	Glands not used as anchorage		P
	Labyrinth type anchorages		N/A
3.10 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		N/A
3.10 (5.2.10.3)	Tests:		P
	- impossible to push cable; unsafe		P
	- pull test: 25 times; pull (N) ..... : 80N		P
	- torque test: torque (Nm) ..... : 0,35 Nm		P

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	- displacement $\leq 2$ mm		P
	- no movement of conductors		P
	- no damage of cable or cord		P
	- function independent of electrical connection		P
3.10 (5.2.11)	External wiring passing into luminaire		N/A
3.10 (5.2.12)	Looping-in terminals		N/A
3.10 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A
3.10 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
3.10 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Other appliance inlet or connector according relevant IEC standard		N/A
3.10 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
3.10 (5.2.18)	Used plug in accordance with		N/A
	- IEC 60083		N/A
	- other standard		N/A
<b>3.10 (5.3)</b>	<b>Internal wiring</b>		<b>P</b>
3.10 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		N/A
	- not delivered/ mounting instruction		N/A
	- factory assembled		N/A
	- socket outlet loaded (A) .....		N/A
	- temperatures ..... : (see Annex 2)		P
	Green-yellow for earth only		P
3.10 (5.3.1.1)	Internal wiring connected directly to fixed wiring		N/A
	Cross-sectional area (mm <sup>2</sup> )..... : 0,75mm <sup>2</sup> and 1,5mm <sup>2</sup>		P

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	Insulation thickness		P
	Extra insulation added where necessary		N/A
3.10 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		P
	Adequate cross-sectional area and insulation thickness		P
3.10 (5.3.1.3)	Double or reinforced insulation for class II		N/A
3.10 (5.3.1.4)	Conductors without insulation		N/A
3.10 (5.3.1.5)	SELV current-carrying parts		P
3.10 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
3.10 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		N/A
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		N/A
	No twisting over 360°		N/A
3.10 (5.3.3)	Insulating bushings:		N/A
	- suitable fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- cables with protective sheath		N/A
3.10 (5.3.4)	Joints and junctions effectively insulated		N/A
3.10 (5.3.5)	Strain on internal wiring		N/A
3.10 (5.3.6)	Wire carriers		N/A
3.10 (5.3.7)	Wire ends not tinned		P
	Wire ends tinned: no cold flow		N/A
3.10.1 (-)	Cord anchorage if applicable		P
	- pull test: 25 times; pull (N) .....:	80 N	P
	- torque test: torque (Nm).....:	0,35 Nm	P
<b>3.11 (8)</b>	<b>PROTECTION AGAINST ELECTRIC SHOCK</b>		<b>P</b>
3.11 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		P
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		N/A
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement	LED-Module	P
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
3.11 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N/A
3.11 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible during starter or lamp replacement		N/A
	- basic insulation not accessible other than during starter or lamp replacement		N/A
	- glass protective shields not used as supplementary insulation		N/A
3.11 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N/A
3.11 (8.2.3.c)	SELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A
	- touch current .....		N/A
	- no-load voltage.....		N/A
	Other than ordinary luminaire:		N/A
	- nominal voltage .....		N/A
3.11 (8.2.4)	Portable luminaire have protection independent of supporting surface		N/A
3.11 (8.2.5)	Compliance with the standard test finger or relevant probe		N/A
3.11 (8.2.6)	Covers reliably secured		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.11 (8.2.7)	Discharging of capacitors $\geq 0,5 \mu\text{F}$		N/A
	Portable plug connected luminaire with capacitor		N/A
	Other plug connected luminaire with capacitor		N/A
	Discharge device on or within capacitor		N/A
	Discharge device mounted separately		N/A
<b>3.12 (12)</b>	<b>ENDURANCE TEST AND THERMAL TEST</b>		<b>P</b>
3.12.2 (-)	If IP > IP 20 relevant test of (12.4), (12.5) and (12.6) after (9.2) before (9.3) specified in 3.13		—
3.12 (12.3)	Endurance test:		<b>P</b>
	- mounting-position..... :	Acc. to mounting instruction	—
	- test temperature (°C) ..... :	50°C	—
	- total duration (h) ..... :	240h	—
	- supply voltage: Un factor; calculated voltage (V).... :	1,1 Un 264V	—
	- lamp used..... :	00-16-725 (Nichia 219C CW )	—
3.12 (12.3.2)	After endurance test:		<b>P</b>
	- no part unserviceable		<b>P</b>
	- luminaire not unsafe		<b>P</b>
	- no damage to track system		N/A
	- marking legible		<b>P</b>
	- no cracks, deformation etc.		<b>P</b>
3.12 (12.4)	Thermal test (normal operation)	(see Annex 2)	<b>P</b>
3.12 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N/A
3.12 (12.6)	Thermal test (failed lamp control gear condition):		N/A
3.12 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A) ..... :		—
	- case of abnormal conditions ..... :		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un ..... :		—
	- measured mounting surface temperature (°C) at 1,1 Un..... :		N/A
	- calculated mounting surface temperature (°C) ..... :		N/A
	- track-mounted luminaires		N/A

IEC 60598-2-3			
Clause	Requirement + Test		Verdict
3.12 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions .....		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C) .....		N/A
	- track-mounted luminaires		N/A
3.12 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
3.12 (12.7.1)	Luminaire without temperature sensing control		N/A
3.12 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N/A
	Test method 12.7.1.1 or Annex W .....		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions .....		—
	- Ballast failure at supply voltage (V) .....		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions .....		—
	- measured winding temperature (°C): at 1,1 Un .....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un .....		—
	- calculated temperature of fixing point/exposed part (°C) .....		—
	Ball-pressure test .....	See Table 3.15 (13.2.1)	N/A
3.12 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N/A
	- case of abnormal conditions .....		—
	- measured winding temperature (°C): at 1,1 Un .....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un .....		—
	- calculated temperature of fixing point/exposed part (°C) .....		—
	Ball-pressure test .....	See Table 3.15 (13.2.1)	N/A



IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.12 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N/A
	- case of abnormal conditions .....		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
3.12 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link .....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- manual reset cut-out .....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- auto reset cut-out .....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- case of abnormal conditions .....		—
	- highest measured temperature of fixing point/ exposed part (°C): .....		—
	Ball-pressure test: .....	See Table 3.15 (13.2.1)	N/A
3.12.1 (-)	Temperature reduction if for outdoor use only		N/A
3.12.2 (-)	(See above)		—
3.12.3 (-)	Glass covers used within the thermal limits declared by the glass manufacturer		N/A

<b>3.13 (9)</b>	<b>RESISTANCE TO DUST, SOLID OBJECTS AND MOISTURE</b>		<b>P</b>
3.13.1 (-)	If IP > IP 20 the order of tests as specified in clause 3.12		<b>P</b>
3.13 (9.2)	Tests for ingress of dust, solid objects and moisture:		—
	- classification according to IP .....	IP65	—
	- mounting position during test .....	Acc. to mounting instruction	—
	- fixing screws tightened; torque (Nm) .....	-	—
	- tests according to clauses .....	9.2.2 and 9.2.6	—
	- electric strength test afterwards		<b>P</b>
	a) no deposit in dust-proof luminaire		N/A
	b) no talcum in dust-tight luminaire		<b>P</b>
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	d) i) For luminaires without drain holes – no water entry		<b>P</b>
	d) ii) For luminaires with drain holes – no hazardous water entry		N/A
	e) no water in watertight luminaire		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	f) no contact with live parts (IP 2X)		N/A
	f) no entry into enclosure (IP 3X and IP 4X)		N/A
	f) no contact with live parts (IP3X and IP4X)		N/A
	g) no trace of water on part of lamp requiring protection from splashing water		N/A
	h) no damage of protective shield or glass envelope		P
3.13 (9.3)	Humidity test 48 h		P
<b>3.14 (10)</b>	<b>INSULATION RESISTANCE AND ELECTRIC STRENGTH</b>		<b>P</b>
3.14 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø .....		—
	Insulation resistance (MΩ) .....		—
	SELV		N/A
	- between current-carrying parts of different polarity :		N/A
	- between current-carrying parts and mounting surface..... :		N/A
	- between current-carrying parts and metal parts of the luminaire .....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N/A
	- Insulation bushings as described in Section 5 .....		N/A
	Other than SELV		P
	- between live parts of different polarity .....	>2,6 MΩ	P
	- between live parts and mounting surface .....	>2,6 MΩ	P
	- between live parts and metal parts .....	>2,6 MΩ	P
	- between live parts of different polarity through action of a switch..... :		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :	>2,6 MΩ	P
	- Insulation bushings as described in Section 5 .....	>2,6 MΩ	P
3.14 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
	Luminaires with manual ignitors		N/A
	Test voltage (V) .....		N/A
	SELV		N/A
	- between current-carrying parts of different polarity :		N/A
	- between current-carrying parts and mounting surface .....		N/A
	- between current-carrying parts and metal parts of the luminaire .....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....		N/A
	- Insulation bushings as described in Section 5 .....		P
	Other than SELV		P
	- between live parts of different polarity .....	1480V	P
	- between live parts and mounting surface .....	1480V	P
	- between live parts and metal parts .....	1480V	P
	- between live parts of different polarity through action of a switch .....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....	1480V	P
	- Insulation bushings as described in Section 5 .....	1480V	P
3.14 (10.3)	Touch current or protective conductor current (mA) :	0,212mA	P

<b>3.15 (13)</b>	<b>RESISTANCE TO HEAT, FIRE AND TRACKING</b>		<b>P</b>
3.15 (13.2.1)	Ball-pressure test .....	See Test Table 3.15 (13.2.1)	N/A
3.15 (13.3.1)	Needle-flame test (10 s) .....	See Test Table 3.15 (13.3.1)	N/A
3.15 (13.3.2)	Glow-wire test (650°C) .....	See Test Table 3.15 (13.3.2)	P
3.15 (13.4)	Proof tracking test (IEC 60112) .....	See Test Table 3.15 (13.4)	N/A

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

3.7 (11.2)	TABLES: Creepage distances and clearances						P	
Table 11.1	Minimum distances (mm) for a.c. (50/60 Hz) sinusoidal voltages							
RMS working voltage (V) not exceeding		50	150	250	500	750	1000	
Creepage distances								
Required basic insulation, PTI ≥ 600		0,6	0,8	1,5	3	4	5,5	
Measured				>3,25				
Required basic insulation, PTI < 600		1,2	1,6	2,5	5	8	10	
Measured								
Required supplementary insulation PTI ≥ 600		-	0,8	1,5	3	4	5,5	
Measured								
Required supplementary insulation PTI < 600		-	1,6	2,5	5	8	10	
Measured								
Required reinforced insulation		-	3,2	5	6	8	11	
Measured								
Clearances								
Required basic insulation		0,2	0,8	1,5	3	4	5,5	
Measured				>1,95				
Required supplementary insulation		-	0,8	1,5	3	4	5,5	
Measured								
Required reinforced insulation		-	1,6	3	6	8	11	
Measured								
Table 11.2	Minimum distances (mm) for non-sinusoidal pulse voltages						N/A	
Rated pulse voltage (peak kV)		2,0	2,5	3,0	4,0	5,0	6,0	8,0
Required clearances		1,0	1,5	2	3	4	5,5	8
Measured								
Rated pulse voltage (peak kV)		10	12	15	20	25	30	40
Required clearances		11	14	18	25	33	40	60
Measured								
Rated pulse voltage (peak kV)		50	60	80	100	-	-	-
Required clearances		75	90	130	170	-	-	-
Measured								

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
3.15 (13.2.1)	<b>TABLE: Ball Pressure Test of Thermoplastics</b>		N/A
<b>Allowed impression diameter (mm) .....</b>			—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)
Supplementary information:			

3.15 (13.3.1)	<b>TABLE: Needle-flame test (IEC 60695-11-5)</b>				N/A
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Supplementary information:					

3.15 (13.3.2)	<b>TABLE: Glow-wire test (IEC 60695-2-11)</b>				P
<b>Glow wire temperature .....</b>		650°C			—
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
protector polycarbonate	schreder	4 s	No	0	P
Any flame or glowing of the sample extinguished within 30 s of withdrawing the glow-wire, and any burning or molten drop did not ignite the underlying parts (Yes/No)..... :					yes
Supplementary information:					

3.15 (13.4)	<b>TABLE: Proof tracking test (IEC 60112)</b>				N/A
<b>Test voltage PTI .....</b>		175 V			—
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:					

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 1		TABLE: Critical components information				P
Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity <sup>1)</sup>
Internal wiring	A	Helukabel	H05VV-F	3x1,5 mm <sup>2</sup>	EN 50525	VDE
Varistor	A	Littelfuse	V275LA40AP (P275L40)	275V AC, 369V DC tc 85°C	IEC 60950	VDE (116895)
Fuse-	A	Littelfuse	.800	T 800mA , 250V	IEC/EN 60127	VDE
Terminal	A	Adels-Contact	500..	450V 0,75-2,5mm <sup>2</sup> T100°C	IEC/EN 60998	VDE
LED converter	B	Mean Well Enterprises Co. Ltd	PLD-25-1050	90-295 VAC 127-417V DC 25,2W tc:70°C Vout:35V	IEC/ EN 61347-2-13	ENEC 17
LED converter	B	Mean Well Enterprises Co. Ltd	PLD-16-700	90-295 VAC 127-417V DC 16,8W tc:70°C Vout:35V	IEC/ EN 61347-2-13	ENEC 17
Fuse-holder for miniature cartridge fuse	B	Adels-Contact	503 SI	400V 1,0-2,5mm <sup>2</sup> T100°C	IEC/EN 60127	VDE
LED-Module	C	Zollner Elektronik AG	Nichia 219C CW 00-16-725	Max 1050mA 19,2V	IEC/EN 62031	TGM VA EE 36464 SFT-2
LED	C	Nichia	NVSW219 CT	1050mA RG 2 at 500lux RG0	IEC/EN 62471 IEC /TR 62778	See Test Report MA 39-VFA 2016-0209.01/B2

Supplementary information:

<sup>1)</sup> Provided evidence ensures the agreed level of compliance. See OD-CB2039.

The codes above have the following meaning:

- A - The component is replaceable with another one, also certified, with equivalent characteristics
- B - The component is replaceable if authorised by the test house
- C - Integrated component tested together with the appliance
- D - Alternative component

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Temperature measurements, thermal tests of Section 12		P				
	Type reference ..... :	SKIDO	—				
	Lamp used..... :	00-16-725 (Nichia 219C CW )	—				
	Lamp control gear used..... :	PLD-25-1050	—				
	Mounting position of luminaire ..... :	mast arm mounting	—				
	Supply wattage (W) ..... :	22,3W	—				
	Supply current (A) ..... :	0,105A	—				
	Calculated power factor..... :	0,92	—				
	Table: measured temperatures corrected for ta = 50 °C:		P				
	- abnormal operating mode ..... :	--	—				
	- test 1: rated voltage..... :	240 V	—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage ..... :	1,06Un (254,4V)	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage ..... :	--	—				
	- test 4: 1,1 times rated voltage or 1,05 times rated wattage ..... :	--	—				
	Through wiring or looping-in wiring loaded by a current of A during the test ..... :	--	—				
Temperature measurements, (°C)							
Part	Ambient	Clause 12.4 – normal				Clause 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
LED Driver tc	50°C	65°C	N/A	N/A	70°C	N/A	N/A
Internal wiring	50°C	N/A	61°C	N/A	90°C	N/A	N/A
Internal wiring by LED-Module	50°C	N/A	62°C	N/A	90°C	N/A	N/A
external wiring	50°C	N/A	59°C	N/A	75°C	N/A	N/A
screw terminal	50°C	N/A	59°C	N/A	90°C	N/A	N/A
connector by LED Module	50°C	N/A	61°C	N/A	80°C	N/A	N/A
Supplementary information:							

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

<b>ANNEX 3</b>	<b>Screw terminals (part of the luminaire)</b>		N/A
<b>(14)</b>	<b>SCREW TERMINALS</b>		N/A
(14.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm <sup>2</sup> )..... :		—
(14.3.3)	Conductor space (mm)..... :		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread) ..... :	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm) ..... :		N/A
	Torque (Nm) ..... :		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N)..... :		N/A
(14.4.8)	Without undue damage		N/A

<b>ANNEX 4</b>	<b>Screwless terminals (part of the luminaire)</b>		N/A
<b>(15)</b>	<b>SCREWLESS TERMINALS</b>		N/A
(15.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A



IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5.1)	Terminals internal wiring		N/A
(15.5.1.1)	Pull test spring-type terminals (4 N, 4 samples) .....		N/A
(15.5.1.2)	Pull test pin or tab terminals (4 N, 4 samples) .....		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples) .....		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples) .....		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples) .....		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples) .....		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples) .....		N/A
(15.6)	Terminals external wiring		N/A
	Terminal size and rating		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N) .....		N/A
	Pull test pin or tab terminals (4 samples); pull (N) .....		N/A

IEC 60598-2-3										
Clause	Requirement + Test					Result - Remark				Verdict
(15.6.3.1)	TABLE: Contact resistance test									N/A
	Voltage drop (mV) after 1 h									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										N/A
	Voltage drop of two inseparable joints									N/A
	Voltage drop after 10th alt. 25th cycle									N/A
	Max. allowed voltage drop (mV) ..... :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										N/A
	Voltage drop after 50th alt. 100th cycle									N/A
	Max. allowed voltage drop (mV) ..... :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										N/A
	Continued ageing: voltage drop after 10th alt. 25th cycle									N/A
	Max. allowed voltage drop (mV) ..... :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										N/A
	Continued ageing: voltage drop after 50th alt. 100th cycle									N/A
	Max. allowed voltage drop (mV) ..... :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										N/A
										N/A
Supplementary information:										

+

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

<p align="center"><b>ATTACHMENT TO TEST REPORT IEC 60598-2-3</b>  <b>EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES</b>  Luminaires  Part 2: Particular requirements  Section 3: Luminaires for road and street lighting</p>			
<b>Differences according to</b> .....: EN 60598-2-3:2003 + A1:2011 used in conjunction with EN 60598-1:2015			
<b>Annex Form No.</b> ....: EU_GD_IEC60598_2_3J <b>Annex Form Originator</b> .....: OVE <b>Master Annex Form</b> .....: 2015-02			
<b>Copyright © 2015 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b>			

	<b>CENELEC COMMON MODIFICATIONS (EN)</b>	
--	--	--

<b>3.5 (3)</b>	<b>MARKING</b>		<b>P</b>
3.5 (3.3.101)	For luminaires not supplied with terminal block: Adequate warning on the package		P

<b>3.6 (4)</b>	<b>CONSTRUCTION</b>		<b>P</b>
<b>3.6 (4.11.6)</b>	Electro-mechanical contact systems		N/A

<b>3.10 (5)</b>	<b>EXTERNAL AND INTERNAL WIRING</b>		<b>P</b>
<b>3.10 (5.2.1)</b>	Connecting leads		P
	- without a means for connection to the supply		N/A
	- terminal block specified		N/A
	- relevant information provided		N/A
	- compliance with 4.6, 4.7.1, 4.7.2, 4.10.1, 11.2, 12 and 13.2 of Part 1		N/A
<b>3.10 (5.2.2)</b>	Cables equal to EN 50525		N/A
	Replace table 5.1 – Supply cord		N/A

<b>3.12 (12)</b>	<b>ENDURANCE TESTS AND THERMAL TESTS</b>		<b>P</b>
3.12 (12.4.2c)	Thermal test (normal operation) see footnote c to table 12.2 relating to unsleeved fixed wiring		P

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

<b>ZB</b>	<b>ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)</b>		N/A
(3.3)	DK: power supply cords of class I luminaires with label		N/A
(4.5.1)	DK: socket-outlets		N/A
(5.2.1)	CY, DK, FI, GB: type of plug		N/A

<b>ZC</b>	<b>ANNEX ZC, NATIONAL DEVIATIONS (EN)</b>		N/A
(4 & 5)	FR: Shuttered socket-outlets 10/16A		N/A
	FR: Safety requirements for high buildings  (Arrêté du 30 décembre 2011 portant règlement de sécurité pour la construction des immeubles de grande hauteur et leur protection contre les risques d'incendie et de panique; Section VIII; Article GH 48, Eclairage)  Glow-wire test for outer parts of luminaires:		N/A
	- 850°C for luminaires in stairways and horizontal travel paths		N/A
	- 650°C for indoor luminaires		N/A
	GB: Requirements according to United Kingdom Building Regulation		N/A

### Type List

Type	Input current at 230V 50Hz [A]	Luminaire max. power [W]	LED Current [mA]
<b>SKIDO</b> SKID 6L_700mA CW .... ....	0,07	15	700
<b>SKIDO</b> SKID 6L_1050mA CW .... ....	0,10	23	1050


IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict



IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict



IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict





IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

