# SRI TRANG GLOVES (THAILAND) PUBLIC COMPANY LIMITED

10 Soi 10 Phetkasem Rd., Hatyai, Songkhla, Thailand, 90110 Tel. (66) 074-344-663 Fax. (66) 074-344-677

SCT.PD.SP.05.035-220421 R.02 PRODUCT SPECIFICATION SHEET : LOOOGF-B-EU-M-NS DAR-SCT-2021-0539 PAGE 1 of 1

# GLOVE SPECIFICATION

Product Specification Group Code :	LOOOGF-B-EU-M-NS
Product Code :	DLOFBOG
Product name :	Latex Examination Gloves, Powder Free, Chlorinated, Non Sterile
Grade :	EU Spec, Medical Grade

### **GENERAL INFORMATION**

Single-us	Single-use disposable examination or protective glove					
Gloves are	Gloves are not marked to designated size.					
Ambidext	Ambidextrous					
Natural R	Natural Rubber					
Rolled cut	Rolled cuff					
Textured at Finger Tip						
STM D3578, ASTM D3767)	Finger : Min. 0.08mm	<b>Paim :</b> Min. 0.08mm				
Max. 2.0mg/glove	Force at break : (according to EN 455-2)	Before Aging : Med. ≥ 6.0N After Aging : Med. ≥ 6.0N				
Max. 50ug/g	<b>Tensile Strength :</b> (according to ASTM D3578, ASTM D412, ASTM D573)	Before Aging : Min. 18Mpa After Aging : Min. 14Mpa				
ength : ccording to EN 455-2) XS-XL : Med. ≥ 240mm		Before Aging : Min. 650% After Aging : Min. 500%				
	Gloves an Ambidext Natural Ri Rolled cur Textured STM D3578, ASTM D3767) Max. 2.0mg/glove Max. 50ug/g	Gloves are not marked to designated siz Ambidextrous Natural Rubber Rolled cuff Textured at Finger Tip STM D3578, ASTM D3767) Finger : Min. 0.08mm Max. 2.0mg/glove Force at break : (according to EN 455-2) Max. 50ug/g Tensile Strength : (according to ASTM D3578, ASTM D412, ASTM D573) % Elongation :				

Available Sizes & Paim width (mm): XS (5-6) : ≤ 80, S (6-7) : 80+/-10, M (7-8) : 95 +/-10, L (8-9) : 110+/-10, XL (9-10) : ≥ 110 (according to EN 455-2)

**Storage:** 3 years storage life (date of expiration see on the box). Keep area cool, dry and dust free, avoid ventilation and storage close to photocopy equipment. Copper-ions discolor the glove. Protect gloves against ultraviolet light sources, as sunlight and oxidizing agents. Storage above  $30^{\circ}$ C will lead to accelerated aging and should be avoided.

# STANDARDS, GUIDELINES AND QUALITY CERTIFICATION

(Every mentioned standard is used in the latest edition.)

Certification :	ISO 9001, ISO 13485	5			
Conformity to guidelines :	Medical Device Regulation (EU)2017/745 : Class I under Rule1 and Rule 5 according to Annex				
	VIII (Subject to EU Declaration of Conformity to brand owner)				
	Personal Protective Equipment Regulation (EU) 2016/425 : Category I or Category III (Subject				
	to EU Type-Examination Certificate)				
Conformity to standards :	Medical	PPE	PPE		
	EN 455	CATI	CAT III		
	ASTM D3578	EN 420	EN 420		
			EN 374		
			EN 16523-1		
Conformity to food regulation :	1935/2004	זי			

#### WARNING AND REPORTING SYSTEM

Potentially allergenic ingredients :

Dithiocarbamate type. (For further information, the actual version of the ingredients list is given on request.)

Please report any incidents with the products to **STGT\_TA@sritranggroup.com** and **regulatory@sritranggroup.com** without undue delay. Our Product Safety Officers will review all information provided and might contact the original informant for further clarification.

# SRI TRANG GLOVES (THAILAND) PUBLIC COMPANY LIMITED

10 Soi 10 Phetkasem Rd., Hatyai, Songkhla, Thailand, 90110 Tel. (66) 074-344-663 Fax. (66) 074-344-677

SCT.PD.SP.05.035-220421 R.02 PRODUCT SPECIFICATION SHEET : LOOOGF-B-EU-M-NS DAR-SCT-2021-0539 Appendix of specification

### **APPENDIX:2**

Product Specification Code :	LOOOGF-B-WHT-EU-MC-NS
Product Code :	DLOFBOG
Material :	Natural Rubber
Treatment and Feature :	Powder Free, Online Chlorinated

# SAMPLING, INSPECTION AND FINAL RELEASE INFORMATION

Product Specification Code	Glove color Ba	Characteristics			Test-Method
		Barrier Defects*	Major Visual Defects*	Minor Defects*	Test-Method
LOOOGF-B-WHT-EU-MC-NS	WHITE (PALE YELLOW)	AQL ≤ 1.5	AQL ≤ 1.5	AQL ≤ 4.0	EN 455-1

#### **Barrier Defects :**

Inspection level G I (ISO 2859-1)

Holes that results in the malfunction of glove as a protection barrier either physically or not physically affect the appearance.

#### Major Visual Defects :

Inspection level G I (ISO 2859-1) Defined defect that disrupt the glove's function or defect that cause an uncomfortable feeling to the user.

#### **Minor Defects :**

Inspection level G I (ISO 2859-1)

Visual defects aggregated are non-conformities of lower degree of concern, which do not prevent correct use of gloves. Minor cosmetic defect which does not affect on the glove's performance

#### Remark :

\* Defect Characteristics following In-house practice.