

**Specificații Tehnice pentru Lot nr. 1: Enterprise Server**

	Specificații Tehnice	Cantitatea
Type and name	<b>Enterprise Server Huawei FusionServer Pro 2288H V5</b>	8
Form Factor	2U rack server (2U Static Rail Kit included)	
Base Configuration	1X 2288H V5 (25*2.5inch HDD Chassis, With 2*GE and 2*10GE SFP+(Without Optical Transceiver)) H22H-05(For oversea); 2X PAC900S12-BE AC power supply unit; 1X SR230-M,Avago3004,M.2 RAID PCIE card-RAID0,1,JBOD,Support Sideband Management,PCIE 3.0 X8,No Cache,HH/HL; 2X M.2 SSD,SATA 6Gb/s-32GB,Hot-Swappable	
SKYLAKE CPU	2X Intel Xeon Gold 6132(2.6GHz/14-core/19.25MB/140W) Processor (with heatsink)	
Memory	6X DDR4 RDIMM Memory,32GB,2666MT/s,2Rank(2G*4bit),1.2V,ECC	
Hard Disk(with 2.5" Front Panel)-SAS	21X HDD,2400GB,SAS 12Gb/s,10K rpm,256MB,2.5inch(2.5inch Drive Bay)	
Hard Disk(with 2.5" Front Panel)-SSD	3X ES3600S V5 SSD,800GB SAS 12Gb/s,Mixed Use,2.5inch(2.5inch Drive Bay)	
RAID Card	1X SR530C-M 2G(LSI3108)SAS/SATA RAID Card,RAID0,1,5,6,10,50,60,2GB Cache,Support SuperCap and Out-of-Band Management; 1X LSI3108 2GB RAID controller supercap(8GB,with a cable and supercap tray),used for rack servers	
Riser Card	1X 3*x8 (x16 slot) Riser1 Module	
PCIe Card-NIC	2X Ethernet Adapter,10Gb Optical Interface(Intel 82599),2-Port,SFP+(with 2x Multi-mode Optical Transceiver),PCIe 2.0 x8	
Cable and Optical Module	8X Optical transceiver,SFP+,850nm,10Gb/s,-7.3~-1dBm,-9.9dBm,LC,MM,0.3km	
Warranty	Hi-Care Remote Support 2288/2288H V5_36Month(s)	
Certifications	CE, UL, FCC, CCC, and RoHS	

Semnat: \_\_\_\_\_ Numele, Prenumele: Victor Baciu În calitate de: Administrator  
Ofertantul: SC Rapid Link SRL Adresa: mun. Chisinau, MD-2028, str. Gh. Asachi 71/7