

OIL ADSORBER

Electronic

medical

chemical

Refinery

textile

food

Automotive

paint spraying

air tools

CNC machines

Coordinate measuring



Technical Specifications

Model	Login Its capacity @ 7 bars, 35 _{he} C	Connection	Max. Pressure barg	Dimensions mm		
	m ₃ /hour			A	B	C
MA 45	45	½"	12	220	220	740
MA 60	60	½"	12	220	220	990
MA 90	90	½"	12	220	220	1240
MA 110	110	½"	12	220	220	1440
MA 150	150	¾"	12	220	360	990
MA 200	210	one"	12	220	360	1210
MA 250	250	one"	12	220	360	1460
MA 300	300	1 ½"	12	320	360	1710
MA 450	450	1 ½"	12	490	360	1210
MA 600	600	1 ½"	12	490	360	1710
MA 900	900	2nd"	12	630	450	1710
MA 1200	1200	2nd"	12	770	450	1710

LOT 5

Capacity correction factor

pressure barg											
5	6	7	8	9	10	11th	12	13	14	15	16
0.75	0.89	one	1.08	1.26	1.31	1.36	1.49	1.62	1.71	1.79	1.90

Standard features

- Aluminum body
- Manometer

Optional additions

- Input filters :1 micron and 0.01 micron oil trap two-stage filtration :
- Output filter 0.01 micron particle trap filter.

Please contact our company for different working pressures and capacities.

Messa reserves the right to make changes in product specifications without prior notice.

