Pluski Safe 2

Safety I.V. Catheter with injection port and wings is designed with a Passive full automatic safety feature which covers the tip of the needle completely after use, hence protecting healthcare workers against the risk of needle stick injuries and related infections.



Key Features:

- Passive full automatic Safety System which cannot be bypassed.
- Self-activation tip cover technology for protection against needle stick injuries, which cannot be bypassed.
- Universal triple beveled back cut needle, which offer lower resistance during insertion, resulting in minimum trauma.
- Injection Port with non-return valve stops backflow of medicine after injection.
- Catheter tip is designed for a smooth cannulation experience, Radiopaque Stripes are also present for easy detection of catheter presence under X-Ray.

- DEHP / LATEX FREE.
- Gauge wise color coded port cap as per international standards.
- Quick Flash back confirm successful cannulation.
- Universal 6% taper for compatibility with any other standard medical device.

GAUGE	CATHETER LENGTH (MM)	CATHETER Ø (MM)	FLOW RATE (ML / MIN.)	UNIT PER BOX	ITEM CODE NO. (REF)		
					PTFE - R/O	FEP - R/O	PUR - R/O
18G	45	1.3	90	100	4041812152	4041812352	4041812552
20G	32	1.1	60	100	4042012152	4042012352	4042012552
22G	25	0.9	36	100	4042212152	4042212352	4042212552
24G	19	0.7	20	100	4042412152	4042412352	4042412552

