

Parameter	Reportable Range	Resolution	Measurement method	
pH (pH units)	6.5 – 8.0	0.001	Potentiometric sensor	
pO2 (mmHg)	10 – 700	0.1	Amperometric sensor	
pCO ₂ (mmHg)	10 – 150	0.1	Potentiometric sensor	
Na (mmol/L)	100 – 180	0.1	Potentiometric sensor	
K (mmol/L)	2.0 – 9.0	0.01	Potentiometric sensor	
Ca (mmol/L)	0.25 – 2.5	0.01	Potentiometric sensor	
CI (mmol/L)	65 – 140	0.1	Potentiometric sensor	
Glu (mg/dL or mmol/L)	20 - 700/1.1 - 38.9	1/0.1	Amperometric sensor	
Lac (mg/dL or mmol/L)	2.7 – 180.2/0.3 -20	0.1/0.01	Amperometric sensor	
Hct (%PCV or Fraction)	10 – 75 /0.10 – 0.75	1%/0.01	Conductance sensor	

Specification

Throughput	Results in 1 minute after sample aspiration				
Sample volume	140µІ / 80µІ				
Quality control	3 or 5 levels QC, External electronic simulator				
Display	7-inch color LCD Display, 800*480				
Interface	4 x USB 2.0 host, 1 x RS232, WLAN				
Input device	Touch screen and barcode scanner				
Power supply	100~240VAC, 50/60Hz				
Battery	5000mAh rechargeable lithium-ion battery, 50 samples continuous testing				
Dimensions (W*H*D)	238*153*310 mm				
Weight	3.65 KG				
Operation Environment	10 °C-31 °C; %RH: 25%-80%; 70 -106.6 KPa				

About Edan

Edan is a healthcare company dedicated to improving the human condition around the world by delivering value-driven, innovative and high-quality medical products and services. For over 20 years, Edan has been pioneering a comprehensive line of medical solutions that address a broad range of healthcare practices including:

- Diagnostic ECG
- Ultrasound Imaging
- In-Vitro Diagnostics

- Patient Monitoring
- Point-of-Care Testing
- Veterinary

• OB/GYN

Healthcare professionals around the world depend on Edan's breakthrough medical technologies and outstanding customer support.



Global Headquarters:

Edan Instruments, Inc. | 15 Jinhui Road, Pingshan District, Shenzhen 518122 P.R. China | +86.755.26898326 | www.edan.com | info@edan.com

U.S. and Canada inquiries:

EDAN Diagnostics, Inc. | 9918 Via Pasar, San Diego, CA 92126

+1.858.750.3066 | www.edandiagnostics.com | edan-info@edandiagnostics.com

© Edan Instruments, Inc. All rights reserved. Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



i15 Blood Gas and Chemistry Analyzer









Portable, lightweight

- Capable to run 50 samples with fully-charged battery
- · Diagnose at the point of care, patient side, out in the field or exam room

Easy, Quick and Convenient

- Zero maintenance
- Minimize hands on time and training requirement
- Auto-sampling
- Report is ready within one minute after sample aspiration

Accurate and Reliable

- · Innovative microchip liquid control technology and micro-sensor multifunction membrane technology
- High sensitivity and accuracyCalibrator, Control and Electronic simulator to TRIPLE guarantee the RESULTS!

- Flexible Data Management
 Acquire patients' information via barcode/QR code
- Up to 10,000 patient data storage
- 4 USB ports and LAN/WiFi for data management
- Optional data management software

Multi-parameter cartridge

- · Multi popular time-sensitive parameters come in one cartridge, including ABG, electrolytes and metabolites
- Single-use cartridge avoids contamination
- Room temperature storage with long shelf-life





i15 Quality Control System

Triple Guarantee the Result



Variety of test Cartridges

	рН	pCO ₂	pO ₂	Na	K	Cl	Ca	Hct	Glu	Lac
Microsample BG3/BG3										
Microsample BG8/BG8	_			_			_			
Microsample BG4/BG4										
Microsample BG9/BG9										
Microsample BG10/BG10										
Microsample BC4/BC4										

Calculated values: cH+, HCO3-act, HCO3-std, BE(ecf), BE(B), BB(B), ctCO2, sO2(est), Ca++(7.4), AnGap, tHb(est), pO2(A-a), pO2(a/A), RI, pO2/FIO2, cH+(T), pH(T), pCO2(T), pO2(T), pO2(A-a)(T), pO2(a/A)(T), RI(T), pO2(T)/FIO2, mOsm