

**DECLARATION OF PERFORMANCE N° 0003**  
**IZGRGL24**

1. Unique identification code of the product type: **Dry pressed ceramic tiles, with water absorption  $E_b \leq 0,5\%$ , glazed**

Reaction to fire	A1 <sub>FL</sub>
Breaking strength	
	Thickness $\geq 7,5$ mm > 1300 N
	Thickness < 7,5 mm > 700 N
Bond strength / adhesion	
- cementitious adhesive, Type C2:	$\geq 0,5$ N/mm <sup>2</sup>
Thermal shock resistance	Pass
Tactility	NPD
Durability	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
Slipperiness	See table

2. Intended use/es: **Internal and external floor and wall use**

3. Manufacturer: **IZIDA-1894 EOOD, 5, Slavyanska Str., Sofia 1000, Bulgaria,**  
[www.izida.eu](http://www.izida.eu)

4. System/s of AVCP: **System 4**

5. Harmonised standard: **EN 14411:2016**

6. Declared performance/s:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EC) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mr. Spas Toshev Shopov

