BMC 417 LIGHT TRUCK







CABIN

TYPE

Low Roof - Without Bed CAB SUSPENSION Mechanical AXLE CONFIGURATION

6X2

ENGINE

BRAND / MODEL

Cummins B4.0EVI E170

Turbo Intercooler Diesel NUMBER OF CYCLINDERS

DISPLACEMENT

3 956 L

MAX. POWER 168 PS (120 kW) @ 2400 rpm

TOROUE

600 Nm @ 1100-1800 rpm

TANKS

FUEL TANK CAPACITY (3845 WB)

ADBLUE TANK CAPACITY

GEAR BOX

BRAND / MODEL Eaton ESO-6106 (Manual) NUMBER OF GEARS

6 Forward, 1 Reverse GEAR RATIO

6,195:1; 0,775:1 (Reverse: 5,69:1) CLUTCH

362 mm [Single Disc]

SUSPENSION

FRONT AXLE

Leaf Spring, Telescopic Shock Absorbers REAR AXLE

Compensating Mechanism Leaf Spring,

Telescopic Shock Absorbers

ANTI-ROLL BAR

Front (1st) and Rear (2nd) Axle

SIZE / NUMBER

215 / 75 R 17.5, 6+1

RIMS

SIZE

6.0 J x 17.5

PERFORMANCE

TOP SPEED (LIMITED) (KM/H)

TURNING BADIUS (M)

3845 WB; 7.3

ELECTRICAL SYSTEM

BATTERIES

2 x 12 V / 92 Ah

ALTERNATOR

28 V, 90 A STARTER

24 V, 3,6 kW

STEERING SYSTEM

TYPE

Hydraulic

BRAKE SYSTEM

BRAKE SYSTEM TYPE Air brake, Disc brake, ABS, ESC, HSA, ASR, AEBS, LDWS

CHASIS

CHASSIS PROFILE

"C" Section

STANDARD ACCESSORIES

Digital Air Conditioner (Multimedia Control) Bluetooth, Radio/MP3 Player

MP5 Multimedia

Advanced Emergency Braking System (AEBS)

Lane Departure Warning System (LDWS)

Hill Start Assist (HSA) Electronic Stability Control (ESC)

Cruise Control

Digital and Analog Cluster

Central Locking System (Remote Control)
Tire Pressue Monitoring System (TPMS)

Power Steering Steering Wheel Control Buttons

Automatic Headlights

Daytime Running Lamps (LED)

Side Marker Lights

Fog Lights

Adjustable Headlights

Rear View Camera Rear Parking Sensor

Heated Exterior Mirrors

Electrically Controlled Windows

Fabric Seats 1 (Driver) + 2 (Passenger) Seat Configuration

Adjustable Driver's Seat

Hand-Lever Controlled Engine Brake

Safety Belt (3 Pcs)

Side Door Document's Area

Car Lighter, Ashtray

USB Charger

Sun Visor

Glove Box

Upper Shelves Inside the Cabin


Cup Holder

Tow Hook (Rear & Front)

Lockable Fuel Tank Cap Lockable AdBlue Tank Cap

PTO Preparation

Spare Tyre



• Axle-1: 1900 kg • Axle-2: 1170 kg • Axle-3: 600 kg

Full Load Weight: 16000 kg

• Axle-1: 3260 kg

• Axle-2: 6380 kg Axle-3: 6360 kg

BMC reserves the right to change the technical specifications of the products without prior notice.

BMC OTOMOTÍV SANAYÍ VE TÍCARET A.Ş.







