



| SIZE | STANDARD RIM | PLY RATING | LOAD INDEX SINGLE / DUAL | SPEED RATE | TREAD DEPTH (mm) | MAX LOAD (kg) | PRESSURE (kpa) |
|-----------|--------------|------------|--------------------------|------------|------------------|---------------|----------------|
| 7.50R16LT | 6.00H | 14PR | 122/118 | K | 14.5 | 1500/1320 | 770 |
| 8.25R16LT | 6.50H | 16PR | 128/124 | K | 15.0 | 1800/1600 | 770 |
| 8.25R20 | 6.50H | 16PR | 139/137 | K | 16.5 | 2430/2300 | 930 |
| 9.00R20 | 7.00 | 16PR | 144/142 | K | 16.5 | 2800/2650 | 900 |
| 10.00R20 | 7.50 | 18PR | 149/146 | K | 18.5 | 3250/3000 | 930 |
| 11.00R20 | 8.00 | 18PR | 152/149 | K | 20.5 | 3550/3250 | 930 |
| 12.00R20 | 8.50 | 18PR | 154/151 | J | 21.5 | 3750/3450 | 830 |
| | 8.50 | 20PR | 156/153 | J | 21.5 | 4000/3650 | 900 |
| 12R22.5 | 9.00 | 18PR | 152/149 | K | 22.0 | 3550/3250 | 930 |