



Approved Coolants

Coolant Specifications

The cooling system must be filled with a ready-mixed coolant containing antifreeze and corrosion-inhibiting additives.

Coolant identification

A sticker behind the grille states the information on the coolant used.



D001705

Approved Coolants

The table below lists the current suppliers that meet DAF specification 74002; the mixtures available are 40% glycol and 60% water and also 50% glycol and 50% water.

The cooling system must not be filled with coolants other than those specified in this overview.

Brand name	Supplier
DAF Xtreme Longlife Coolant	DAF Trucks N.V.
TRP Long Life Coolant	DAF Trucks N.V.
Havoline XLC	Arteco
DELO XLC Antifreeze / Coolant	Chevron / Texaco
Havoline Xtended Life Coolant	Chevron / Texaco
Caltex Extended Life Coolant	Caltex
Glacelf Auto Supra/Coolelf Auto Supra	Total
NIS a.d. Novi Sad	Nisotec Antifriz Long Life 100
Maxigel Plus/Ultracooling Plus	Renault Truck Oils
BP Procool	BP
Castrol Radicool SF Premix	Castrol
Castrol Radicool SF	Castrol
Inugel Optimal/Inugel Optimal Ultra	Motul
Yacco LR Organique	Yacco
Petrol Antifriz Koncentrat	Petrol
Protex Long Life/Coolmix LL	Orvema
Protex Long Life	Orvema
Coolmix LL -38	Orvema
Technocooling SMB	SMB Auto
York 718	York SAS
Coolant Maxmaster Truckcool	Platinum Oil Wielkopolskie Centrum Dystrybucji
OPET EXTENDED LIFE ANTIFREEZE	OPET FUCHS Madeni Yağ A.Ş.
Maintain Fricofin LL	Fuchs Europe Schmierstoffe GMBH

