

bScope

HIGHLIGHTS

- Provided with APL (Antimicrobial Protection Layer)
- Microscopes for research and laboratories
- Monocular, binocular and trinocular models
- Digital models available
- HWF 10x/20 mm eyepieces
- Reversed ball-bearied quadruple or quintuple nosepiece with slot for polarization filter
- E-plan, E-plan IOS and Plan IOS objectives
- Plan Phase IOS objectives
- Rackless integrated X-Y mechanical stage
- Color coded condenser
- 3 W NeoLED™ adjustable illumination system
- Integrated carrying grip
- Cable Storage System
- 10 Years warranty



● BS.1152-PLi

TECHNICAL SPECIFICATIONS

EYEPiece(S)

High wide field HWF 10x/20 mm secured eyepiece(s) with 20 mm field of view.
The eyepiece of monocular models is supplied with pointer

HEAD

- The bScope is available with a monocular head (45° inclined Ø 23.2 mm tube) or with a Siedentopf type head, 360° rotatable, with 30° inclined Ø 23.2 mm tubes
- Binocular and trinocular models are equipped with a diopter ± 5 adjustment on left eyepiece
- The interpupillary distance is adjustable between 48 to 76 mm
- The models equipped with plan infinity corrected PLi objectives have a unique swiveling system of the eyepiece tubes for ergonomic positioning of both tubes in a high (431 mm) and in a low position (377 mm)
- The trinocular head comes with a Ø 23.2 mm tube, ensuring a maximum of flexibility and has a fixed light path beam splitter (20:80) and generates an erect image
- Models with an integrated USB-2.0 camera are supplied with a 5.0 MP 1/2.5" CMOS sensor with a resolution of 2592 x 1944 pixels (see page 4)

NOSEPIECE

Revolving and reversed ball-bearing quadruple or quintuple nosepiece

OBJECTIVES - 45 MM PARFOCAL

The state-of-the-art production techniques and multi layer coatings used for the manufacturing of the bScope objectives enable the bScope to be used for the most demanding applications. World class spherical aberration correction and modern CNC and assembly technology ensure the perfect centering of the objectives

MONOCULAR MODEL BS.1151-XXX
BINOCULAR MODEL BS.1152-XXX
TRINOCULAR MODEL BS.1153-XXX

385 (h) x 195 (w) x 235 (d) | 6.3 kg
409 (h) x 195 (w) x 235 (d) | 6.5 kg
459 (h) x 195 (w) x 235 (d) | 6.6 kg

- Brightfield models: E-Plan, E-plan IOS infinity corrected, Plan IOS infinity corrected 4x/0.10, 10x/0.25, 20x/0.40, S40x/0.65, S60x/0.85 and S100x/1.25 oil immersion objectives
- Phase contrast models: Plan Phase IOS infinity corrected 10x/0.25, 20x/0.40, S40x/0.65 and S100x/1.25 oil immersion objectives
- Darkfield model: E-plan 4x/0.10, 10x/0.25, 20x/0.40, S40x/0.65, S60x/0.85 objectives. The S100x/1.25 oil immersion objective has a built-in iris diaphragm

All S40x, S60x and S100x oil immersion objectives are spring loaded. All optics are anti-fungus treated and anti-reflection coated for maximum light throughput

FOCUSING

Double coaxial, low-positioned coarse and fine adjustments with 180 graduations. Precision 1.11 μ m, 200 μ m per rotation, total travel range approximately 19 mm. Supplied with an adjustable rack stop to prevent damage to sample and objectives. The coarse adjustment is equipped with friction control

STAGE

- The bScope is equipped with a scratch resistant 152/197 x 131 mm stage with integrated 75 x 36 mm X-Y rackless mechanical stage, Vernier scale, soft-close removable specimen holder
- The rackless stage has no protruding parts, enables more smooth movements and is safer in use. Low-positioned X-Y control knobs prevent fatigue during long working sessions. The bScope can be equipped with a heating stage which can be set up to 50° Celsius by a PID temperature controller. Only available with newly purchased microscopes

CONDENSER FOR BRIGHTFIELD

The standard in height adjustable Abbe N.A. 1.25 condenser for brightfield comes with an iris diaphragm and swing-out filter holder. The condenser is color coded. Optionally available swing-out Abbe condenser (BS.9105)

ZERNIKE CONDENSER FOR PHASE CONTRAST

The in height adjustable Zernike NA. 1.25 phase contrast disc condenser comes with phase annuli for 10/20/S40x and S100x phase contrast objectives, an iris diaphragm, a swing-out filter holder and also a BF position for bright field contrast. Phase contrast objectives in PL-PHi phase contrast version. Supplied with alignment telescope and green filter

CONDENSER WITH SLIDER(S) FOR PHASE CONTRAST

The in height adjustable NA. 1.25 simple phase contrast condenser has a free slot for either a slider for 10/S40x phase contrast objectives or a slider for 20/S100x phase contrast objectives. The condenser has an iris diaphragm and filter holder. The condenser also includes a BF position for bright field contrast. Phase contrast objectives in PL-PHi version. Supplied with alignment telescope and green filter

CONDENSER FOR DARKFIELD

A state-of-the-art condenser equipped with reflective cardioid mirrors, with an integrated high powered 3 W LED light source. Together with a S100x objective with built-in iris diaphragm this forms a 1000x magnification darkfield solution. The power supply of the 3 W LED light source is built in the microscope. The darkfield condenser can easily be exchanged for a brightfield condenser which is also included

DARKFIELD EQUIPMENT

The BS.1153-EPL/DF is equipped with a darkfield oil immersion cardioid mirror condenser with a integrated 3 W LED illumination and a plan PL S100x oil immersion objective with built-in iris

POLARISATION

The bScope has an integrated slot above the nosepiece for an optional polarization filter

ILLUMINATION

The microscopes of the bScope are equipped with a 3 W NeoLED adjustable illumination system for increased light output and a 100-240 Vac integrated power supply. On request, rechargeable batteries are also available

NEOLED™ ILLUMINATION

The 3 W adjustable Köhler NeoLED diascopic illumination is powered by an internal 100-240 V power supply making it suitable for worldwide use. The innovative NeoLED design offers larger apertures, allowing the optical system of the bScope microscope to produce images at higher resolutions, very close to the theoretical diffraction limit of the optics. Other benefits of the NeoLED is the low energy consumption, no heating and a long operating lifetime

KÖHLER ILLUMINATION

A Köhler illumination ensures for all infinity corrected IOS models the highest possible contrast and the maximum achievable resolving power. It generates a uniform illumination of the sample and eliminates all interference from dust on lenses and side glare of the light source

The Köhler illumination is optional for non-IOS models

CORDLESS USE

The optional rechargeable AA batteries turn the bScope into a cordless system

CSS – CABLE STORAGE SYSTEM

Allows users to easily stow away excess cable length into the back of the instrument during operation and to roll up the power cable for easy storage

CARRYING GRIP

The integrated carrying grip at the back of the microscope ensures safe transportation of the microscope

ANTI-THEFT SLOT

At the back of the microscope a Kensington Security Slot is placed, which can be used to secure the instrument from theft

PACKAGE CONTENT

Smart Styrofoam packaging ensures a low environmental footprint while maintaining maximum safety during transport. Supplied with power cord, dust cover, tools, a spare fuse, white filter, user manual and 5 ml immersion oil

Phase contrast models are supplied with green filter and alignment telescope.

An optional aluminum case can be supplied

- Darkfield cardioid mirror condenser



APL (ANTIMICROBIAL PROTECTION LAYER)

Using the same technology already used extensively throughout the healthcare environment in wall coatings, patient lighting, air pressure stabilization and suction liners, APL prevents the growth of unwanted microbes that can cause degradation, discoloration, staining or odors of the Euromex microscopes



BSCOPE® FOR BRIGHTFIELD AND DARKFELD *

MODELS	Mono	Bino	Trino	HWF 10x/20 mm eyepieces	Quadruple nosepiece E-plan 4/10/S40/S100x	Quadruple nosepiece plan IOS 4/10/S40/S100x	Quintuple nosepiece E-plan IOS 4/10/S40/S100x	Quintuple nosepiece plan IOS 4/10/S40/S100x	Köhler NeoLED™	Neo-LED™	2-position swiveling ergo head
BS.1151-EPL	
BS.1152-EPL	
BS.1153-EPL	
BS.1153-EPL/DF*	
BS.1152-EPLi	
BS.1153-EPLi	
BS.1152-PLi	
BS.1153-PLi	
BS.1152-PLi/4N	
BS.1153-PLi/4N	

* BS.1153-EPL/DF model is equipped with a dark field oil immersion cardioïd mirror condenser and a S100x oil immersion objective with built-in iris diaphragm

AA Batteries are optional

Some models are also available as medical device, EU MDR 2017-745, contact your Euromex dealer

BSCOPE FOR PHASE CONTRAST

MODELS	Bino	Trino	HWF 10x/20 mm eyepieces	Quadruple nosepiece E-plan Phase 10/20/S40 S100x	Quintuple nosepiece E-plan Phase IOS 10/20/ S40 S100x	Quintuple nosepiece Plan Phase IOS 10/20/ S40 S100x	Köhler NeoLED™	NeoLED™	2-position swiveling ergo head
BS.1152-PLPhi	
BS.1153-PLPhi	

Rechargeable batteries is optional

All models are equipped with a 152/197 x 131 mm stage with integrated 75 x 36 mm X-Y rackless mechanical stage

These models are also available as medical device, EU MDR 2017-745, contact your Euromex dealer



● BS.1151-EPL



● BS.1153-PLPhi



● BS.1152-PLi



bScope digital

HIGHLIGHTS

- Binocular model
- Color coded condenser
- Integrated 5.0 MP CMOS color USB.2 camera
- 2592 x 1944 pixels
- 7 frames per second (2592 x 1944 pixels)
- 27 frames per second (1280 x 960 pixels)
- ImageFocus Alpha software
- 10 Years warranty (2 years on camera)



● BS.1157-PLi

TECHNICAL SPECIFICATIONS

CAMERA

The digital bScope microscopes are equipped with a 5.0 MP 1/2.5 inch CMOS USB-2.0 camera, 24 bits color depth, 7 frames per second (2592 x 1944 pixels) or 27 frames per second (1280 x 960 pixels). Dynamic range is 76 db and signal/noise ratio 41 db. Supplied with USB-2.0 cable and a micrometer 1mm/100 calibration slide

SOFTWARE

The capture and analysis ImageFocus Alpha software allows to save images in .jpg, .tif, .bmp or .dicom formats as well as .avi format videos. Measurements and annotations can be done on live or captured images. Compatible with Windows 10 and higher, both 32 and 64 bits configurations. A Mac OS version is also available. Free updates can be downloaded from our website

Further specifications are identical to the analog bScope® models

MODELS	Binocular head	HWF 10x/20 mm eyepieces	Quintuple nosepiece E-plan IOS 4/10/S40/S100x	Quintuple nosepiece plan IOS 4/10/S40/S100x	Köhler NeoLED™
BS.1157-EPLi	•	•	•	•	•
BS.1157-PLi	•	•	•	•	•

All models can optionally be supplied with three AA rechargeable batteries

ACCESSORIES AND SPARE PARTS

EYEPieces

BS.6010 HWF 10x/20 mm eyepiece, Ø 23.2 mm tube
BS.6010-P HWF 10x/20 mm eyepiece with pointer, Ø 23.2 mm tube
BS.6010-C HWF 10x/20 mm eyepiece with crosshairs, Ø 23.2 mm tube
BS.6010-CM HWF 10x/20 mm eyepiece with 10/100 micrometer and crosshairs
BS.6012 WF 12.5x/14 mm eyepiece
BS.6015 WF 15x/11 mm eyepiece
BS.6020 WF 20x/11 mm eyepiece
BS.6099 Pair of eyecups

OBJECTIVES - 45 MM PARFOCAL

BS.7104 E-plan EPL 4x/0.10 objective. WD 37.0 mm
BS.7110 E-plan EPL 10x/0.25 objective. WD 6.61 mm
BS.7120 E-plan EPL 20x/0.40 objective. WD 1.85 mm
BS.7140 E-plan EPL S40x/0.65 objective. WD 0.64 mm
BS.7160 E-plan EPL S60x/0.85 objective. WD 0.20 mm
BS.7100 E-plan EPL S100x/1.25 oil immersion objective. WD 0.19 mm
86.521 Plan PL S100x/1.25 oil immersion objective with built-in iris diaphragm. Working distance 0.33 mm



BS.8204	E-plan EPLI 4x/0.10 infinity corrected IOS objective. WD 18.9 mm
BS.8210	E-plan EPLI 10x/0.25 infinity corrected IOS objective. WD 5.95 mm
BS.8220	E-plan EPLI 20x/0.40 infinity corrected IOS objective. WD 2.61 mm
BS.8240	E-plan EPLI S40x/0.65 infinity corrected IOS objective. WD 0.78 mm
BS.8200	E-plan EPLI S100x/1.25 oil immersion infinity corrected IOS objective. WD 0.36 mm
BS.8404	Plan PLi 4x/0.10 infinity corrected IOS objective. WD 21.0 mm
BS.8410	Plan PLi 10x/0.25 infinity corrected IOS objective. WD 5.0 mm
BS.8420	Plan PLi 20x/0.40 infinity corrected IOS objective. WD 8.8 mm
BS.8440	Plan PLi S40x/0.65 infinity corrected IOS objective. WD 0.66 mm
BS.8460	Plan PLi S60x/0.80 infinity corrected IOS objective. WD 0.46 mm
BS.8400	Plan PLi S100x/1.25 oil immersion infinity corrected IOS objective. WD 0.36 mm
BS.8710	Plan Phase PLPHi 10x/0.25 infinity corrected IOS objective. WD 5.00 mm
BS.8720	Plan Phase PLPHi 20x/0.40 infinity corrected IOS objective. WD 8.80 mm
BS.8740	Plan Phase PLPHi S40x/0.65 infinity corrected IOS objective. WD 0.66 mm
BS.8700	Plan Phase PLPHi S100x/1.25 oil immersion infinity corrected IOS objective. WD 0.36 mm

CONDENSERS AND ACCESSORIES

BS.9102	Abbe condenser 1,25 NA with slot for darkfield and phase contrast sliders. Without darkfield slider and without phase contrast slider
BS.9170	Darkfield stop for BS.9102 condenser
BS.9105	Swing-out Abbe condenser 0.9/1.25 NA

PHASE CONTRAST ACCESSORIES

BS.9123	Zernike phase contrast kit with plan PLPH 10/20/S40 and S100 oil phase contrast objectives, Zernike rotating condenser, telescope and green filter
BS.9126	Zernike phase contrast kit with plan PLPHi 10/20/S40 and S100 oil phase contrast IOS infinity corrected objectives, Zernike rotating condenser, telescope and green filter
BS.9164	Phase contrast kit with Abbe condenser with slot for slider. Plan PLPHi phase S40x contrast objectives, slider with 40x annuli only, telescope and green filter
BS.9194	Slider with phase contrast annuli 40x. Needs BS.9102 condenser with slot
BS.9148	Alignment telescope for bScope IOS version with 30 mm tubes
BS.9149	Alignment telescope for bScope non IOS version with 23.2 mm tubes
BS.9162	Phase contrast kit with Abbe condenser with slot for slider. Plan PLPHi 10/S40x phase contrast infinity corrected objectives, slider with 10 and 40x annuli, telescope and green filter
BS.9163	Phase contrast kit with Abbe condenser with slot for slider. Plan PLPHi 20/S100x phase contrast infinity corrected objectives, slider with 20 and 100x annuli, telescope and green filter

POLARIZATION ATTACHMENTS

BS.9647	Polarization polarizer 16 mm diameter for slider under bScope head
BS.9651	Polarization attachment for lamphouse of bScope with 360° scale
BS.9660	Polarization kit: analyzer under head and polarizer on lamphouse
AE.5152-N	Small rotatable stage to be used with BS.9660

CAMERA ACCESSORIES

AE.5130 Universal Ø 23.2 mm tube adapter with built-in 2x lens for SLR photo camera with APS-C sensor. Needs T2 adapter

AE.5025 T2 ring for Nikon D SLR digital camera

AE.5040 T2 ring for Canon EOS SLR digital camera

MISCELLANEOUS

BS.9577-L Add-on for left handed mechanical stage (only with new purchased microscope)

BS.9870 Mirror attachment for bScope

BS.9880 Köhler attachment for bScope

BS.9900 Aluminum transport case for bScope

AE.9919 Nylon microscope bag XL, 58 (h) x 32 (w) x 24 (d)

AE.9916 Dust cover XL

BS.9993 NeoLED™ replacement unit

AE.1370 Set rechargeable batteries

AE.5226 Glass fuses 3A 250V, 10pcs

DISPOSABLES

PB.5155 Microscope slides 76 x 26 mm, ground edges, 50 pieces

PB.5157-W Microscope slides 76 x 26 mm, ground edges and frosted side white color, 50 pieces per pack

PB.5157-B Microscope slides 76 x 26 mm, ground edges and frosted side blue color, 50 pieces per pack

PB.5160 Microscope slides 76 x 26 mm with cavity, ground edges. 10 pieces per pack

PB.5165 Cover glasses 18 x 18 mm, 0.13-0.17 mm, 100 pieces

PB.5168 Cover glasses 22 x 22 mm, 0.13-0.17 mm, 100 pieces

PB.5245 Lens cleaning paper, 100 sheets per pack

PB.5255 Immersion oil, 25 ml. Refraction index $n = 1.515$

PB.5274 Iso propyl alcohol 99%, 200 ml

PB.5275 Cleaning kit: lens fluid, lint free lens tissue/paper, brush, air blower, cotton swabs

PB.5276 Microscope maintenance and servicing kit, 16pcs: cleaning brush, 6 pcs screwdriver set, air blower, 3 pcs Allen key, 1.5, 2, 2.5 mm, lens cleaning fluid 20 ml, cleaning cloth 140 x 140 mm, 100 pcs Lens tissue sheets, tube of maintenance grease, 10 ml bottle of oil, packed in a nice toolbox



● AE.9916



AE.9919 ●



● BS.1153-PLi
with camera

