www.lumed.com





DESCRIPTION

MANUFACTURER

LUMED "EUROCATCH" disposable electrodes are pre-gelled (single-use) and have a silver/silver chloride sensor. All adhesive foams and types used are equipped with a hypoallergenic medical-grade adhesive that is non-irritating to the skin.

| troams and types used are equipped with a hypoanergenic medical-grade adhesive that is non-inflating to the skin. | | | | | | | |
|---|-----------|--------|-----------|---------------|------------|--------------------|--|
| REFERENCE | MATERIAL | SHAPE | GEL TYPE | Usability | DIMENSIONS | PER POUCH/BOX/CASE | |
| €T1119 | FOAM | ROUND | WET | HOLTER/STRESS | 50 mm | 50/400/4800 pcs | |
| €T1136€ | FOAM | OVAL | WET | 48 hours | 32 x 50 mm | 50/500/6000 pcs | |
| €T1166 | FOAM | SQUARE | WET | 48 hours | 32 x 32 mm | 50/500/6000 pcs | |
| Technical features | | | | | | | |
| acz impedanc | .∈ @10 Hz | | < 300 Ohm | | | | |
| acz impedance repeat | | | < 150 Ohm | | | | |
| DC OFFSET VO | LTAGE | | | < 1 mV | | | |
| COIIN | | | | 22 uV | | | |

| < 1 mV | | |
|--|--|--|
| 22 μV | | |
| < 0.2 mV/sec | | |
| < 1.7 mV | | |
| Medical grade pressure sensitive adhesive | | |
| Glass-filled ABS - Ag/AgCl Coated | | |
| Stainless Steel | | |
| Directive 93/42/EEC and amendments. Class I medical device | | |
| Italian Medical Device Data Standard Registration: | | |
| 239855/R; CND: C020501; GMDN: 35035 | | |
| *Non-Active Medical Device* | | |
| | | |

PRODUCT SHELF LIFE 36 Months

LUMED srl

Technical data sheet ETnnnn Rev. 2.0 of 04/05/2021