



JOINT-STOCK COMPANY
THE TRANSNATIONAL FINANCE AND PRODUCTION PETROLEUM COMPANY «UKRTATNAFTA»
3 Svishtovska Str., Kremenchuk, Poltava region, 39610, Ukraine
ID Code in the Unified State Register of Enterprises and Organizations of Ukraine 00152307



Testing center of JSC "UKRTATNAFTA"
QUALITY CERTIFICATE No.8
dated «23» April, 2026
AVIATION TURBINE FUEL JET A-1
DSTU 4796:2007



20342
Випробування

Certificate of conformity No. UA.056.II.00121-25,
issued by the conformity assessment body of SE "Poltavastandartmetrologiya", valid from 22.04.2025 to 21.04.2027

The name of the additive	Contents, mg/dm ³
Electrical Conductivity Improver Stadis 450	0,8
Antioxidants Agidol-1:	
hydrotreated component	20
no hydrotreated component	did not add

Manufacturing plant **JSC "UKRTATNAFTA"**
Date of production **22.04.2026**
Tank No. **791** Level of filling, (cm) **705** Quantity, (t) **5195**
Date of sampling **22.04.2026** Date of laboratory testing **23.04.2026**

Property	Norm according to the regulatory document	Test Result	Test Method
1 Acidity, total mg KOH/g, max	0,10	0,013	according to ASTM D 3242
2 Aromatics, %, max			
- percent by mass	28	22	according to GOST 6994-74
- percent by volume	25	19,2	according to ASTM D1319
3 Sulfur, mercaptan, percent by mass, %, max	0,003	0,0010	according to ASTM D3227
4 Sulfur, total percent by mass, %, max	0,30	0,0208	according to ASTM D4294
5 Distillation:			according to ASTM D86
10 % recovered, temperature, °C, max	205	173,0	
50 % recovered, temperature, °C	Not regulated	187,0	
90 % recovered, temperature, °C	The definition is mandatory		
final boiling point, °C, max.	»	219,0	
distillation residue, %, max	300	249,0	
distillation loss, %, max	1,5	1,2	
	1,5	0,3	
6 Flash point, °C, min	36	48,0	according to GOST 6356-75
7 Density, kg/m ³ , within the range of			
- at 20 °C	770 - 840	797,9	according to GOST 3900-85
- at 15 °C	775 - 840	801,5	according to ASTM D1298
8 Freezing point, °C, max	minus 47	minus 59	according to ASTM D2386
9 Viscosity, mm ² /s:			according to ASTM D445
- at minus 20 °C, max	8,0	3,460	
- at 20 °C, min	1,25	1,529	
10 Net heat of combustion, MJ/kg, min	42,8	43,126	according to ASTM D 4809
11 One of the following requirements shall be met: smoke point, mm, min	25		according to ASTM D1322
or smoke point, mm min(naphthalenes, vol, no more than 3 %)	19	25,6	
naphthalenes, vol, max	3	0,75	according to ASTM D1840
12 Copper strip corrosion (2 h ± 5 m at 100 °C), rating, no more	No. 1	1a	according to ASTM D130
13 Thermal stability (2,5 h at control temperature of 260 °C min)			according to ASTM D3241
- filter pressure drop, kPa (mm Hg), max	3,3 (25)	0,0 (0)	
- annex A1 VTR, VTR Color Code, max	3	1	
	(no peacock or abnormal color deposits)		
- amount of sediment, mg/100 cm ³ , max	12	8,5	according to GOST 11802-88
14 Existent gum content, mg/100 cm ³ , max	7	1,9	according to ASTM D381
15 Microseparometer :			
a) assessment of interfaces, max	1	1	according to ASTM D1094
b) With electrical conductivity additive, min	70	91	according to ASTM D3948
16 Electrical conductivity, pS/m, within the range of	50 - 450	86	according to ASTM D2624
17 Lubricity (wear spot diameter), mm, max *	0,85	not determined	according to ASTM D5001

Aviation turbine fuel Jet A-1 clean, transparent and free of water, sediment and cloudy particles.

* The indicator 17 was not indicated on the base of footnote 5 before the table DSTU 4796:2007. Aviation turbine fuel Jet A-1 contains no more than 95% hydrotreated component

GOST 6994-74, GOST 11802-88 is not valid in Ukraine.

The warranty period of fuel storage is 5 years from the date of its manufacture.

Conclusion: as per the sample test results, AVIATION TURBINE FUEL JET A-1 meets the requirements of DSTU 4796:2007

Head of Central Laboratory – Head of Technical Control Department

O.V. Zinchenko

