



COMBINATUL DE CIMENT DIN RIBNITA  
S.A.T.I. Republica Moldova  
Municipiul Ribnita, Str. P.Zaporojta, Nr. 1

# Certificat de calitate

(aerian, nehidratat, calcic, concasat)

Certificat de conformitate № ГОСТ ПМП.АО.41.25 10 57.26333

Сертифікат відповідності № UA.033.0319-20

GOST 9179-77 «Var industrial. Conditii tehnice».  
GOST 22688-77 «Var industrial. Incercari de laborator».  
ДСТУ Б.В.2.7-90:2011

Caracteristicile esentiale chimice si fizice a varului industrial:

| Caracteristicile esentiale chimice si fizice                           | Един.<br>измер. | Performata |
|------------------------------------------------------------------------|-----------------|------------|
| CaO + MgO                                                              | %               | 92,5       |
| CO <sub>2</sub>                                                        | %               | 1,5        |
| Reziduu la stingere                                                    | %               | 1,1        |
| Apa hidrata                                                            | %               | 0,85       |
| Timpul de stingere                                                     | min             | 2          |
| Temperatura de stingere                                                | °C              | 90         |
| Uniformitatea modificării volumului                                    |                 | corespunde |
| Activitatea efectivă specifică a radionuclizilor naturali              | Bq/ kg          | 80,4       |
| Termen de valabilitate garantat de la data expedierii către consumator | zile            | 30         |
| Var industrial (aerian, nehidratat, calcic, concasat) corespunde:      |                 | I grad     |

Sef Laboratorie

S. Bespalico

