

CE   RoHS

Color

RAL 9006

Electrical

Input power	15 W
Input voltage	220 - 240 V
Frequency	50 - 60 Hz
Power factor	0.99
Inrush current	11 A / 220 µs

Optical


Optic name	L04
Optic type	TYPE-II
Luminous flux	1954 lm ±10%
Luminous efficacy	130 lm/W
Performance temperature Tq	+25 °C
Constant light output	No
Color rendering index	>70
Color temperature	4000 K
Color tolerance	5 SDCM
ULOR	0
LED quantity	4

Lifetime

Lumen depreciation	L90 after 100 000 h
Warranty	5 years
Ambient temperature range	-40 ... +50 °C


Protection	Protection class	Class I
	Surge protection L-N	12 kV
	Surge protection L/N-PE	12 kV
	LED module thermal protection w/ NTC	No
	Ingress protection	IP66
	Impact resistance	IK08
Housing	Body material	Die-cast aluminium
	Cover material	Flat tempered glass
	Optic material	PMMA
	Color	RAL 9006 (white aluminium)
	Dimensions	517 x 170 x 96 mm
	Max wind load area SCd	0.04 m ²
	Mounting	Post top / side-entry, 60 mm
	LED module replaceability	Replaceable by a professional
	Driver replaceability	Replaceable by a professional
Controls	Accessibility of electronic components	Tool-less
	Dimming	No dimming
Approvals	CE	Yes
	ENEC	Yes
	ENEC+	Yes
	RoHS	Yes

Light distribution



Dimensions

A x B x C (mm): 517 x 170 x 96



Product images

