

# imageRUNNER 1643iF/1643i 1643P

# imageRUNNER 1643 Series

# Black-and-White | Compact | User-Friendly

Print up to 45 ppm (BW)

Scan in color and black and white

Print up to 8-1/2" x 14"

2,300-sheet maximum paper capacity

Small businesses and corporate workgroups depend on solutions that help maximize resources, boost productivity, and are easy to manage. The cost-efficient imageRUNNER 1643 Series can do all that, and more. With fast output, scanning, faxing,<sup>1</sup> and high reliability, the imageRUNNER 1643iF/1643i multifunction devices help you accomplish a lot in a small space. The imageRUNNER 1643P printer model offers fast and reliable printing.



# WORKFLOW EFFICIENCY

Whether you're a small business or part of a workgroup, the imageRUNNER 1643iF/1643i models can help boost operational efficiency. Scan and email documents or conveniently scan to/print from a USB memory stick. The ID Card Copy feature easily copies two-sided cards onto the same page. Extend your document management capabilities when you scan using the standard PDF (OCR) format. Mobile workers can print from compatible mobile devices. Application Library provides users with a unique, customized device experience.



# SECURITY

Safeguard information with the imageRUNNER 1643iF/1643i models' security features. Canon's uniFLOW solution lets users securely retrieve documents from a networked device after authentication. Standard security features include the ability to send encrypted PDFs and add a digital device signature to PDF files. These models also include technology to verify that the device, firmware, and applications initialize without tampering. TX Archiving automatically forwards a copy of a fax to an administrator-defined destination.<sup>1</sup> And with no hard disks in these models, confidential information is not stored locally on the device.



# QUALITY AND RELIABILITY

With a first-copy-out time as fast as 6.3 seconds and output up to 45 ppm, the imageRUNNER 1643 Series is a quick performer. Scan documents in black and white and color to email addresses or networked locations. The 5" intuitive, color touchscreen display<sup>2</sup> has smartphone-like usability. The standard 650-sheet capacity can be increased to 2,300 sheets to handle many jobs without interruption.





# FLEET MANAGEMENT

An ideal replacement for single-function printers or older models, the imageRUNNER 1643 Series can easily integrate into your network of Canon devices to help streamline and simplify management and maintenance. Even receive alerts when supplies or service calls are needed with imageWARE Enterprise Management Console and plug-ins.




# EFFICIENT PERFORMANCE

Designed with your bottom line in mind, the Canon imageRUNNER 1643 Series helps minimize costs and maximize reliability while the robust design helps ensure dependable operation. Canon's uniFLOW\* software can help control costs by managing, tracking, and charging back usage. And simple-to-replace, high-yield consumables help keep work moving while achieving a low cost per page.



The imageRUNNER 1643 Series is ENERGY STAR\* certified and has a low TEC (Total Energy Consumption) rating. Rated EPEAT\* Silver,<sup>3</sup> these models follow Canon's stringent Green Procurement policy and environmental commitments.



# Main Unit

# Туре 1643P:

1643iF/1643i: Monochrome Laser Multifunctional Monochrome Laser Printer

### **Core Functions**

1643iF: Print, Copy, Scan, Send, Fax 1643i: Print, Copy, Scan, Send 1643P: Print

### Processor

Canon Dual Custom Processor<sup>2</sup> (Shared)

### **Operation Panel**

5" TFT LCD WVGA Color Touch Panel 5-Line LCD Panel

Memory

1.0 GB RAM

## Interface Connection<sup>4</sup>

1643iF/1643i: 1000Base-T/100Base-TX/10- Base-T, Wireless LAN (IEEE 802.11 b/g/n), NFC, <sup>1</sup> Wi-Fi Direct Connection 1643P: 1000Base-T/100Base-TX/10-Base-T
1643iF/1643i: USB 2.0 (Host) x2, USB 2.0 (Device) x1 1643P: USB 2.0 (Host) x3, USB 2.0 (Device) x1
<b>(LTR, 20 lb. Bond)</b> 550-sheet Paper Cassette,

	100-sheet Stack Bypass
Optional:	550-sheet PAPER FEEDER PF-C1 (up to
Maximum:	2 300 Sheets

### Paper Output Capacity (LTR, 20 lb. Bond)

150 Sheets Maximum:

### Supported Media Sizes

Ca

Βv

assette:	Letter, Legal, Statement, Executive
/pass:	Letter, Legal, Statement, Executive,
	Custom size (3" x 5" to 8-1/2" x 14"),
	Envelope (C5/DL/ COM-10/Monarch)

### Supported Media Weights

Cassette:	16 lb. Bond to 32 lb. Bond (60 to 120 g/m <sup>2</sup> )
Bypass:	16 lb. Bond to 73 lb. Cover (60 to $199 \text{ g/m}^2$ )

### Copy Speed<sup>2</sup>/Print Speed

Up to 45 ppm (Letter); Up to 36 ppm (Legal)

### Warm-up Time

From Power On:	1643iF/1643i: 14 Seconds or Less <sup>5</sup>
	1643P: 30 Seconds or Less <sup>5</sup>
From Sleep	1643iF/1643i: 4 Seconds or Less
Mode:	1643P: 3 Seconds or Less

### Dimensions (W x D x H)

	(
1643iF:	19-7/16" x 18-5/16" x 17-3/16"
	(494 mm x 465 mm x 452 mm)
1643i:	18-7/8" x 15-5/16" x 17-13/16"
	(480 mm x 465 mm x 452 mm)
1643P:	16-1/8" x 14-13/16" x 10-13/16"
	(409 mm x 376 mm x 275 mm)

### Installation Space (W x D)

1643iF:	27-7/8" x 43-1/2" (708 mm x 1105 mm)
1643i:	27-5/16" x 43-1/2" (694 mm x 1105 mm)
1643P:	24-5/16" x 43-7/16" (617 mm x 1104 mm)
Weight <sup>6</sup>	
1643iF/1643i:	Approx. 41.9 lb. (19 kg)

1643P: Approx. 25.3 lb. (11.5 kg)

### **Print Specifications**

First-Print-Out Time (LTR)

# Approx. 5.7 Seconds

Print Resolution (dpi)

600 × 600

### Standard Page Description Languages

UFR II LT, PCL<sup>®</sup>5e/6, Adobe<sup>®</sup> PS<sup>®</sup> 3 (Standard on 1643iF/1643P, optional on 1643i) Barcode Printing Kit Optional:

### Direct Print Support

TIFF, JPEG, PDF and XPS (only LPR) Supported File Available from USB memory, LPR Types:

## **Print Features**

Suspend Job Timeout, Profile Settings, Secure Print, Header/ Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Front/ Back Covers, Toner Reduction, Poster Printing

### **Operating System**

Windows 10/8.1/7 (32/64 bit), Windows 1643iF/ 1643i/1643P: Server (2019/2016/2012 R2 (64 bit)/2012 (64 bit)/2008 R2 (64 bit)/2008 (32/64 bit), Mac\* (OS X 10.6 and later => 10.9 ~ 10/14) Linux (Web Distribution)

# Copy Specifications (1643iF/1643i Only)

First-Copy-Out Time (LTR) As fast as 6.0 Seconds (via Platen)

Copy Resolution (dpi) Reading/ Printing: Up to 600 x 600

# **Copy Specifications**

Automatic or Manual (9 Levels) **Multiple Copies** 

Up to 999

Magnification

3)

25% - 400% (1% Increments) from Platen Glass Preset Reductions

# 25%, 50%, 64%, 78%

Preset Enlargements 129%, 200%, 400%

### Basic Copy Features

Preset R/E Ratios by Area, Paper Setting, Favorite Setting, Two-Sided, Density Adjustment, Original Type Selection

### **Special Copy Features**

Two-sided Original, Sort, Job Build, N on 1, Different Size Originals, Density Adjustment, Original Type Selection, Sharpness, Erase Frame, Copy ID Card

# Scan Specifications (1643iF/1643i Only)

# Туре

Single Pass Duplexing Automatic Document Feeder **Document Feeder Paper Capacity** 

LTR: 50 Sheets (20 lb. Bond), LGL: 30 Sheets (20 lb. Bond) Maximum Original Size

Up to 8-1/2" x 14"

### **Document Feeder Supported Media Sizes** 4-1/8" x 5" to 8-1/2" x 14

**Document Feeder Supported Media Weights** Simplex: 13 lb. to 28 lb. Bond (50 to 105 g/m<sup>2</sup>) Duplex: 17 lb. to 28 lb. Bond (64 to 105 g/m<sup>2</sup>)

Platen Acceptable Originals Sheet, Book, 3-Dimensional Objects

### Network TWAIN Scan Standard

Network Scan Utility ScanGear MF

### Scan Resolution (dpi) Up to 600 x 600

# Scan Speed (LTR)

300 dpi Simplex: Up to 38ipm (BW)/13ipm (Color) . Duplex: Up to 70ipm (BW)/ 26 (Color) 600 dpi

Simplex: Up to 21 ipm (BW) Duplex: Up to 35 ipm (BW)

### Send Specifications (1643iF/1643i Only) Destination

E-mail/Internet FAX (SMTP), SMB, FTP

# Color Mode

Color, BW

Scan Resolution (dpi) 600 dpi, 300 dpi (CL/BW)

# Address Book

LDAP (50)/Local (300)/Speed Dial (281)

### **Communication Protocol**

FTP (TCP/IP), SMB (TCP/IP) File: Email: SMTP POP3

### **File Format**

TIFF, JPEG, PDF(Compact, Searchable, Standard: Encrypted, Digital Signature)

### Universal Send Features

Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, File Name, Subject/Message, E-mail Priority, TX Report, Original Content Orientation

### Fax Specifications (1643iF Only)

### Maximum Number of Connection Lines

One

Modem Speed 33.6 Kbps Super G3: 14.4 Kbps G3:

**Compression Method** MH, MR, MMR, JBIG

# Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Letter, Legal, Statement, Executive Fax Features

Two-sided Original, Density (for Scanning), Sharpness, TX Report, RX Mode, Resolutions, Favorite Settings

### **Store Specifications**

Memory Media Standard: USB

# Security Specifications

Online

802.1X, IPv6

Device Signature

1643P: Secure Print

### Authentication

Optional:

Network

Standard:

Document

Standard:

1643iF/1643i: Department ID, Embedded Standard: Universal Login Manager, uniFLOW Online Express 1643P: Department ID

Authentication before SMTP

1643iF/1643i/1643P: uniFLOW and uniFLOW

1643iF/1643i: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0,

IEEE 802.1X, IPv6, SMTP Authentication, POP

1643P: IP/Mac Address Filtering, IPSEC, TLS

Encrypted Communication, SNMP V3.0, IEEE

1643iF/1643i: Secure Print, Encrypted PDF,

## **Environmental Specifications**

# **Power Requirements**

120-127 V, 60 Hz, 7.1 A		
Power Consumption		
Maximum:	1643iF/1643i: Approx. 1430W	
	1643P: Approx. 1370W	
Sleep Mode	1643iF/1643i: 0.9 W <sup>8</sup>	
	1643P: 1.9 W <sup>9</sup>	
Typical Electricity Consumption (TEC) Rating <sup>10</sup>		
	1643iF/1643i: 0.40 kWh	
1643P: 0.50 kWh		

# Plug (Main Unit)

# NEMA 5-15P

Standards ENERGY STAR® Certified Rated EPEAT® Silver<sup>3</sup>

# Paper Supply Options PAPER FEEDER PF-C1

Paper Capacity: Paper Type:	550 Sheets [20 lb. Bond (80 g/m²)] Thin, Plain, Thick, Color, Recycled, Bond
Paper Size:	LTR, LGL, STMT, EXE Custom Size: 4-1/8" x 5-7/8" to 8-1/2" x 14" (105.0 mm x 148.0mm to 216.0 mm x 355.6 mm)
Paper Weight:	16 lb. Bond to 32 lb. Bond (60 to 120 g/m²)
Power Source:	From the Main Unit
Dimensions	18-7/8" x 18-1/4" x 33-1/8"
$(W \times D \times H)$ :	(480 mm x 464 mm x 842 mm) <sup>11</sup>
Weight:	8.8 lb. (4 kg)
CABINET TYP	E-S
D:	20 15 /10"20 0 /10"17"

Dimensions 20-15/16" x 20-9/16" x17"  $(W \times D \times H)$ : (532 mm x 522 mm x 432 mm) Weight: 33.07 lb. (15 kg)

# **Other Options**

### 1643iF/1643i/1643P:

USB Keyboard Universal Keyboard Stand-A1 Card Reader Assembly for Universal Keyboard Stand Convenience Stapler-Á1

### 1643iF/1643i:

ADF Access Handle-A1 Copy Control Interface Kit-C1 Barcode Printing Kit-E1 MiCard Attachment Kit-B1

## 1643i:

PS Printer Kit-CB1

### 1643P:

Barcode Printing Kit-F1 SD card-C1 PCL Font Set-C1 SX-BR-4600WAN

### Consumables

Toner Yield

20,500 Images (Estimated Yield @ ISO 19752 Coverage) NOTE: Toner not included in the main unit.

<sup>1</sup> imageRUNNER 1643iF model only.

- <sup>2</sup> Applies to imageRUNNER 1643iF/1643i models only. <sup>3</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- imageRUNNER 1643P model does not have direct connection capabilities, and does not come standard with Wi-Fi.
- Time from device power-on until copy ready
- (not print reservation)
- <sup>6</sup> Includes consumables
- <sup>7</sup> No charge for this solution, however activation is required.
- <sup>8</sup> 0.9 W Sleep mode not available in all circumstances due to certain settings.
- <sup>9</sup> 1.9 W Sleep mode not available in all circumstances
- due to certain settings.
  Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0. 1 Attached to Main Unit

NOTE: Check for availability and details for uniFLOW solutions.

For more information, call or visit 1.800.815.4000 CSA.CANON.COM



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Solutions America Sales Representative for details. Products shown with optional accessories. Canon Solutions America does not provide legal course or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, under the optional products and the second se HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without ©2019 Canon U.S.A., Inc. All rights reserved.



