

Republica Moldova, MD-2002
mun. Chişinău, str. Calea Basarabiei 26/6
Tel: +373 22 477 699, +373 68 157 575
info@laiola.md, www.laiola.md



LAIOLA®
C.F: 1003600039415 TVA: 030215
BC "MAIB" S.A. suc „Ştefan cel Mare”
SWIFT: AGRNMD2X885
IBAN: MD23AG000000022511670152

END USER STATEMENT

The undersigned company (name and address)

LAIOLA LTD CALEA BASARABIEI 26/6 CHISINAU – REPUBLICA MOLDOVA

running the activity of: sales of gas devices

declares to import the following goods supplied by the Italian company

MADAS s.r.l......

• Description of goods:

GAS devices as per Appendix

(If the items are in a large number they can be listed in an annex)

• Quantity: No. 138 pieces

• Value: EUR 13425,30 goods value

• Contract/Order number: ORDER DATED 14/05/24 14/05

• Date of signature: 14/05/24 14/05

• Specific purposes for which the goods are to be used

(If the goods are to be incorporated into another product, then that product and

its use should also be described) gasification of apartment buildings and private houses

The above said goods are assigned exclusively for civil purposes and will not be used for:

• Military or nuclear explosive applications, in civil nuclear activities facilities not covered by safeguard clause A.I.E.A. (International Agency for Atomic Energy) or in applications related to development and/or production of chemical weapons and weapons of mass destruction and missiles that can be used as such weapon carriers.

The above mentioned material will be used in the following place: (address)

LAIOLA LTD CALEA BASARABIEI 26/6 CHISINAU – REPUBLICA MOLDOVA

The undersigned company undertakes not to sell, not to transfer, nor to divert during the shipment and neither to re-export to Russia, Belarus and the Ukrainian zones subject to sanctions or to areas to which companies under the law of an EU country are not allowed to transfer goods, nor even in their own and declares that a statement of taking charge of goods, duly legalized, will be issued once goods are received.

The undersigned companies declare:

- not to be listed and not to be owned/controlled by listed subjects,
- not to sell the goods to listed subjects or subjects owned/controlled by listed subjects,

Said statement is issued on request of MADAS s.r.l., placed in S.Pietro di Legnago – Verona, Italy.

Company Stamp Legal Representative

Signature:

(Print name, surname and title of signatory in capital)

Date 14/05/24



FBC03Z	1122	FRG/2MBCZ DN 20 10-25 MBAR	10,00	PZ
FB03Z	1111	FRG/2MBZ DN 20 10-25 MBAR	20,00	PZ
FB04Z	2221	FRG/2MBZ DN 25 20-30 MBAR	80,00	PZ
FB04Z	3322	FRG/2MBZ DN 25 30-60 MBAR	10,00	PZ
RB50Z	2112	RG/2MBZ DN 50 FL 17-32 MBAR	12,00	PZ
RB32Z	2112	RG/2MBZ DN 32 FL 17-32 MBAR	6,00	PZ

Company Stamp Legal Representative

Signature:

(Print name, surname and title of signatory in capital)

Date 14/05/24





ROMANIA Arad , Strada Mierlei 12, VAT RO 4470552

INVOICE NR 219 E/20.10.2021

Attention: COMANAC ION
Title : MANAGER
Company Name : LAIOLA CHISINAU
Calea Basarabiei 26/6, C/F 1003600039415
REPUBLICA MOLDOVA
Project title: Export delivery
P.O. Number: 219 E/ 20.10.2021
Invoice Number 219 E
Terms: ex. works

DESCRIPTION	QUANTITY	UNIT PRICE	COST
Regulator FE 10 S MS-SS-MXS	250	€	€
Regulator FE 10 S MS-SS-MXS	80	€	€
Regulator FE 25 S MS -SS -MXS	150	€	€
Subtotal			€
Tax		0,00 %	€
Total			€



ADMINISTRATION

IRIMESCU GHEORGHE

PACKING LIST : 1 pallet x 120x80x160 cm, 1 pallet 120x80x140 cm, 480 regulatoare de gaz

GROSS WEIGHT =826 kg, NET WEIGHT = 806 kg, cod 84811019

Payment details : [RO63INGB0016000035330711](#), Swift [INGBROBU](#) , [ING BANK N.V.](#)

Goods listed on the present INVOICE 219 E/20.10.2021, **originate in ITALY**

OC. SO210340310002000
Area B
TYPE FE25 L
N. from 202150753158 to 202150753657
LOT: Z22631
assembly drawing.
overall dimen.drg.
face to face .
FIXTURES

Shut Off max	NO
Shut Off min	YES
Relief Valve	YES
Connections	1" GP x 1" GP x TAPPO 3/4"

MANUFACTURING DETAIL

	pressure containing parts	materials	notes
Regulator & Fixtures	BODY	ZAMA 3 EN 1774	
	COVER	ZAMA 3 EN1774	
	DIAPHRAGM	NBR EN 549	

REGULATOR'S & FIXTURES'S OPERATING CHARACTERISTICS

Allowable pressure DP:	8.60 bar	Shell strength:	15.00 bar
Inlet pressure range bpu:	0.40 ÷ 6.00 bar	Working temperature:	- 20 ÷ + 60 °C
Accuracy AC:	10	Lock-up pressure SG:	20
Accuracy AG:	max/min 10	Fluid:	N.G.

TEST

External leakage test (1.1 x DP) (Inlet):	9.50 bar	Internal leakage test (1.1 x DP):	9.50 bar
External leakage test (1.2 x Pds) (Outlet):	270.00 mbar		
Set Points:	Regulator (Pds)	30.00 mbar	Relief Valve (Pdo)
	Shut Off max (Pdso)	NO mbar	50.00 mbar
			Shut Off min (Pdsu)
			// mbar

Notes:
 OUTLET TEST POINT VERSION

 MU REG Dept. ISSUED BY CONTROL QUALITY
 ARMANDO AMADINI



 Signature of inspector or person authorized by customer for
 witnessing the acceptance test only

Date:

 Pietro Fiorentini®	DICHIARAZIONE DI CONFORMITA' DECLARATION OF CONFORMITY	Nr S1087328
		Data: 30/09/21

Noi PIETRO FIORENTINI S.p.A. con sede legale ad Arcugnano Italy - Via E. Fermi 8/10, dichiariamo sotto la nostra ed unica responsabilità che:

A) l'attrezzatura/e a pressione più sotto è/sono stata/e progettata/e, fabbricata/e, provata/e e controllata/e secondo una corretta prassi costruttiva, come prescritto dalla Direttiva sulle Attrezzature a Pressione 2014/68/UE all' articolo 4 comma 3.

B) l'attrezzatura/e a pressione più sotto è/sono stata/e concepita/e in accordo alla UNI 11655, alla UNI EN 16129 ed alla UNI EN 334 per quanto applicabile.

C) (solo per Italia) tale attrezzatura è conforme ai requisiti indicati nei D.M. 16 aprile 2008 e 17 aprile 2008 ai quali è necessario fare riferimento per una corretta utilizzazione delle singole apparecchiature e/o sistemi.

We PIETRO FIORENTINI S.p.A. with registered office in Arcugnano (VI) Italy - Via E. Fermi 8/10, declare under our sole responsibility as follows:

A) the pressure equipment below specified has/have been designed, manufactured, tested and inspected in accordance with sound engineering practice with as prescribed by of Pressure Equipment Directive 2014/68/UE, article 4 point 3.

B) the pressure equipment below specified has/have conceived in accordance to the standard UNI 11655, UNI EN 16129 and UNI EN 334 where applicable.

C) (only for Italy) this pressure equipment is in accordance with provisions of D.M.16 of april 2008 and 17 of april 2008 to which it is necessary to refer for a correct use of single equipment and/or system.

Descrizione attrezzatura a pressione / Description of pressure equipment

Tipo di Valvola / Type of valve : **FE25 L**

Matricola/e / Serial N/s : from **202150753158** to **202150753657**

Lotto / Lot : **Z22631**

C.O. / O.C. : **SO210340310002000**

ACCESSORI / FIXTURES	
Shut Off max	NO
Shut Off min	YES
Relief Valve	YES
Connections	1" GP x 1" GP x TAPPO 3/4"

Pressure Regulator Division – Quality Control – DESENZANO

EMESSO DAL CONTROLLO QUALITA' / ISSUED BY QUALITY CONTROL:
ARMANDO AMADINI



OC. SO210339290007000
Area B
TYPE FE10 S
N. from 202150781827 to 202150782076
LOT: Z22701
assembly drawing.
overall dimen.drg.
face to face .
FIXTURES

Shut Off max	YES
Shut Off min	YES
Relief Valve	YES
Connections	3/4" GPC x 1" GP

MANUFACTURING DETAIL

	pressure containing parts	materials	notes
Regulator & Fixtures	BODY	ZAMA 3 EN 1774	
	COVER	ZAMA 3 EN1774	
	DIAPHRAGM	NBR EN 549	

REGULATOR'S & FIXTURES'S OPERATING CHARACTERISTICS

Allowable pressure DP:	8.60 bar	Shell strength:	15.00 bar
Inlet pressure range bpu:	0.30 ÷ 6.00 bar	Working temperature:	- 20 ÷ + 60 °C
Accuracy AC:	10	Lock-up pressure SG:	20
Accuracy AG:	max/min 10	Fluid:	N.G.

TEST

External leakage test (1.1 x DP) (Inlet):		9.50 bar	Internal leakage test (1.1 x DP):		9.50 bar
External leakage test (1.2 x Pds) (Outlet):		270.00 mbar			
Set Points:	Regulator (Pds)	27.50 mbar	Relief Valve (Pdo)	38.70 mbar	
	Shut Off max (Pdso)	70.00 mbar	Shut Off min (Pdsu)	// mbar	

Notes:
 OUTLET TEST POINT VERSION

 MU REG Dept. ISSUED BY CONTROL QUALITY
 ARMANDO AMADINI



 Signature of inspector or person authorized by customer for
 witnessing the acceptance test only

Date:

 Pietro Fiorentini®	DICHIARAZIONE DI CONFORMITA' DECLARATION OF CONFORMITY	Nr S1087456
		Data: 06/10/21

Noi PIETRO FIORENTINI S.p.A. con sede legale ad Arcugnano Italy - Via E. Fermi 8/10, dichiariamo sotto la nostra ed unica responsabilità che:

A) l'attrezzatura/e a pressione più sotto è/sono stata/e progettata/e, fabbricata/e, provata/e e controllata/e secondo una corretta prassi costruttiva, come prescritto dalla Direttiva sulle Attrezzature a Pressione 2014/68/UE all' articolo 4 comma 3.

B) l'attrezzatura/e a pressione più sotto è/sono stata/e concepita/e in accordo alla UNI 11655, alla UNI EN 16129 ed alla UNI EN 334 per quanto applicabile.

C) (solo per Italia) tale attrezzatura è conforme ai requisiti indicati nei D.M. 16 aprile 2008 e 17 aprile 2008 ai quali è necessario fare riferimento per una corretta utilizzazione delle singole apparecchiature e/o sistemi.

We PIETRO FIORENTINI S.p.A. with registered office in Arcugnano (VI) Italy - Via E. Fermi 8/10, declare under our sole responsibility as follows:

A) the pressure equipment below specified has/have been designed, manufactured, tested and inspected in accordance with sound engineering practice with as prescribed by of Pressure Equipment Directive 2014/68/UE, article 4 point 3.

B) the pressure equipment below specified has/have conceived in accordance to the standard UNI 11655, UNI EN 16129 and UNI EN 334 where applicable.

C) (only for Italy) this pressure equipment is in accordance with provisions of D.M.16 of april 2008 and 17 of april 2008 to which it is necessary to refer for a correct use of single equipment and/or system.

Descrizione attrezzatura a pressione / Description of pressure equipment

Tipo di Valvola / Type of valve : **FE10 S**

Matricola/e / Serial N/s : from **202150781827** to **202150782076**

Lotto / Lot : **Z22701**

C.O. / O.C. : **SO210339290007000**

ACCESSORI / FIXTURES	
Shut Off max	YES
Shut Off min	YES
Relief Valve	YES
Connections	3/4" GPC x 1" GP

Pressure Regulator Division – Quality Control – DESENZANO

EMESSO DAL CONTROLLO QUALITA' / ISSUED BY QUALITY CONTROL:
ARMANDO AMADINI



 Pietro Fiorentini®	INSPECTION CERTIFICATE 3.1 ACCORDING TO EN 10204	N° C1087594 Date: 14/10/21																								
OC. SO210339290008000																										
Area B																										
TYPE FE10 S																										
N. from 202150782077 to 202150782156																										
LOT: Z22701																										
assembly drawing.	overall dimen.drg.	face to face .																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2" style="padding: 5px;">FIXTURES</th> </tr> <tr> <td style="width: 50%; padding: 5px;">Shut Off max</td> <td style="padding: 5px;">YES</td> </tr> <tr> <td style="padding: 5px;">Shut Off min</td> <td style="padding: 5px;">YES</td> </tr> <tr> <td style="padding: 5px;">Relief Valve</td> <td style="padding: 5px;">YES</td> </tr> <tr> <td style="padding: 5px;">Connections</td> <td style="padding: 5px;">3/4" GPC x 1"1/4 GP</td> </tr> </table>			FIXTURES		Shut Off max	YES	Shut Off min	YES	Relief Valve	YES	Connections	3/4" GPC x 1"1/4 GP														
FIXTURES																										
Shut Off max	YES																									
Shut Off min	YES																									
Relief Valve	YES																									
Connections	3/4" GPC x 1"1/4 GP																									
MANUFACTURING DETAIL																										
Regulator & Fixtures	<table border="0" style="width: 100%;"> <tr> <th style="text-align: left;">pressure containing parts</th> <th style="text-align: left;">materials</th> <th style="text-align: left;">notes</th> </tr> <tr> <td>BODY</td> <td>ZAMA 3 EN 1774</td> <td></td> </tr> <tr> <td>COVER</td> <td>ZAMA 3 EN1774</td> <td></td> </tr> <tr> <td>DIAPHRAGM</td> <td>NBR EN 549</td> <td></td> </tr> </table>	pressure containing parts	materials	notes	BODY	ZAMA 3 EN 1774		COVER	ZAMA 3 EN1774		DIAPHRAGM	NBR EN 549														
pressure containing parts	materials	notes																								
BODY	ZAMA 3 EN 1774																									
COVER	ZAMA 3 EN1774																									
DIAPHRAGM	NBR EN 549																									
REGULATOR'S & FIXTURES'S OPERATING CHARACTERISTICS																										
<table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">Allowable pressure DP:</td> <td style="width: 10%;">8.60</td> <td style="width: 10%;">bar</td> <td style="width: 30%;">Shell strength:</td> <td style="width: 10%;">15.00</td> <td style="width: 10%;">bar</td> </tr> <tr> <td>Inlet pressure range bpu:</td> <td>0.30 ÷</td> <td>6.00 bar</td> <td>Working temperature:</td> <td>- 20 ÷</td> <td>+ 60 °C</td> </tr> <tr> <td>Accuracy AC:</td> <td></td> <td>10</td> <td>Lock-up pressure SG:</td> <td></td> <td>20</td> </tr> <tr> <td>Accuracy AG:</td> <td>max/min</td> <td>10</td> <td>Fluid:</td> <td></td> <td>N.G.</td> </tr> </table>			Allowable pressure DP:	8.60	bar	Shell strength:	15.00	bar	Inlet pressure range bpu:	0.30 ÷	6.00 bar	Working temperature:	- 20 ÷	+ 60 °C	Accuracy AC:		10	Lock-up pressure SG:		20	Accuracy AG:	max/min	10	Fluid:		N.G.
Allowable pressure DP:	8.60	bar	Shell strength:	15.00	bar																					
Inlet pressure range bpu:	0.30 ÷	6.00 bar	Working temperature:	- 20 ÷	+ 60 °C																					
Accuracy AC:		10	Lock-up pressure SG:		20																					
Accuracy AG:	max/min	10	Fluid:		N.G.																					
TEST																										
<table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">External leakage test (1.1 x DP) (Inlet):</td> <td style="width: 20%;">9.50 bar</td> <td style="width: 30%;">Internal leakage test (1.1 x DP):</td> <td style="width: 20%;">9.50 bar</td> </tr> <tr> <td>External leakage test (1.2 x Pds) (Outlet):</td> <td>270.00 mbar</td> <td></td> <td></td> </tr> <tr> <td>Set Points:</td> <td>Regulator (Pds)</td> <td>27.50 mbar</td> <td>Relief Valve (Pdo)</td> </tr> <tr> <td></td> <td>Shut Off max (Pdso)</td> <td>70.00 mbar</td> <td>Shut Off min (Pdsu)</td> </tr> <tr> <td></td> <td></td> <td></td> <td>38.70 mbar</td> </tr> <tr> <td></td> <td></td> <td></td> <td>// mbar</td> </tr> </table>			External leakage test (1.1 x DP) (Inlet):	9.50 bar	Internal leakage test (1.1 x DP):	9.50 bar	External leakage test (1.2 x Pds) (Outlet):	270.00 mbar			Set Points:	Regulator (Pds)	27.50 mbar	Relief Valve (Pdo)		Shut Off max (Pdso)	70.00 mbar	Shut Off min (Pdsu)				38.70 mbar				// mbar
External leakage test (1.1 x DP) (Inlet):	9.50 bar	Internal leakage test (1.1 x DP):	9.50 bar																							
External leakage test (1.2 x Pds) (Outlet):	270.00 mbar																									
Set Points:	Regulator (Pds)	27.50 mbar	Relief Valve (Pdo)																							
	Shut Off max (Pdso)	70.00 mbar	Shut Off min (Pdsu)																							
			38.70 mbar																							
			// mbar																							
Notes: OUTLET TEST POINT VERSION																										
MU REG Dept. ISSUED BY CONTROL QUALITY ARMANDO AMADINI		Signature of inspector or person authorized by customer for witnessing the acceptance test only 																								
Date:																										

 Pietro Fiorentini®	DICHIARAZIONE DI CONFORMITA' DECLARATION OF CONFORMITY	Nr S1087594
		Data: 14/10/21

Noi PIETRO FIORENTINI S.p.A. con sede legale ad Arcugnano Italy - Via E. Fermi 8/10, dichiariamo sotto la nostra ed unica responsabilità che:

A) l'attrezzatura/e a pressione più sotto è/sono stata/e progettata/e, fabbricata/e, provata/e e controllata/e secondo una corretta prassi costruttiva, come prescritto dalla Direttiva sulle Attrezzature a Pressione 2014/68/UE all' articolo 4 comma 3.

B) l'attrezzatura/e a pressione più sotto è/sono stata/e concepita/e in accordo alla UNI 11655, alla UNI EN 16129 ed alla UNI EN 334 per quanto applicabile.

C) (solo per Italia) tale attrezzatura è conforme ai requisiti indicati nei D.M. 16 aprile 2008 e 17 aprile 2008 ai quali è necessario fare riferimento per una corretta utilizzazione delle singole apparecchiature e/o sistemi.

We PIETRO FIORENTINI S.p.A. with registered office in Arcugnano (VI) Italy - Via E. Fermi 8/10, declare under our sole responsibility as follows:

A) the pressure equipment below specified has/have been designed, manufactured, tested and inspected in accordance with sound engineering practice with as prescribed by of Pressure Equipment Directive 2014/68/UE, article 4 point 3.

B) the pressure equipment below specified has/have conceived in accordance to the standard UNI 11655, UNI EN 16129 and UNI EN 334 where applicable.

C) (only for Italy) this pressure equipment is in accordance with provisions of D.M.16 of april 2008 and 17 of april 2008 to which it is necessary to refer for a correct use of single equipment and/or system.

Descrizione attrezzatura a pressione / Description of pressure equipment

Tipo di Valvola / Type of valve : **FE10 S**

Matricola/e / Serial N/s : from **202150782077** to **202150782156**

Lotto / Lot : **Z22701**

C.O. / O.C. : **SO210339290008000**


ACCESSORI / FIXTURES	
Shut Off max	YES
Shut Off min	YES
Relief Valve	YES
Connections	3/4" GPC x 1"1/4 GP

Pressure Regulator Division – Quality Control – DESENZANO

EMESSO DAL CONTROLLO QUALITA' / ISSUED BY QUALITY CONTROL:
ARMANDO AMADINI



CERTIFICAT DE CIRCULAȚIE A MĂRFURILOR

1 Exportator (Numele, adresa completă, țară)	EUR. 1 Nr. V 053092 Consultați notele de pe verso înainte de a completa formularul.		
3 Destinatar (Numele, adresa completă, țară) (Opțional)	2 Certificat utilizat în schimburile preferențiale dintre și (indicați țările, grupurile de țări sau teritoriile implicate)		
	4 Țara, grupul de țări sau teritoriul din care produsele sunt considerate originare	5 Țara, grupul de țări sau teritoriul de destinație	
	6 Informații privind transportul (Opțional)		
7 Observații		8 Numărul articolului; Mărci și numere; Numărul și tipul coletelor⁽¹⁾; Descrierea mărfurilor 2 EUROPALET , 480 regulatoare de gaze COD 84811019 9 Masa brută (kg) sau altă unitate de măsură (litri, m³ etc.) 826 kg 10 Facturi (Opțional) 2195/20.10.2021	
11 VIZA VĂMII <i>Declarație certificată</i> Document de export ⁽²⁾ Formular nr. din Biroul vamal Țara emitentă sau teritoriul emitent Locul și data (Semnătura)	12 DECLARAȚIA EXPORTATORULUI Subsemnatul (subsemnata) declar că mărfurile descrise mai sus îndeplinesc condițiile necesare pentru eliberarea prezentului certificat.  Locul și data (Semnătura) 		

⁽¹⁾ Dacă mărfurile nu sunt ambalate, indicați numărul articolelor sau menționați „în vrac”, după caz.

⁽²⁾ Se completează numai în cazul în care reglementările țării exportatoare sau ale teritoriului impun acest lucru.