Canon

Product Data
No. MPDCT0451EAK

CSDS-002A

APPLICATION

This kit upgrades the Aquilion systems with the coneXact 3D volume reconstruction algorithm. Using coneXact, the Aquilion 80 detector row system generates 160 slices per rotation, the 64 detector row system generates 128 slices per rotation, the 40 detector row system generates 80 slices per rotation, while the 16 detector row system generates 32 slices per rotation.

The applicable CT systems are shown below.

CSDS-002A/2./0*

(333 (32) (12)	
SYSTEM MODEL	
Aquilion Prime SP	TSX-303B/1, /4, /5, /8, /9, /A, /D, /E
Aquilion PRIME	TSX-303A/1, /A, /L, /T
Aquilion Serve SP	TSX-307B/1,/2
Aquilion Serve	TSX-307A/1,/2
Aquilion Exceed LB	TSX-202A/1,/3
Aquilion	TSX-101A/s**
	TSX-101A/u
Aquilion Lightning	TSX-036A/1, /4, /7, /A, /C, /E

- *: Depends on region
- **: CSDS-002A/0 is not applicable.

Note: Some systems may not be available in your country or region. Please check with your sales representative.

FEATURES

- · Generates a maximum of:
 - 160 image slices for 80 detector row system
 - 128 image slices for 64 detector row system
 - 80 image slices for 40 detector row system
 - 32 image slices for 16 detector row system
- Achieves ultra-high resolution images where fine detail is required.

COMPOSITION

MASS

• Mass: 0.1 kg (0.2 lb)

POWER REQUIREMENTS

The ratings of the CT system have not been changed.

AMBIENT CONDITIONS

Same as those for the CT system.

CSDS-002A

MPDCT0451EAK

CANON MEDICAL SYSTEMS CORPORATION

1385, Shimoishigami, Otawara-shi, Tochigi 324-8550, Japan

https://global.medical.canon

©Canon Medical Systems Corporation 2014-2023. All rights reserved.
Design and specifications are subject to change without notice.
Model number: CSDS-002A MPDCT0451EAK 2023-12 CMSC/Produced in Japan

Canon Medical Systems Corporation meets internationally recognized standards for Quality Management System ISO 9001, ISO 13485. Canon Medical Systems Corporation meets the Environmental Management System standard ISO 14001.

Made For life