

**DECLARATION OF PERFORMANCE**  
(According to Regulation EU 305/2011, Annex 5)

**No: 001DOP-NG**

- 1. Identification code of the product type:** Used as Indoor Wall Covering Dry Pressed Group BII Eb  $\leq$  % 10 (Annex L), Glazed Ceramic Tiles
- 2. Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** interior wall covering
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer:**  
NG Kütahya Seramik Porselen Turizm A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mahallesi Ramazan Özen (Osب) Sok.No: 2 Merkez / Kütahya
- 5. Name and contact address of the authorized representative :** Not relevant.
- 6. System or system of assesment and verification of constancy of performance of the construction product :** System 4
- 7. Declaration of performances concerning a construction product covered by a harmonised standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
- 8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

**9. Declared performances:**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1	TS EN 14411
Breaking strength	Thickness $\geq$ 7,5mm >600 N Thickness <7,5mm >200 N	TS EN 14411
<b>Release of dangerous substance, for:</b>		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
<b>Bond strength/adhesion, for:</b>		
- Cementitious adhesives, Type C1	$\geq$ 0,5 N/mm <sup>2</sup>	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
<b>Durability for:</b>		
- Internal use:	Pass	TS EN 14411

**10.Declaration:** The performance of the product identified in point 1 is in conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

Yüksel KAYA / Deputy Director General of Finance and Sales  
Kütahya/TÜRKİYE- 05.10.2022

NG KÜTAHYA SERAMİK  
Porselen Turizm A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mah. Ramazan Özen (OSB) Sk. No:2  
Tel: 0 274 229 12 00 Fax: 225 12 13  
Cıllı Y.D. No: 607 027 3858 KÜTAHYA  
Mersis No: 0607 0273 8560 0015

DECLARATION OF PERFORMANCE  
(According to Regulation EU 305/2011, Annex V)

No: 002DOP-NG

1. **Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb  $\leq$  % 0,5 (Annex G), Glazed Ceramic Tiles
2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal or external floor or wall coverings.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer:**  
NG Kütahya Seramik Porselen Turizm A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mahallesi Ramazan Özen (OsB) Sok.No: 2 Merkez / Kütahya
5. **Name and contact address of the authorized representative:** Not relevant.
6. **System or system of assesment and verification of constancy of performance of the construction product:** System 4
7. **Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1	TS EN 14411
<b>Breaking strength</b>	Thickness $\geq$ 7,5mm >1300 N Thickness <7,5mm >700 N	TS EN 14411
<b>Slipperiness</b> <sup>(1)</sup>	Refer to the technical documentation or catalog	TS EN 14411
<b>Release of dangerous substance, for:</b>		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
<b>Resistance to thermal shock</b>	Pass	TS EN 14411
<b>Tactility</b>	NPD	TS EN 14411
<b>Bond strength/adhesion, for:</b>		
- Cementitious adhesives, Type C2	$\geq$ 1,0 N/mm <sup>2</sup>	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
<b>Durability for:</b>		
- Internal use:	Pass	TS EN 14411
- External use: freeze-thaw resistance	Pass	TS EN 14411

Note: (1) where required by regulations

**10.Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales  
Kütahya/TÜRKİYE- 05.10.2022

NG KÜTAHYA SERAMİK  
PORSELEN TURİZM A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mah. Ramazan Özen (OSB) Sk. No:2  
Tel: 0 274 225 12 20 Fax: 225 12 13  
Tic. Sic. No: 607 027 3856 KÜTAHYA  
Mersis No: 0607 0273 8560 0015



DECLARATION OF PERFORMANCE  
(According to Regulation EU 305/2011)

No: 003DOP-NG

1. **Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Blb % 0,5 < Eb ≤ % 3 (Annex H), Glazed Ceramic Tiles

2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal floor or wall coverings.

4. **Name, registered trade name or registered trade mark and contact address of the manufacturer:**

NG Kütahya Seramik Porselen Turizm A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mahallesi Ramazan Özen (OsB) Sok.No: 2 Merkez / Kütahya

5. **Name and contact address of the authorized representative:** Not relevant.

6. **System or system of assesment and verification of constancy of performance of the construction product:** System 4

7. **Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. **Declared performances:**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 <sub>FL</sub> /A1	TS EN 14411
Breaking strength	Thickness ≥7,5mm >1100 N Thickness <7,5mm >700 N	TS EN 14411
Slipperiness <sup>(1)</sup>	Refer to the technical documentation or catalog	TS EN 14411
<b>Release of dangerous substance, for:</b>		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
<b>Tactility</b>	NPD	TS EN 14411
<b>Bond strength/adhesion, for:</b>		
- Cementitious adhesives, Type C2	≥ 1,0 N/mm <sup>2</sup>	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
<b>Durability for:</b>		
- Internal use:	Pass	TS EN 14411

Note: (1) where required by regulations

10. **Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales  
Kütahya/TÜRKİYE- 05.10.2022

NG KÜTAHYA SERAMİK  
PORSELEN TURİZM A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mah. Ramazan Özen (OSB) Sk. No:2  
Tel: 0 274 225 12 00 Fax: 225 12 13  
Çinili V.D/No: 607 027 3856 KÜTAHYA  
Mersis No: 0607 0273 0500 0015

DECLARATION OF PERFORMANCE  
(According to Regulation EU 305/2011, Annex V)

No: 004DOP-NG

1. **Identification code of the product type:** Used as Indoor and Outdoor Floor and Wall Cladding Low Water Absorption Dry Pressed Group Bla Eb  $\leq$  % 0,5 (Annex G), Glazed ,Unglazed Ceramic Tiles

2. **Type batch or serial number or any other element allowing identification of the construction product:** Identification code of the product type, barcode number, ship date

3. **Intended use or uses of the construction product,in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Internal or external floor or wall coverings.

4. **Name, registered trade name or registered trade mark and contact address of the manufacturer:**

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Granit Fabrikası Şubesi  
NG KÜTAHYA SERAMİK  
Çalca OSB Mah.4 Cad. No :5 Merkez-Kütahya/ TÜRKİYE

5. **Name and contact address of the authorized representative:** Not relevant.

6. **System or system of assesment and verification of constancy of performance of the construction product:** System 4

7. **Declaration of performances concerning a construction product covered by a harmonised Standard :** NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.

8. **Declaration of performances concerning a construction product for which a European Technical Assesment has been issued:** Not relevant.

9. **Declared performances:**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 <sub>FL</sub> /A1	TS EN 14411
Breaking strength	Thickness $\geq$ 7,5mm >1300 N Thickness <7,5mm >700 N	TS EN 14411
Slipperiness <sup>(1)</sup>	Refer to the technical documentation or catalog	TS EN 14411
<b>Release of dangerous substance, for:</b>		
- Cadmium	NPD	TS EN 14411
- Lead	NPD	TS EN 14411
Resistance to thermal shock	Pass	TS EN 14411
Tactility	NPD	TS EN 14411
<b>Bond strength/adhesion, for:</b>		
- Cementitious adhesives, Type C2	$\geq$ 1,0 N/mm <sup>2</sup>	TS EN 14411
- Reaction resin adhesives	NPD	TS EN 14411
- Dispersion adhesives	NPD	TS EN 14411
<b>Durability for:</b>		
- Internal use:	Pass	TS EN 14411
- External use: freeze-thaw resistance	Pass	TS EN 14411

Note: (1) where required by regulations

10.**Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Yüksel KAYA / Deputy Director General of Finance and Sales  
Kütahya/TÜRKİYE- 05.10.2022

NG KÜTAHYA SERAMİK  
PORSELEN TURİZM A.Ş.  
NG KÜTAHYA SERAMİK  
Çalca Mah. Ramazan Özen (OSB) Sk. No:2  
Tel: 0 274 225 12 00 Fax: 225 12 13  
E-Posta: info@ngk.com.tr  
Mersis No: 0607 0273 8560 0015



ORGANISMUL DE CERTIFICARE „CERTMATCON”



# CERTIFICAT DE CONFORMITATE

Nr. de înregistrare

13 C001995-22

Data emiterii: 04 aprilie 2022

Valabil pînă la: 04 aprilie 2023

**CertMatCon**

## ORGANISMUL DE CERTIFICARE

CERTMATCON mun. Chișinău, str. Uzinelor, 4/2, etaj 4, of. 4, MD2023, tel. 022-903-001; cell. 078-191-001, e-mail: [office@certmatcon.md](mailto:office@certmatcon.md), [WWW.CERTMATCON.MD](http://WWW.CERTMATCON.MD).

PRIN PREZENTUL DOCUMENT SE CONFIRMĂ FAPTUL, CĂ PRODUSELE IDENTIFICATE ASTFEL:  
DENUMIREA / DESCRIEREA

Plăci ceramice, presate prin metoda uscată,  
cu absorbție de apă redusă  $E_b \leq 0,5 \%$ , Grupa BI<sub>n</sub>;  
cu absorbție de apă sporită  $E_b > 10 \%$ , Grupa BIII.

Codul NCM  
6908

SÎNT CONFORME CU CERINȚELE STABILITE ÎN :

RNI 06-5.3.35:2001 pct. 2.2; SM EN 14411:2017 pct. 5.2 tab. 2 Anexa A, pct. A1-A5,  
Anexa B tab. 2, pct. B1, B6, B8, pct. 8.

## PRODUCĂTOR

ТОВ "Церсанит Инвест", Ucraina.

Codul țării  
UA

## SOLICITANT

"BOMI-SERVIS" S.R.L.,  
str. Eternitate, 3, or. Drochia, r-l Drochia, Republica Moldova.

Codul IDNO  
1003607015849

## CERTIFICATUL ESTE ELIBERAT ÎN BAZA

Raport de evaluare final Nr. 1042 din 01.04.2022, eliberat de OC "CertMatCon", mun. Chișinău, str. Uzinelor, 4/2, etaj 4, of. 4, MD 2023; Raport de încercări Nr. 097/4 din 18.02.2022, eliberat de Centrul de Încercări, Expertiză și Cercetare (CÎEC) din cadrul "CertMatCon" SRL, mun. Chișinău, str. Feredeului, 12, MD 2005, certificat de acreditare Nr. LÎ-101 valabil pînă la 11.07.2025, eliberat de CNA "MOLDAC"; Rapoarte de încercări Nr. 14.1 din 28.03.2022, Nr. 089 din 03.02.2021, eliberate de "CIPC Incerc Test" SRL, mun. Chișinău, str. Varnița, 16/1.

## INFORMAȚIE SUPLEMENTARĂ:

Certificare voluntară. Certificatul este valabil doar în cazul asigurării cu informație în limba de stat la fiecare ambalaj/unitate de produs conform legislației în vigoare.  
Contract de prestări servicii Nr. 896 din 16.01.2018.

Seria V Nr. 000776



Conducătorul OC

PUHA Ion

În atenția antreprenorilor și organelor de control!  
Copiile certificatelor de conformitate se legalizează în modul stabilit de  
OC „CERTMATCON”, informații pe [www.certmatcon.md](http://www.certmatcon.md)  
Falsificarea certificatelor se pedepsește conform legislației





SC ROMCONSTRUCT AG SRL BUZAU  
 SOS. POGONELE, NR. 12  
 Reg. Com.: J10 / 2877 / 94  
 CIF: R6736732  
 Tel./fax: 00 40238 726731 , 426175  
 www.romconstruct.ro



SC ROMCONSTRUCT AG SRL BUZAU  
 STR. POGONELE, NR. 12 -BUZAU  
 SR EN 14509:2013  
 Panouri tip sandvis

## DECLARATIE DE PERFORMANTA

Nr.:02-PS

1. Cod unic de identificare al produsului: **Panouri sandvis autoportante, izolante, cu peliculă dublă de acoperire metalică.**
2. Tipul: Panou sandvis de acoperis cu 5 nervuri (grosime 80 mm. ; miez :PUR)
3. Utilizarea preconizată a produsului: **Acoperisuri si placare acoperisuri, pereti exteriori si placare pereti, pereti si plafone in interiorul anvelopei cladirii**
4. Numele fabricantului: **SC ROMCONSTRUCT AG SRL -BUZAU**
5. Reprezentant autorizat: **Nu este cazul**
6. Sistemul de evaluare si verificare a constantei performantei produsului pentru constructii: **Sistemul 4**
7. Standard armonizat: SR EN 14509:2013

### 8. Performante declarate:

Caracteristici esentiale		Performanta declarata	Standard armonizat
Rezistenta mecanica:			SR EN 14509:2013
-rezistenta la forfecare a materialului de miez		0.100Mpa	
-efort de compresiune ( la deformatie 10%)		0.110 Mpa	
-rezistenta la tractiune transversala pe panou		0.100 Mpa	
Capacitate portanta:			
-moment de incovoiere final	Fata interioara	5.04 KNm/m	
	Fata exteriora	7.40 KNm/m	
-moment de incovoiere reazem central	Sarcina descendenta	4.70 KNm/m	
	Sarcina ascendenta	4.41 KNm/m	
Conductivitate termica material miez(10C)		0.0220 W/mK	
Rezistenta termica(10C)		2.69 mpK/W	
Densitate material miez		36.7 kg./mc	
Reactie la foc		NPD	
Rezistenta la foc		NPD	

9. Performantele produsului identificat la punctele 1 si 2 sunt in concordanta cu performantele declarate la punctul 8.

Aceasta declaratie de performanta este emisa in conformitate cu regulamentul (UE) NR.305 /2011 si regulamentul 574/2014 pe raspunderea exclusiva a fabricantului identificat mai sus.

Copia Declaratiei de performanta este pusa la dispozitie, in conf. cu art. 7 al.3 din regulamentul nr. 305/2011 pe site-ul societatii: www.romconstruct.ro

Semnata pentru si in numele fabricantului, de catre :

Director,  
 Dan Popescu



SC ROMCONSTRUCT AG SRL BUZAU  
 SOS. POGONELE, NR. 12  
 Reg. Com.: J10 / 2877 / 94  
 CIF: R6736732  
 Tel./fax: 00 40238 726731, 426175  
 www.romconstruct.ro



SC ROMCONSTRUCT AG SRL BUZAU  
 STR. POGONELE, NR. 12 -BUZAU

SR EN 14509:2013

**Panouri tip sandvis**

## DECLARATIE DE PERFORMANTA

Nr.:03-PS

1. Cod unic de identificare al produsului: **Panouri sandviș autoportante, izolante, cu peliculă dublă de acoperire metalică.**
2. Tipul: Panou sandvis de perete (grosime 80 mm. miez :PUR)
3. Utilizarea preconizata a produsului: **Acoperisuri si placare acoperisuri, pereti exteriori si placare pereti, pereti si plafoane in interiorul anvelopei cladirii**
4. Numele fabricantului: **SC ROMCONSTRUCT AG SRL -BUZAU**
5. Reprezentant autorizat: **Nu este cazul**
6. Sistemul de evaluare si verificare a constantei performantei produsului pentru constructii: **Sistemul 4**
7. Standard armonizat: SR EN 14509:2013
8. **Performante declarate:**

Caracteristici esentiale		Performanta declarata	Standard armonizat
<b>Rezistenta mecanica:</b>			SR EN 14509:2013
-rezistenta la forfecare a materialului de miez		0.100 Mpa	
-efort de compresie ( la deformatie 10%)		0.110 Mpa	
-rezistenta la tractiune transversala pe panou		0.100 Mpa	
<b>Capacitate portanta:</b>			
-moment de incovoiere final	Fata interioara	4.41 KNm/m	
	Fata exteriora	5.69 KNm/m	
-moment de incovoiere reazem central	Sarcina descendenta	3.2 KNm/m	
	Sarcina ascendenta	2.91 KNm/m	
<b>Conductivitate termica material miez(10C)</b>		0.0220 W/mK	
<b>Rezistenta termica(10C)</b>		2.59 mpK/W	
<b>Densitate material miez</b>		37.9 kg./mc.	
<b>Reactie la foc</b>		NPD	
<b>Rezistenta la foc</b>		NPD	

9. Performantele produsului identificat la punctele 1 si 2 sunt in concordanta cu performantele declarate la punctul 8.

Aceasta declaratie de performanta este emisa in conformitate cu regulamentul (UE) NR.305 /2011 si regulamentul 574/2014 pe raspunderea exclusiva a fabricantului identificat mai sus.

Copia Declaratiei de performanta este pusa la dispozitie, in conf. cu art. 7 al.3 din regulamentul nr. 305/2011 pe site-ul societatii: www.romconstruct.ro

Semnata pentru si in numele fabricantului, de catre :

Director,  
 Dan Popescu

DP/01-PS



SC ROMCONSTRUCT AG SRL BUZAU  
SOS. POGONELE, NR. 12  
Reg. Com.: J10 / 2877 / 94  
CIF: R6736732  
Tel./fax: 00 40238 726731 , 426175  
www.romconstruct.ro

CE

SC ROMCONSTRUCT AG SRL BUZAU  
STR. POGONELE, NR. 12 -BUZAU  
SR EN 14509:2013  
Panouri tip sandvis

## DECLARATIE DE PERFORMANTA

Nr.:02-PS

1. Cod unic de identificare al produsului: **Panouri sandvis autoportante, izolante, cu peliculă dublă de acoperire metalică.**
2. Tipul: Panou sandvis de acoperis cu 5 nervuri (grosime 80 mm. ; miez :PUR)
3. Utilizarea preconizată a produsului: **Acoperisuri si placare acoperisuri, pereti exteriori si placare pereti, pereti si plafone in interiorul anvelopei cladirii**
4. Numele fabricantului: **SC ROMCONSTRUCT AG SRL -BUZAU**
5. Reprezentant autorizat: **Nu este cazul**
6. Sistemul de evaluare si verificare a constantei performantei produsului pentru constructii: **Sistemul 4**
7. Standard armonizat: SR EN 14509:2013

### 8. Performante declarate:

Caracteristici esentiale		Performanta declarata	Standard armonizat
Rezistenta mecanica:			SR EN 14509:2013
-rezistenta la forfecare a materialului de miez		0.100Mpa	
-efort de compresiune ( la deformatie 10%)		0.110 Mpa	
-rezistenta la tractiune transversala pe panou		0.100 Mpa	
Capacitate portanta:			
-moment de incovoiere final	Fata interioara	5.04 KNm/m	
	Fata exteriora	7.40 KNm/m	
-moment de incovoiere reazem central	Sarcina descendenta	4.70 KNm/m	
	Sarcina ascendenta	4.41 KNm/m	
Conductivitate termica material miez(10C)		0.0220 W/mK	
Rezistenta termica(10C)		2.69 mpK/W	
Densitate material miez		36.7 kg./mc	
Reactie la foc		NPD	
Rezistenta la foc		NPD	

9. Performantele produsului identificat la punctele 1 si 2 sunt in concordanta cu performantele declarate la punctul 8.

Aceasta declaratie de performanta este emisa in conformitate cu regulamentul (UE) NR.305 /2011 si regulamentul 574/2014 pe raspunderea exclusiva a fabricantului identificat mai sus.

Copia Declaratiei de performanta este pusa la dispozitie, in conf. cu art. 7 al.3 din regulamentul nr. 305/2011 pe site-ul societatii: www.romconstruct.ro

Semnata pentru si in numele fabricantului, de catre :

Director,  
Dan Popescu





# CERTIFICAT

**DE VERIFICARE A ASIGURĂRII CONTROLULUI PRODUCȚIEI ÎN FABRICĂ**  
**Numărul: CV-037-2020**

**Pentru:**

**Ferestre și uși din profile de policlorură de vinil (PVC) și aluminiu,  
inclusiv:**

**Ferestre fixe cu ramă, ferestre și uși – ferestre acționate manual sau automat și ansambluri  
compuse, pentru a fi montate în goluri verticale ale pereților;**

**Uși exterioare pentru pietoni acționate manual cu canaturi netede sau fățuite.**

Fabricat de:

**"FAȚADE AUTENTICE" S.R.L.,  
str. Uzinelor, 11, mun. Chișinău, Republica Moldova.**

Fabricat la punctul de lucru: **str. Unirii, 74, or. Sângera, mun. Chișinău, Republica Moldova.**

Produsele au fost supuse de către proiectantul de sisteme încercărilor inițiale de tip pentru produs și unui control al procesului de producție care cuprinde toate măsurile necesare pentru îndeplinirea și menținerea cerințelor specificate în documentele de referință. OC Certmatcon a efectuat verificarea asigurării controlului producției în fabrică de către producător conform sistemului 4, a evaluat rapoartele privind încercările inițiale de tip și va efectua supravegherea continuă a procesului de producție.

Acest certificat atestă îndeplinirea prevederilor descrise în anexa ZA a standardului:

**SM EN 14351-1+A2:2016**

Acest certificat a fost emis prima dată la data de 29.09.2020 și va rămâne valabil până la data de 28.09.2023, atât timp cât standardul armonizat, produsul pentru construcții, metodele de evaluare a constanței performanței și condițiile de producție în fabrică nu sunt modificate esențial.

Acest certificat poate fi suspendat sau retras dacă se constată că nu se mențin condițiile în baza cărora a fost emis.



**Director General**  
**Ion PUHA**