

Vipoil TAP-15

Transmission Oil

PRODUCT DESCRIPTION

VIPOIL TAP-15 is high quality transmission oil designed for truck and agricultural machinery obtained from high-quality mineral oils supplemented with additives that provide resistance to high pressures, oxidation, heat dissipation resulting from friction.

SPECIFICATIONS

SAE 90
API GL-3

APPLICATIONS

It is recommended for the lubrication of manual transmissions for trucks as well as classic cylindrical and bevel gears with straight, bevel or hypoid toothing that operate at mechanical loads and high temperatures and moderate loads.

BENEFITS

- Very good oxidation stability
- Resistance to foaming
- Excellent demulsification
- Properties:
 - anti-wear,
 - anti-corrosion
 - anti-oxidants,
 - anti-foaming.

TYPICAL PROPERTIES

Characteristics	Test Method	Value
Density at 15°C, g/cm ³ , max.	ASTM D4052	0.880
Kinematic Viscosity at +40°C, mm ² /s ⁻¹ .	ASTM D445	152.0
Kinematic Viscosity at +100°C, mm ² /s ⁻¹ .	ASTM D445	14.7
Viscosity Index, min.	ASTM D2270	95
Flash Point °C, min.	ASTM D92	235
Pour Point °C, min.	ASTM D97	-24
F.Z.G., Fail Load Stage	DIN 51354	12
Demulsibility. at +82 °C, min	DIN 51599	<30
4-Ball Weld Load, N	ASTM D2783	2500

* These values are informative. Variations of these characteristics may occur.

This lubricant does not present a particular danger if it is used according to our recommendations and according to the purpose for which it was produced. The security sheet according to the European legislation in force can be obtained on request.