



DESTONER PULPER DELTA



Video




DELTA 1



DELTA 2



DELTA ZERO



MODEL		
Cod.	Description	€
802	Destoner DELTA ZERO	
801	Destoner DELTA 1 Three-phase	
803	Destoner DELTA 2 Three-phase	

OPTIONAL		
Cod.	Description	€
4260	Additional internal basket for DELTA 0 with hole size 0,8 - 12 mm	
4261	Additional internal basket for DELTA 1 with hole size 0,8 - 12 mm	
4262	Additional internal basket for DELTA 2 with hole size 0,8 - 12 mm	
4263	Single rubber plate for DELTA 0	
4264-1	Single rubber plate for DELTA 1	
4264-2	Single rubber plate for DELTA 2	
4265	Internal basket for DELTA ZERO with hole 0,6 mm	
4266	Internal basket for DELTA 1 with hole 0,6 mm	
4250	Electronic speed variator for Delta 1/2	
4251	Increased difference for 5,5 Kw engine for Delta 2	

STANDARD FEATURES

- Engine and emergency stop
- Structure in AISI 304 stainless steel
- Stainless steel shaft with adjustable rubber blades
- Electrical system with emergency stop
- Stainless steel loading screw
- Stainless steel mesh with 0.8-12mm holes
- Thermal protection for the engine

(Conversion: IE3 2,2Kw = IE1 3Kw)

MODEL	ENGINE HP (Kw)	POWER	STONE UNLOADING HEIGHT	JUICE UNLOADING HEIGHT	LOADING HEIGHT	CAPACITY	DIMENSION mm	WEIGHT
802	1,5 (1,1)	Single-phase / Three-phase	400 mm	300 mm	1300 mm	550 Kg/h	1100x650x1300	80 Kg
801	4 (3)	Three-phase	480 mm	370 mm	1420 mm	1200 Kg/h	1400x700x1420	150 Kg
803	5,5 (4)	Three-phase	480 mm	370 mm	1620 mm	2000 Kg/h	1800x850x1850	250 Kg