

Technical Data		KS-Q3	
Light Intensity		100,000 Lux @ D=30cm / 40,000 Lux @ D=50cm	
Control System (KS-Q3)		stepless brightness dimmer control and switcher intergrated in the handle	
Flexiable arm		76cm length flexiable plastic sleeve goose neck	
Lamphead		Diameter=75mm length =110mm	
Diameter of Light Spot		80-150mm @ D=30-50cm	
Light source		1x LED bulb	
LED life span		50,000 hours	
Color Temperature		4500K-5500K	
Input Connected Load		100-260V 50/60MHz	
Power consumption		3W	
Class of Protection		Class II	
Mounting Options		Mobile, Table, Wall& Rail	
Battery type (KS-Q3B)		1800mAh	8 hours work



LED Spot Exam Light

- + The economic, compact, focused, flexible light



- + Ultra-high brightness from a nutshell with a on/off handle



- + Multi-functional control systems provides the attractive performance

- + A selectable range of mounted brackets are installed on the floor, wall, surgical table, desk, rail

- + Meet hygienic and cleaning requirements via spray disinfection





Select color of shell

Select the control system

Select the mounted bracket



Standard Fitting (Mobile)




Top part+vertical stand+ABS base

Code of base	ABS01Black or ABS02 white
Material:	Integrated plastic
Castors	D-50mm with 5 brake
Data of base	D-53cm 5 branches 1.2kgs
Vertical pole	85cm length powder coated steel


Option (Mobile)



Code of base	DM01 Black or White
Material:	Powder coated steel
Castors	D-50mm with 5 brake
Data of base	D-58cm 5 branches 3.35kgs
Vertical pole	85cm length powder coated steel



Wall Mounted Clamp	
Code	WM01
Material:	Aluminium
Plug-in hole	D-22mm



Rail Mounted Clamp		
Code	RC01	RC02
Material:	Aluminium	
Clamp size max	34x9.5 mm	80x9.5 mm
Plug-in hole	D-22mm	D-22mm



Table Clamp	
Code	TC01
Material:	Aluminium
Plug-in hole	D-22mm

