i-SENSYS MF421dw \ MF426dw \ MF428x \ MF429x

RELIABLE, SECURE AND EASY-TO-USE MULTI-FUNCTION PRINTER FOR AN OFFICE OR SME.

The i-SENSYS MF420 series are multi-function printers offering SMEs speed, durability, and quality. Mobile connectivity maximises productivity.



Callost Callost



MF428x

MF429x

- Save time with fast print speeds of up to 38ppm
- Increase productivity with double sided single pass scanning
- High quality 1200 x 1200 dpi print resolution
- Easy operation with large colour touch screen
- Improved flexibility with varied media support; A4, A5,A6
- Increase control with the Universal Login Manager (MF428x and MF429x)
- Enhanced security & accounting with uniFLOW (MF428x and MF429x)
- Improve quality & reliability with Canon Genuine all-in-one cartridges
- Application Library allowing automation, added shortcuts and a customised interface
- Secure PIN feature allowing employers and employees maximum control over print jobs



OPTIONAL ACCESSORIES

Cassette Feeding Module - AH1

- Additional 550 sheet paper cassette, 1unit can be added to main unit.
- Barcode Print Kit- E1E (Available on MF428x & MF429x)
- Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation

Send PDF Security Feature Set-E1 (Available on MF428x & MF429x)

• Send encrypted PDF and add digital device signature to PDF files. This kit, which is delivered electronically, includes a license access certificate for activation.

Telephone 6 Kit Long Cord (Available on MF426dw & MF429x)

33.6 Kbps (Up to 3 seconds/page⁵)

• Optional telephone handset for fax function.

TECHNICAL SPECIFICATIONS

Machine type Available functions

PRINTER Print speed

Printing method Print quality Print resolution Warm-up time First Print Out Time Printer languages

Fonts

Print margins

Toner saver mode Advanced printing features

COPIER Copy speed

First Copy Output Time (FCOT) Copy resolution Copy modes Double sided copying Multiple copy Reduction / Enlargement Other features

SCANNER Type Scan resolution

Scan speed

Colour scanning depth Greyscales Compatibility Max. scan width Scan to E-mail / PC / USB memory key / FTP

Scan to Cloud iFAX FAX

Mono Laser All-In-One MF421dw / MF428x : Print, Copy and Scan MF426dw / MF429x: Print, Copy, Scan and Fax

Single sided : Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape) Double sided : Up to 30.3 ipm (A4) Monochrome laser beam printing Up to 1200 x 1200 dpi 600 x 600 dpi Approx. 14 seconds or less from power on Approx: 5.5 seconds or less MF421dw: UFRII, PCL 5e', PCL6 MF426dw / MF428x / MF429x: UFRII, PCL 5e', PCL6, Adobe® PostScript

MF421dw / MF426dw: 45 PCL fonts 136 PostScript fonts MF428x / MF429x: 93 PCL fonts 136 PostScript fonts 5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

Yes Secure Print Print from USB memory key (JPEG/TIFF/PDF) Barcode Print² (MF428x, MF429x only) Google Cloud Print Ready IOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon PRINT Business app

Single sided (A4): Up to 38 ppm Double sided (A4): Up to 30.3 ipm ADF (A4): Approx. 6.6 seconds or less Platen (A4): Approx. 6.4 seconds or less Up to 600 x 600 dpi Text, Text/Photo (Default),Text/Photo (High Quality), Photo 2-sided to 2-sided (Automatic) Up to 999 copies 25-400% in 1% increments Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy

Colour Ontical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi Single sided mono: 38ipm (300x600dpi) Single sided colour: 13ipm (300x600dpi) Double sided mono: 70ipm (300x600dpi) Double sided colour: 26ipm (300x600dpi)

24 bit/24 bit (input/output) 256 levels TWAIN, WIA, ICA 216mm TIFF/JPEG/PDF/Compact PDF/Searchable PDF/Encrypted PDF³(MF428x, MF429x only)/PDF (Digital signature)³ (MF428x, MF429x only) TIFF/JPEG/PDF/PNG4 ITU-T 37

MF426dw. MF429x only

Modem speed Receive mode Fax resolution

FAX memory Speed dials Group dials/destinations Sequential broadcast Memory backup

Double sided faxing Other features

MEDIA HANDLING Scanner type Paper input (Standard)

Paper input (Option) Paper output Media types

Media sizes

Media weights

Double sided printing

INTERFACE & SOFTWARE Interface type

Operating System compatibility

Network Protocol

Fax only, Fax/Tel Auto Switch, Answer Mode, Manual Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Up to 512 pages⁵ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash memory) Yes (Transmit and Receive) Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports Platen, 2-sided ADF (single pass) 250-sheet cassette 100-sheet multi-purpose tray 50-sheet ADF 550-sheet cassette 150-sheet Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, I6K, Custom sizes: Min. 105 x 148 mm Max. 215.9 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter; Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COMI0, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm. ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 105 x 128 mm Max 215.9 x 355.6 mm Cassette (standard and optional): 52 to 120 g/m² multi-purpose tray: 52 to 163 g/m ADF: 50 to 105 g/m²

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap Custom size - Min. 210 x 279.4 mm Max. 215.9 x 355.6 mm 60 to 120 g/m²

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection Windows* 10 / Windows* 81 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008 Mac OS X version 10.8.5 & up Linux

Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPv4, IPv6) Scan: Email, SMB, WSD-Scan(IPv4, IPv6), FTP-Scan, iFAX TCP/IP Application Services: Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6) DHCP, ARP+PING, Auto IP, WINS (IPv4) DHCPv6 (IPv6)

Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security (wired): IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)

Security (wireless): WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(AES)



TECHNICAL SPECIFICATIONS

i-SENSYS MF421dw \ MF426dw \ MF428x \ MF429x

Software and printer management

MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, IW Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: envices such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager (MF428x, MF429x only) uniFLOW online (MF428x, MF429x, only) uniFLOW online Express (MF428x, MF429x only) uniFLOW compatibility with embedded uniFLOW Login Device Client (MF428x, MF429x only)

GENERAL FEATURES

Recommended Monthly Print Volume Duty cycle Processor Speed Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment

Power Source Power Consumption

Noise Levels

750 - 4,000 pages per month

Max. 80,000 pages per month⁷ 800MHz x 2 1GB 12.7 cm LCD Colour Touch Screen 453 mm x 464 mm x 392 mm

682 mm x 1.083 mm x 895 mm

Approx. 16.9 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V(±10%) 50/60Hz (±2Hz) Maximum: Approx. 130 W Standby: Approx. 130 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.2 kWh/week (230V) For detailed information relating to Lot26 regulation, charae on the standard s please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx Sound Pressure[®] : Active: 55 dB Standby: Inaudible⁹ Sound Power⁸: Active: 72.2 dB Standby: Inaudible⁶

CONSUMABLES Cartridges

Accessories/ options Items

Cartridge 052 (3,100 pages ¹⁰)¹¹ Cartridge 052H (9,200 pages ¹⁰)¹¹

CST.Feeding Module-AH1 (550-sheet cassette) TEL 6 Kit Long Cord (Telephone handset) (MF426dw, MF429x only) Barcode Printing Kit-EIE (MF428x, MF429x only) MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) (MF428x, MF429x only) MiCard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) (MF428x, MF429x only) MiCard Attachment Kit-B1 (MF428x, MF429x only) Send PDF Security Feature Set-E1 (MF428x, MF429x only)

Notes:

⁽¹⁾ A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device. ^[2] Accessory - Barcode Printing Kit-E1E - is required

^[3] Accessory - Send PDF Security Feature Set-E1 is required

^[4] Scan by MF Scan Utility or Canon PRINT Business app

^[5]Based on ITU-T Standard Chart No. 1

^[6]Linux support both printing and scanning Available from December 2018.

⁽⁷⁾ Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product ^[8] Declared noise emission in accordance with ISO 9296

⁽⁹⁾ Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

^[10] Based on ISO/IEC 19752

[11] Printer ships with Cartridge 052 (3,100 pages)

Canon (UK) Ltd

Woodhatch Reigate Surrey RH2 8BF Telephone No: 01737 220000 Facsimile No: 01737 220022 canon.co.uk

Canon Inc. Canon.com

Canon Europe canon-europe.com

UK English Edition © Canon Europa N.V., 2018

Canon

RELIABLE, SECURE AND EASY-TO-USE MULTI-FUNCTION PRINTER FOR AN OFFICE OR SME.

The i-SENSYS MF420 series is a multi-function printer offering SMEs speed, durability, and quality. Mobile connectivity maximises productivity.

Sales Start Date: April 2018

i-SENSYS MF421dw \ MF426dw \ MF428x \ MF429x



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
i-SENSYS MF421dw GB	2222CO41AA	8714574657042
i-SENSYS MF426dw GB	2222C032AA	8714574656953
i-SENSYS MF428x GB	2222C027AA	8714574656908
i-SENSYS MF429x GB	2222C018AA	8714574656731

ACCESSORIES:

Product Name	Mercury Code	EAN Code
Cassette Feeding Module-AH1	0732A033AA	4549292092769
– MiCard Attachment kit-B1	5146B002AA	4549292027235
Barcode Printing Kit-E1E	5143B002AA	N/A (e-delivery)
Send PDF Security Feature Set-E1	9594B002AA	N/A (e-delivery)
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910
Telephone 6 Kit UK (CW)	0752A053AA	4960999453897
Telephone 6 Kit SA (CW)	0752A055AA	4960999453927

CONSUMABLES:

Product Name	Mercury Code	EAN Code
Cartridge 052	2199C002AA	4549292089400
Cartridge 052 H	2200C002AA	4549292089424

EASY SERVICE PLAN:

Product Name	Mercury Code	EAN Code
Installation service	7950A546AA	4960999794426
- 3-year on-site next day service-Pack C (MF426dw & MF429x)	7950A527AA	4960999793313
	7950A526AA	4960999793306

Canon