Clear-Guard™ range

Medium efficiency

The Clear-Guard range of breathing filters includes a number of options, all designed for use in breathing and anaesthetic systems for the protection of the patient, hospital personnel and the equipment from potential microbial contamination. Designed with a rounded ergonomic polypropylene housing, the Clear-Guard 3 range represents our most cost-effective filter option, and is available with an integral 90° elbow, reducing the need for an additional catheter mount or separate patient elbow.

The Clear-Guard Midi low volume filter provides a further option with minimum deadspace; ideal for use in anaesthesia.

Make an enquiry Clear-Guard 3				(b)
Code	1544007	1544000	1544011	1544012
Box City.	150	150	75	75
Luer lock port	1	-	1	
Filtration efficiency	>99.99%	>99.99%	>99.99%	>99.99%
Resistance to flow at 30L/min	0.9cm H ₂ O	0.8cm H ₂ O	0.9cm H ₂ O	1.2cm H ₂ O
Resistance to flow at 60L/min	1,9cm H ₂ O	1.9cm H₃O	2.5cm H₂O	3.3cm H ₂ O
Compressible volume	60ml	60ml	60ml*	60mi*
Weight	279	289	42g	43g
Connectors	22F/15M-22M/15F	22F/15M-22M/15F	22F/15M-22M/15F	22F/15M-22M/15F
Minimum tidal volume	>200ml	>200ml	>200ml	>200ml
Accessories			Superset** catheter mount** 3504000	Superset™ catheter mount with fixed elbow** 3502000



3501000



Refer to information on catheter mount volumes in Patient Connections.

