

Touch Screen Constant-Temperature Incubator

Features:

- * Large LCD touch screen.
- * D type: with inner glass door.
G type: with viewing window.
- * Microprocessor controller.
- * Stainless steel chamber.

Safety Functions:

- * Over temperature alarm.
- * Independent limit temperature alarm system.
- * Leakage current and over-voltage protector.

Standard Accessories:



Test port

Optional Accessories:



Base stand



Footmaster Caster



UV lamp

Technical Parameters:

Model	BJPX-H54BK(D/G)	BJPX-H88BK(D/G)	BJPX-H160BK(D/G)
Capacity	54L	88L	160L
Temperature Control Method	PT100		
Temperature Range	RT+5~85°C		
Temperature Stability	±0.5°C (at 37°C)		
Temperature Uniformity	±1°C (at 37°C)		
Ambient Temperature	5~30°C, recommend 25°C±2°C		
Timing Range	0~99.9h		
Shelves	2pcs/adjustable		
Power Consumption	345W		495W
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional)		
Internal Size(W*D*H)mm	395*346*395	500*364*500	558*518*600
External Size(W*D*H)mm	D type: 536*588*681 G type: 522*626*587	D type: 650*573*793 G type: 627*621*692	D type: 718*732*890 G type: 685*779*790
Package Size(W*D*H)mm	D type: 606*648*818 G type: 592*676*724	D type: 720*630*930 G type: 697*671*829	D type: 788*792*1027 G type: 755*829*927
Gross Weight(kg)	D type: 51 G type: 44	D type: 65 G type: 51	D type: 89 G type: 69

Constant-Temperature Incubator

Features:

- * LCD display.
- * Microcomputer temperature controller.
- * Double door design and magnetic door sealing.
- * Castors are equipped for easy movement.
- * The working chamber adopts round angle structure, easy to clean.

Safety Functions:

- * Over temperature protection, temperature sensor malfunction alarm.
- * Parameters can be saved automatically when power off or system error.

Technical Parameters:

Model	BJPX-H35	BJPX-H50II	BJPX-H80II	BJPX-H160II	BJPX-H270II
Capacity	35L	48L	84L	160L	270L
Temp. Range	RT+5~65°C				
Temp. Fluctuation	±0.3°C				
Time Range	0~5999mins				
Shelves	2pcs/adjustable			3 pcs/adjustable	
Consumption	200W	437W	502W	580W	688W
Power Supply	Standard:AC220V,50/60Hz; Optional:AC220V,60Hz; AC110V,60Hz				
Internal Size(mm)	340*320*320	350*348*400	410*405*510	505*455*700	600*600*750
External Size(mm)	620*490*490	510*548*740	570*590*850	673*645*1033	768*795*1083
Package Size(mm)	740*600*670	590*650*930	730*700*1030	800*800*1210	930*940*1250
Gross Weight(kg)	31	50	75	99.5	150



Double-layer Door (D type)



Glass Viewing Window Door (G type)



BJPX-H35



BJPX-H50/80/160/270II