

SPECIFICAȚII TEHNICE (F4.1)

Numărul licitației: nr. ocds-b3wdp1-MD-1584002450127	02.04.2020	Alternativa nr.-
Denumirea licitației: Serviciul de Protecție și Pază de Stat	1,3,4	Pagina 1 din 1

LOT	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
1	Calculatoare (sisteme desktop)	ATOL	MDA	AE	Conform Caietului de Sarcini	<p>*Intel® Core™ i5-9400, S1151, 2.9-4.1GHz (6C/6T), 9MB Cache, Intel® UHD Graphics 630, 14nm 65W, Box</p> <p>*GIGABYTE Z390 D, Socket 1151, Intel® Z390 (9th/8th Gen CPU), Dual 4xDDR4-4266, CPU Intel graphics, HDMI, 3xPCIe X16, 6xSATA3, RAID, 1xM.2, 3xPCIeX1, ALC887 HDA, GbE LAN, 8xUSB3.1, RGB Lightning, ATX</p> <p>*8GB DDR4-3200 Kingston ValueRam, PC25600, CL22, 1.2V, 1Rx8 M.2 NVMe</p> <p>*SSD 500GB Kingston A2000, Interface: PCIe3.0 x4 / NVMe1.3, M2 Type 2280 form factor, Sequential Reads 2200 MB/s, Sequential Writes 2000 MB/s, Max Random 4k Read 180,000 / Write 200,000 IOPS, SM2263EN controller, 96-layer 3D NAND TLC</p> <p>*DEEPCOOL "D-SHIELD V2" ATX Case, with Side-Window, without PSU, 1x120mm rear fan, Bottom mounted PSU, Optimized space contracted design, VGA Compatibility: 370mm, 1xUSB3.0, 2xUSB2.0 /Audio, Black</p> <p>*PSU DEEPCOOL "DN650 New version", 650W, ATX 2.31, 80 PLUS®, Active PFC, 120mm fan with PWM, +12V (50A), 20+4 Pin, 1xEPS(4+4Pin), 5x SATA, 4xPCI-E(6+2pin), 3x Peripheral, MTBF100000Hours, CircuitShield™,</p> <p>*SVEN RX-110, Optical Mouse, 1000 dpi, USB, Black</p> <p>*ZALMAN "ZM-K200M",</p> <p>Multimedia Keyboard, 10-Keys, Ergonomically designed, 8 Blue colored direction keys, USB, Black</p> <p>*Gembird Mouse pad MP-A1B1-GREY, Cloth mouse pad, 220x250x4 mm, Grey</p> <p>*TP-LINK TG-3468, 32-bit Gigabit PCIe Network Interface Card, Realtek RTL8168B, 10/100/1000Mbps Auto-Negotiation RJ45 port, Auto MDI/MDIX</p> <p>*SVEN 248 Black (USB), 2.0 / 2x3W RMS, USB/DC 5V power supply, headphone jack, AUX input, 2.8"</p> <p>*UPS APC BE850G2-RS</p> <p>*Surge Protector SVEN SF-05L, 5 Sockets, 3.0m, Black</p> <p>*23.8" AOC IPS LED 24P1 Black 3-sides Borderless (5ms, 50M:1, 250cd, 1920x1080, 178°/178°, VGA, DVI, DisplayPort, HDMI, USB Hub: 4 x USB3.0, Speakers 2 x 2W, Audio Line-out, Pivot, Height-adjustable, VESA)</p> <p>*Cable Extension CCP-USB3-AMAF-6, 1.8 m,</p> <p>*USB3.0 super-speed A-plug A-socket, Gold-plated contacts, Blue</p> <p>*Garanție 2 ani, timp maxim de remediere 30 zile, în caz de trimitere a blocul de sistem la service, hard discurile nu se vor preda.</p>	ISO
3	Imprimanta laser	LBP6030	CHINA	Canon	Conform Caietului de Sarcini	<p>*Printer Canon i-Sensys LBP6030 Black, A4, 2400x600 dpi, 18ppm, 60-163 g/m2, 32lb+SCoA Win, CAPT, Max. 5k pages per month, Paper Input: 150-sheet tray, 7.8 seconds First Print Out Time, USB 2.0,</p> <p>*Cartridge 725 (1600 pages 5%) 700 pages starter Laser Cartridge Canon 725 (HP CE285A), black (1600 pages) for LBP-6030/6020/6000 and MF3010</p> <p>*Cable USB2.0 - 3m - Cablexpert - CCP-USB2-AMBM-10, 3m, Professional series, USB 2.0 A-plug B-plug, Black</p> <p>*Garanție 2 ani, timp maxim de remediere 30 zile</p>	ISO
4	Dispozitiv multifuncțional	MF443dw	CHINA	Canon	Conform Caietului de Sarcini	<p>*MFD Canon i-Sensys MF443DW, Mono Printer/DADF/Duplex/Scanner/Net,WiFi, A4, 1200x1200 dpi, 38ppm, Up to 80k ,1Gb, Scan 9600x9600dpi-24 bit, 12.7 cm LCD,Paper Input 250-sheet tray, 100-sheet tray, USB 2.0,</p> <p>*Cartridge 057/057H (2400/10000 pages* 5%) Laser Cartridge Canon 057H (3010C002)</p> <p>*Cable USB2.0 - 3m - Cablexpert - CCP-USB2-AMBM-10, 3m, Professional series, USB 2.0 A-plug B-plug, Black</p> <p>*Garanție 2 ani, timp maxim de remediere 30 zile</p>	ISO

Semnat: _____

Nume: **Cobîlaș Eugeniu**

În calitate de: Administrator

Ofertantul: „Accent Electronic” SA

Adresa: or. Chișinău, str. Bulgară 33/1

Data: 02.04.2020