

Radifocus™ Guide Wire M

Standard Type

Guide Wire



Description

Characteristics

Preparation

General specifications

Item specifications

Downloads



Description



For more than 40 years, RADIFOCUS™ Guide Wire M has been the gold standard for leaders in interventional care. Together, we have transformed the field, from pioneering technology to setting new standards in crossability and trackability.



Preparation

General specifications

Item specifications

Downloads

As we celebrate this important milestone, we invite you to experience our broad product portfolio and imagine a bright future for patient care.

Guide Wire M Standard type is a Nitinol hydrophilic guide wire covered with polyurethane containing tungsten and a hydrophilic polymer coating (M Coat) for vessel access, lesion crossing and device support.

Designed to direct a catheter to the desired anatomical location in the vascular system (peripheral, cerebral as well as coronary vasculature) during diagnostic or interventional procedures.

Characteristics

Preparation

General specifications

Item specifications

Downloads

- Highly flexible, tapered tip for atraumatic and controlled navigation through vessels
- M Coat hydrophilic coating for low friction endovascular steerability and trackability
- Radiopaque polyurethane jacket for good fluoroscopic visibility and controlled navigation
- Superelastic Nitinol core:
 - features adaptable shape memory and high flexibility
 - prevents kinking for swift device exchange
- One-piece construction with one-to-one torque transmission for predictable navigation
- Rounded, atraumatic tip for the prevention of vessel trauma and low friction guidewire insertion

Description

Characteristics

Preparation

General specifications

Item specifications

Downloads

General specifications

Core material

Nitinol

Radiopaque jacket

Polyurethane layer containing tungsten

Hydrophilic coating

M Coat

Guidewire diameters

0.018" (0.46 mm + 0.02 mm)* / 0.025" (0.64 mm + 0.00 mm)* /
0.032" (0.81 mm + 0.00 mm)* /
0.035" (0.89 mm + 0.01 mm)* / 0.038" (0.97 mm + 0.02 mm)*

Guidewire lengths

50 cm / 80 cm / 120 cm / 150 cm / 180 cm / 220 cm / 260 cm /
300 cm / 400 cm / 450 cm



General specifications

Distal flexible lengths

1 cm / 3 cm / 5 cm / 8 cm

Item specifications

Distal curves

Straight / Angled / 1.5 mm J shape / 3 mm J shape

Downloads

Units per box

5

Characteristics

Item specifications

Preparation

RF*GA35453M, RF*GS35403M, RF*GS35453M, RF*GR35153M

General specifications

Above items may have additional lead time. Please contact your Terumo representative for more information.

Item specifications

Downloads

Product code	Wire type	Outer diameter	Length	Flexible tip length curve	Tip shape
RF-GA18053M	Standard	0.018" (0.46 mm + 0.02 mm)*	50 cm	3 cm	Angled
RF-GA18153M	Standard	0.018" (0.46 mm + 0.02 mm)*	150 cm	3 cm	Angled
RF*GA18153M	Standard	0.018" (0.46 mm + 0.02 mm)*	150 cm	3 cm	Angled
RF-GS18153M	Standard	0.018" (0.46 mm + 0.02 mm)*	150 cm	3 cm	Straight
RF*GS18153M	Standard	0.018" (0.46 mm + 0.02 mm)*	150 cm	3 cm	Straight



Characteristics

Preparation

General specifications

Item specifications

Downloads

Characteristics

Preparation

General specifications

Item specifications

Downloads

RF-GA18183M

Standard

0.018" (0.46 mm + 0.02 mm)*

180 cm

3 cm

Angled

RF-GA18183M

Standard

0.018" (0.46 mm + 0.02 mm)*

180 cm

3 cm

Angled

RF-GS18183M

Standard

0.018" (0.46 mm + 0.02 mm)*

180 cm

3 cm

Straight

RF-GS18183M

Standard

0.018" (0.46 mm + 0.02 mm)*

180 cm

3 cm

Straight

RF-GA18223M

Standard

0.018" (0.46 mm + 0.02 mm)*

220 cm

3 cm

Angled

RF-GA18223M

Standard

0.018" (0.46 mm + 0.02 mm)*

220 cm

3 cm

Angled

RF-GA18263M

Standard

0.018" (0.46 mm + 0.02 mm)*

260 cm

3 cm

Angled

RF-GA18263M

Standard

0.018" (0.46 mm + 0.02 mm)*

260 cm

3 cm

Angled

RF-GS18263M

Standard

0.018" (0.46 mm + 0.02 mm)*

260 cm

3 cm

Straight

RF-GS18263M

Standard

0.018" (0.46 mm + 0.02 mm)*

260 cm

3 cm

Straight

RF-GA25053M

Standard

0.025" (0.64 mm + 0.00 mm)*

50 cm

3 cm

Angled

RF-GA25123M

Standard

0.025" (0.64 mm + 0.00 mm)*

120 cm

3 cm

Angled

RF-GA25123M

Standard

0.025" (0.64 mm + 0.00 mm)*

120 cm

3 cm

Angled

RF-GS25123M

Standard

0.025" (0.64 mm + 0.00 mm)*

120 cm

3 cm

Straight

RF-GS25123M

Standard

0.025" (0.64 mm + 0.00 mm)*

120 cm

3 cm

Straight

RF-GA25153M

Standard

0.025" (0.64 mm + 0.00 mm)*

150 cm

3 cm

Angled

RF-GA25153M

Standard

0.025" (0.64 mm + 0.00 mm)*

150 cm

3 cm

Angled

RF-GS25153M

Standard

0.025" (0.64 mm + 0.00 mm)*

150 cm

3 cm

Straight

RF-GS25153M

Standard

0.025" (0.64 mm + 0.00 mm)*

150 cm

3 cm

Straight

Privacy - Terms

Description

RF-GA25183M

Standard0.025" (0.64 mm + 0.00 mm)*180 cm3 cmAngled

Characteristics

RF*GA25183M

Standard0.025" (0.64 mm + 0.00 mm)*180 cm3 cmAngled

Preparation

RF-GS25183M

Standard0.025" (0.64 mm + 0.00 mm)*180 cm3 cmStraight

General specifications

RF*GS25183M

Standard0.025" (0.64 mm + 0.00 mm)*180 cm3 cmStraight

RF-GA25263M

Standard0.025" (0.64 mm + 0.00 mm)*260 cm3 cmAngled

Item specifications

RF*GA25263M

Standard0.025" (0.64 mm + 0.00 mm)*260 cm3 cmAngled

Downloads

RF-GS25263M

Standard0.025" (0.64 mm + 0.00 mm)*260 cm3 cmStraight

RF*GS25263M

Standard0.025" (0.64 mm + 0.00 mm)*260 cm3 cmStraight

RF-GA32123M

Standard0.032" (0.81 mm + 0.00 mm)*120 cm3 cmAngled

RF*GA32123M

Standard0.032" (0.81 mm + 0.00 mm)*120 cm3 cmAngled

RF-GS32123M

Standard0.032" (0.81 mm + 0.00 mm)*120 cm3 cmStraight



Description

Characteristics

Preparation

General specifications

Item specifications

Downloads

RF*GS32123M	Standard	0.032" (0.81 mm + 0.00 mm)*	120 cm	3 cm	Straight	
RF-GA32153M	Standard	0.032" (0.81 mm + 0.00 mm)*	150 cm	3 cm	Angled	
RF*GA32153M	Standard	0.032" (0.81 mm + 0.00 mm)*	150 cm	3 cm	Angled	
RF-GS32153M	Standard	0.032" (0.81 mm + 0.00 mm)*	150 cm	3 cm	Straight	
RF*GS32153M	Standard	0.032" (0.81 mm + 0.00 mm)*	150 cm	3 cm	Straight	
RF-GA32183M	Standard	0.032" (0.81 mm + 0.00 mm)*	180 cm	3 cm	Angled	
RF*GA32183M	Standard	0.032" (0.81 mm + 0.00 mm)*	180 cm	3 cm	Angled	
RF-GS32183M	Standard	0.032" (0.81 mm + 0.00 mm)*	180 cm	3 cm	Straight	
RF*GS32183M	Standard	0.032" (0.81 mm + 0.00 mm)*	180 cm	3 cm	Straight	
RF-GA32263M	Standard	0.032" (0.81 mm + 0.00 mm)*	260 cm	3 cm	Angled	
RF*GA32263M	Standard	0.032" (0.81 mm + 0.00 mm)*	260 cm	3 cm	Angled	



Privacy - Terms

Description

RF-GS32263M

Standard

0.032" (0.81 mm + 0.00 mm)*

260 cm

3 cm

Straight

Characteristics

RF*GS32263M

Standard

0.032" (0.81 mm + 0.00 mm)*

260 cm

3 cm

Straight

Preparation

RF-GA35053M

Standard

0.035" (0.89 mm + 0.01 mm)*

50 cm

3 cm

Angled

General specifications

RF-GA35083M

Standard

0.035" (0.89 mm + 0.01 mm)*

80 cm

3 cm

Angled

Item specifications

RF*GA35083M

Standard

0.035" (0.89 mm + 0.01 mm)*

80 cm

3 cm

Angled

Downloads

RF-GA35123M

Standard

0.035" (0.89 mm + 0.01 mm)*

120 cm

3 cm

Angled

RF*GA35123M

Standard

0.035" (0.89 mm + 0.01 mm)*

120 cm

3 cm

Angled

RF-GS35123M

Standard

0.035" (0.89 mm + 0.01 mm)*

120 cm

3 cm

Straight

RF*GS35123M

Standard

0.035" (0.89 mm + 0.01 mm)*

120 cm

3 cm

Straight

RF-GA35151M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

1 cm

Angled



Privacy - Terms

Description

Characteristics

Preparation

General specifications

Item specifications

Downloads



RF*GA35151M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

1 cm

Angled

RF*GA35151M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

1 cm

Angled

RF GS35151M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

1 cm

Straight

RF*GS35151M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

1 cm

Straight

RF*GA35153M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

3 cm

Angled

RF*GR35153M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

3 cm

Angled
(1.5 mm)



RF*GB35153M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

3 cm

Angled
(3 mm)



RF*GS35153M

Standard

0.035" (0.89 mm + 0.01 mm)*

150 cm

3 cm

Straight



Privacy - Terms

Description

Characteristics

Preparation

General specifications

Item specifications

Downloads

RF-GA35155M
RF*GA35155M
RF-GS35155M
RF*GS35155M
RF-GA35158M
RF*GA35158M
RF-GS35158M
RF*GS35158M
RF-GA35181M
RF*GA35181M
RF-GS35181M
RF*GS35181M
RF-GA35183M

Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	5 cm	Angled
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	5 cm	Angled
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	5 cm	Straight
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	5 cm	Straight
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	8 cm	Angled
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	8 cm	Angled
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	8 cm	Straight
Standard	0.035" (0.89 mm + 0.01 mm)*	150 cm	8 cm	Straight
Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	1 cm	Angled
Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	1 cm	Angled
Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	1 cm	Straight
Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	1 cm	Straight
Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	3 cm	Angled



Download Terms

Characteristics

Preparation

General specifications

Item specifications

Downloads

RF*GR35183M	Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	3 cm	Angled (1.5 mm)
RF-GS35183M	Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	3 cm	Straight
RF*GS35183M	Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	3 cm	Straight
RF*GA35188M	Standard	0.035" (0.89 mm + 0.01 mm)*	180 cm	8 cm	Angled
RF-GA35223M	Standard	0.035" (0.89 mm + 0.01 mm)*	220 cm	3 cm	Angled
RF*GA35223M	Standard	0.035" (0.89 mm + 0.01 mm)*	220 cm	3 cm	Angled
RF-GS35223M	Standard	0.035" (0.89 mm + 0.01 mm)*	220 cm	3 cm	Straight
RF*GS35223M	Standard	0.035" (0.89 mm + 0.01 mm)*	220 cm	3 cm	Straight
RF-GA35261M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	1 cm	Angled
RF*GA35261M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	1 cm	Angled
RF-GS35261M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	1 cm	Straight
RF*GS35261M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	1 cm	Straight
RF*GA35263M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	3 cm	Angled

Characteristics

Preparation

General specifications

Item specifications

Downloads

RF*GR35263M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	3 cm	Angled (1.5 mm)
RF-GS35263M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	3 cm	Straight
RF*GS35263M	Standard	0.035" (0.89 mm + 0.01 mm)*	260 cm	3 cm	Straight
RF-GA35303M	Standard	0.035" (0.89 mm + 0.01 mm)*	300 cm	3 cm	Angled
RF*GA35303M	Standard	0.035" (0.89 mm + 0.01 mm)*	300 cm	3 cm	Angled
RF-GS35303M	Standard	0.035" (0.89 mm + 0.01 mm)*	300 cm	3 cm	Straight
RF*GS35303M	Standard	0.035" (0.89 mm + 0.01 mm)*	400 cm	3 cm	Angled
RF-GA35403M	Standard	0.035" (0.89 mm + 0.01 mm)*	400 cm	3 cm	Straight
RF*GA35403M	Standard	0.035" (0.89 mm + 0.01 mm)*	400 cm	3 cm	Straight
RF-GA35453M	Standard	0.035" (0.89 mm + 0.01 mm)*	450 cm	3 cm	Angled
RF*GS35453M	Standard	0.035" (0.89 mm + 0.01 mm)*	450 cm	3 cm	Straight
RF-GA38151M	Standard	0.038" (0.97 mm + 0.02 mm)*	150 cm	1 cm	Angled
RF*GA38151M	Standard	0.038" (0.97 mm + 0.02 mm)*	150 cm	1 cm	Angled



Privacy - Terms

Description

RF*GA38153M	Standard	0.038" (0.97 mm ± 0.02 mm)*	150 cm	3 cm	Angled
RF*GS38153M	Standard	0.038" (0.97 mm ± 0.02 mm)*	150 cm	3 cm	Straight
RF*GS38153M	Standard	0.038" (0.97 mm ± 0.02 mm)*	150 cm	3 cm	Straight
RF*GA38183M	Standard	0.038" (0.97 mm ± 0.02 mm)*	180 cm	3 cm	Angled
RF*GA38183M	Standard	0.038" (0.97 mm ± 0.02 mm)*	180 cm	3 cm	Angled
RF*GS38183M	Standard	0.038" (0.97 mm ± 0.02 mm)*	180 cm	3 cm	Straight
RF*GS38183M	Standard	0.038" (0.97 mm ± 0.02 mm)*	180 cm	3 cm	Straight
RF*GA38223M	Standard	0.038" (0.97 mm ± 0.02 mm)*	220 cm	3 cm	Angled
RF*GA38223M	Standard	0.038" (0.97 mm ± 0.02 mm)*	220 cm	3 cm	Angled
RF*GA38263M	Standard	0.038" (0.97 mm ± 0.02 mm)*	260 cm	3 cm	Angled
RF*GA38263M	Standard	0.038" (0.97 mm ± 0.02 mm)*	260 cm	3 cm	Angled
RF*GS38263M	Standard	0.038" (0.97 mm ± 0.02 mm)*	260 cm	3 cm	Straight
RF*GS38263M	Standard	0.038" (0.97 mm ± 0.02 mm)*	260 cm	3 cm	Straight

Characteristics

Preparation

General specifications

Item specifications

Downloads