

SPECIFICATIONS

PKC4000

PKC4000-NDI

CONNECTIONS	Interfaces IP(RJ45)×1, RS-232×1, RS-485/RS-422×4, TALLY×1, USB2.0 (For upgrade)
	IP Protocol ONVIF, VISCA-IP ONVIF, VISCA-IP, NDI@ HX, NDI@ HX2
	Serial Protocol PELCO-D, PELCO-P, VISCA
	Serial Baud Rate 2400, 4800, 9600, 19200, 38400, 115200 bps
	LAN Port 1000M×1 (PoE/PoE+ : IEEE802.3 af/at)
	Display 5 inch Touch Screen
USER INTERFACES	Knob Quickly control iris, shutter speed, gain, auto exposure, white balance, etc.
	Joystick Pan/Tilt/Zoom
	Camera Group 10 (Each group connect up to 10 cameras)
	Camera Address Up to 100
	Camera Preset Up to 255
POWER	Power PoE/ DC 7~24V
	Power Consumption PoE: <8W, DC: <8W
ENVIRONMENT	Working Temperature -20°C~60°C
	Storage Temperature -20°C~70°C
DIMENSION	Dimension(LWD) 340mm×195mm×49.5mm/ 340mm×195mm×110.2mm(With joystick)
	Weight Net: 1730g, Gross : 2360g

ACCESSORIES



12V 2A Power Adapter



Tally Connector

