



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

ENEC Certification Body registered under ID 30. Validity of ENEC+ licences can be checked at www.enecplus.eu
Jednostka Certyfikująca ENEC zarejestrowana pod numerem ID 30. Ważność licencji ENEC+ można sprawdzić na www.enecplus.eu

LICENCE

to use the ENEC+ Mark



Licence/Certificate No. / Licencja/ Certyfikat Nr **0085/ENEC+/22**

Under the conditions given in the following pages of this document, the licence to use the ENEC+ Mark in conjunction with the suffix 30, as shown above, has been issued to:

Zgodnie z warunkami przedstawionymi na następujących stronach tego dokumentu, licencja na używanie Znaku ENEC+ w połączeniu z przyrostkiem 30, jak ukazano powyżej, została wydana dla:

LUG Light Factory Sp. z o.o.
ul. Gorzowska 11; 65-127 Zielona Góra, Poland

For the product: Dla wyrobów:

Luminaires for road and street lighting *Oprawy oświetleniowe drogowe i uliczne*

Trade name(s): Znak towarowy:



Type(s)/Model(s): Typ(y), model(e):

URBINO LED IK10 family cl. II – series – see the Appendix/ szczegóły – patrz Załącznik

Complying with the following EPRS for performance: Zgodnymi z następującym EPRS dot. cech funkcjonalnych

EPRS 003:2018-05 based on/ opartym na

EN 62722-2-1:2016 - see the test report / patrz raport z badań:

B10-3/166/B/22 dated / z dnia 2022-09-30 performed by the Testing Laboratory Łukasiewicz-IMiF PREDOM Division (Accreditation PCA AB 003) + (Appendix No 1 – lists of the luminaires – on CD).

This ENEC+ Licence/Certificate is only valid in conjunction with: Niniejsza Licencja/certyfikat ENEC+ jest ważna tylko w połączeniu z

ENEC Licence/Certificate No.: Licencją/ Certyfikatem ENEC Nr:

0296/ENEC/22 dated 2022-09-30 **issued by:** Łukasiewicz- IMiF PREDOM Division

Date: Data 2022-09-30

Signatures:

Name:

Józef Foks

Filip Walczak

Position:

Certification Office
Łukasiewicz- IMiF PREDOM
Division

Leader of the Łukasiewicz- IMiF
PREDOM Division

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Niniejsza licencja została wydana zgodnie z założeniem i pod warunkiem, że licencjobiorca posiada wszelkie niezbędne prawa w odniesieniu do wyrobu przedstawionego do badań i certyfikacji.

Additional information – see the Appendix. Dodatkowe informacje – patrz Załącznik.



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 1/13

Nazwa i adres posiadacza certyfikatu: <i>Name and address of the license holder:</i>	LUG Light Factory Sp. z o.o. . ul. Gorzowska 11 65-127 Zielona Góra Polska
Nazwa i adres producenta: <i>Name and address of manufacturer:</i>	LUG Light Factory Sp. z o.o. . ul. Gorzowska 11 65-127 Zielona Góra Polska
Nazwa i adres miejsca produkcji: <i>Name and address of manufacturing place:</i>	LUG Light Factory Sp. z o.o. . ul. Gorzowska 11 65-127 Zielona Góra Polska
Nazwa wyrobu: <i>Name of product:</i>	URBINO LED IK10 family cl. II – series
Typ (model): <i>Type (model):</i>	Oprawy uliczne
Znak handlowy: <i>Trade mark :</i>	LUG
Dane techniczne: <i>Technical data:</i>	
- rated voltage	220-240V
- rated frequency	50/60Hz
- rated power	Class II
- type of lamp	IP66
- protection against electric shock	IK10
- ta:	-40°C to 50°C -35°C to 50°C* -30°C to 50°C** -25°C to 50°C*** * - For luminaires equipped with: Vossloh Schwabe SPC/230/10K/i ** - For luminaires equipped with: Tridonic LCA 120W 300-1050mA Philips Xi FP 70W 0.3-1.0A NLD C150 230V sXt Philips Xi FP 110W 0.3-1.0A NLD C150 230V sXt Vossloh Schwabe SP/230/10K *** - For luminaires equipped with: LACROIX DL-PAK 70

Wykaz modeli:
List of models:

Choice sheet of the luminaires URBINO LED IK10 family cl II – series:
Example of symbol:

130822.5LR7B27S1405.201.B.V

1 2 3 4 5 6 7 8 9

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 2/13

Designations used on the marking of luminaries (some designation may not appear in the name) :

1	13075 13082	-	Code of the series URBINO LED IK10 with LED Cree XPG3 modules Code of the series URBINO LED IK10 with LED Luxeon 5050 modules
2	2	-	Color: 2: grey 5: graphite 0: another
3	5L	-	Type of power supply: 2L - DIMM 1-10V 3L - DALI 5L - on-off 6L - on-off / DALI 7L - ZHAGA D4i PL - programmable
4	R7	-	CRI: R7 = 70-79 R8 = 80-89
5	B27	-	Color temperature: B22 = 2200 B27 = 2700 B30 = 3000 B40 = 4000 B57 = 5700 B65 = 6500
6	S1405	-	Max. luminous flux (e.g. S1450 = 14050lm)
7	2	-	Safety Class II
8	01	-	Optic: 01 O1 - for road lighting type O1 02 O2 - for road lighting type O2 ... 99 O99 - for road lighting type O99
9	B.V	-	Additional equipment A - additional corrosion protection B - Tool-free access to the LED Driver U - ø76mm pole N - NEMA Socket Z - ZHAGA Socket T - NTC Sensor W - Twilight Sensor V - Surge Device Protector 10kV P- Anti pressure vent I- iBloc ("URBAN" smart city system) K- Knife switch connector



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 3/13

Luminaire	Used LED module	LED module ratings	ENEC for luminaire	Report for module
URBINO LED IK10 family	<p style="text-align: center;">LUXEON 5050 modules ML21XXXYY.WQQQ.UUV</p> <p style="text-align: center;">1 2 3 4 5 6 7 8</p> <p>Designations used on the marking of LED boards:</p> <p>1. ML - PCB designation (ML – LED module); 2. 21 - Year of the project; 3. XXX - Number of the project: <i>Luxeon modules: 660, 661, 663, 670, 671, 672, 673, 680, 681, 682, 683, 690, 691, 692, 693</i> 4. YY - Project variant (PCB design, milling, dimensions, soldermask color, laminate thickness, LED configuration): 00...99 5. W - Light color: W: White 6. QQQ - CRI and CCT: 722: CRI 70 and 2200K 727: CRI 70 and 2700K 730: CRI 70 and 3000K 735: CRI 70 and 3500K 740: CRI 70 and 4000K 750: CRI 70 and 5000K 757: CRI 70 and 5700K 765: CRI 70 and 6500K 822: CRI 80 and 2200K 827: CRI 80 and 2700K 830: CRI 80 and 3000K 835: CRI 80 and 3500K 840: CRI 80 and 4000K 850: CRI 80 and 5000K 857: CRI 80 and 5700K 865: CRI 80 and 6500K 7. UU - Assembly variant (selected components not mounted): 01...99 8. V - NTC Thermistor type: A - none B - 10K C - 47K</p>	Max 5,6A	0296/ENEC/22 dated 30-09-2022	ENEC+ for modules: 0066/ENEC+/21 Report No. Z7-3/144/B/21 Ł-IMiF PREDOM Division
	<p style="text-align: center;">CREE XPG3 modules ML21XXXYY.WQQQ.UUV</p> <p style="text-align: center;">1 2 3 4 5 6 7 8</p> <p>Designations used on the marking of LED boards:</p> <p>1. ML - PCB designation (ML – LED module); 2. 21 - Year of the project; 3. XXX - Number of the project: <i>Cree modules: 600, 601, 610, 611</i> 4. YY - Project variant (PCB design, milling, dimensions, soldermask color, laminate thickness, LED configuration): 00...99 5. W - Light color: W: White 6. QQQ - CRI and CCT: 722: CRI 70 and 2200K 727: CRI 70 and 2700K 730: CRI 70 and 3000K 735: CRI 70 and 3500K 740: CRI 70 and 4000K 750: CRI 70 and 5000K 757: CRI 70 and 5700K 765: CRI 70 and 6500K 822: CRI 80 and 2200K 827: CRI 80 and 2700K 830: CRI 80 and 3000K 835: CRI 80 and 3500K 840: CRI 80 and 4000K 850: CRI 80 and 5000K 857: CRI 80 and 5700K 865: CRI 80 and 6500K 7. UU - Assembly variant (selected components not mounted): 01...99 8. V - NTC Thermistor type: A - none B - 10K C - 47K</p>			ENEC+ for modules: 0078/ENEC+/22 Report No. B10-3/090/B/22 Ł-IMiF PREDOM Division

Possible configurations of luminaires and more information - see the Appendix No. 1 – Lists of the luminaires - on CD (data received from the manufacturer)

After construction review of the luminaires family and taking into account the clause 3.2 of the standard EN 62722-2-1 for test was chosen models:

130822.5LR7B27S1405.201.B.V with LED Module ML2167043.W727.01A:

- S1405= 14050lm,
- R7 = ≥ 70 CRI,
- B27 = 2700K.



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 4/13

Wykaz komponentów:
List of components:

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
LED Module	A	LUG	ML21XXXXYY.WQQQ.UUV (Luxeon 5050 modules) (choice sheet below)	Tc -40°C to +85°C	EN 62031	ENEC
<p>ML21XXXXYY.WQQQ.UUV 1 2 3 4 5 6 7 8</p> <p>Designations used on the marking of LED boards:</p> <p>1. ML - PCB designation (ML – LED module); 2. 21 - Year of the project; 3. XXX - Number of the project: Luxeon 5050 modules: 660, 661, 662, 663, 670, 671, 672, 673, 680, 681, 682, 683, 690, 691, 692, 693 4. YY - Project variant (PCB design, milling, dimensions, soldermask color, laminate thickness, LED configuration): 00...99 5. W - Light color: W: White 6. QQQ - CRI and CCT: 722: CRI 70 and 2200K 727: CRI 70 and 2700K 730: CRI 70 and 3000K 735: CRI 70 and 3500K 740: CRI 70 and 4000K 750: CRI 70 and 5000K 757: CRI 70 and 5700K 765: CRI 70 and 6500K 822: CRI 80 and 2200K 827: CRI 80 and 2700K 830: CRI 80 and 3000K 835: CRI 80 and 3500K 840: CRI 80 and 4000K 850: CRI 80 and 5000K 857: CRI 80 and 5700K 865: CRI 80 and 6500K 7. UU - Assembly variant (selected components not mounted): 01...99 8. V - NTC Thermistor type: A - none B - 10K C - 47K</p>						
LED Module	B	LUG	ML21XXXXYY.WQQQ.UUV (Cree XPG3 modules) (choice sheet below)	Tc -40°C to +85°C	EN 62031	Tested and accepted by PREDOM Division TR No. B10-3/089/B/22
<p>ML21XXXXYY.WQQQ.UUV 1 2 3 4 5 6 7 8</p> <p>Designations used on the marking of LED boards:</p> <p>1. ML - PCB designation (ML – LED module); 2. 21 - Year of the project; 3. XXX - Number of the project: Cree XPG3 modules: 600, 601, 610, 611 4. YY - Project variant (PCB design, milling, dimensions, soldermask color, laminate thickness, LED configuration): 00...99 5. W - Light color: W: White 6. QQQ - CRI and CCT: 722: CRI 70 and 2200K 727: CRI 70 and 2700K 730: CRI 70 and 3000K 735: CRI 70 and 3500K 740: CRI 70 and 4000K 750: CRI 70 and 5000K 757: CRI 70 and 5700K 765: CRI 70 and 6500K 822: CRI 80 and 2200K 827: CRI 80 and 2700K 830: CRI 80 and 3000K 835: CRI 80 and 3500K 840: CRI 80 and 4000K 850: CRI 80 and 5000K 857: CRI 80 and 5700K 865: CRI 80 and 6500K 7. UU - Assembly variant (selected components not mounted): 01...99 8. V - NTC Thermistor type: A - none B - 10K C - 47K</p>						
Control gear	A	OSRAM	OT180W/UNV/800C/2DIMLT 2/P6	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT100W/UNV/800C/2DIMLT 2/P6	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 5/13

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	OSRAM	OT 110/170...240/1A0 1DIMLT2 G1 CE	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 20/170-240/1A0 1DIM LT2 G1 CE	220..240V, 50-60Hz, ta= -40...+60°C, tc max=75°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 75/170...240/1A0 1DIMLT2 G1 CE	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi Dim 250W 0.7A 1-10V 230V	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.3-1.0A S1 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCA 120W 300-1050mA	220..240V, 50-60Hz, ta= -30...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCA 75W 250-750mA one	220..240V, 50-60Hz, ta= -40...+70°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCA 120W 350-1050mA o	220..240V, 50-60Hz, ta= -40...+70°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCA 160W 350-1050mA o	220..240V, 50-60Hz, ta= -40...+70°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT DX 40/220...240/1A0 DIMA LT2 E	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT DX 75/220...240/1A0 DIMA LT2 E	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT DX 110/220...240/1A0 DIMA LT2 E	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT DX 165/220...240/1A0 DIMA LT2 E	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 20/170...240/1A0 4DIMLT2 G2 CE	220..240V, 50-60Hz, ta= -40...+60°C, tc max=75°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 40/170...240/1A0 4DIMLT2 G2 CE	220..240V, 50-60Hz, ta= -40...+60°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 75/170...240/1A0 4DIMLT2 G2 CE	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 110/170...240/1A0 4DIMLT2 G2 CE	220..240V, 50-60Hz, ta= -40...+60°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 20/170...240/1A0 1DIMLT2 G1 CE	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 40/170...240/1A0 1DIMLT2 G1 CE	220..240V, 50-60Hz, ta= -40...+60°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 40/120...277/1A0 4DIMLT2 E	220..240V, 50-60Hz, ta= -40...+60°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 60/170...240/1A0 4DIMLT2 E	220..240V, 50-60Hz, ta= -40...+60°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 90/170...240/1A0 4DIMLT2 E	220..240V, 50-60Hz, ta= -40...55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 165/170...240/1A0 4DIMLT2 E	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 6/13

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	OSRAM	OT 50/120...277/800 2DIMLT2 P	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 50/120...277/1A2 2DIMLT2 P	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 100/120...277/800 2DIMLT2 P	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 110/120...277/1A4 2DIMLT2 P	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 60/220...240/1A4 1DIMA P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 100/220...240/1A4 1DIMA P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 150/220...240/1A4 1DIMA P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 200/220...240/1A4 1DIMA P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=75°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 40W 0.7A Prog+ GL-J sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 75W 0.35-0.70A GL Prog+ sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 75W 0.1-1.05A Prog GL F sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 100W 0.7A Prog+ GL-Z sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 150W 0.1-1.05A Prog+ GL F sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 150W 0.35-0.70A GL Prog sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 300W 1.5A Prog+ GL-R sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi BP 12W 0.1-0.5A S 230V C100	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi BP 22W 0.2-0.7A S 230V C123	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi BP 40W 0.2-0.7A S 230V C123	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi BP 40W 0.3-1.0A S 230V C123	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 22W 0.2-0.7A S1 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 22W 0.3-1.0A S1 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.2-0.7A S1 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.3-1.0A S1 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.2-0.7A S1 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.3-1.0A S1 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.5-1.5A S1 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 110W 0.2-0.7A S1 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 7/13

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	Philips	Xi LP 110W 0.3-1.0A S1 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 165W 0.2-0.7A S1 230V C170 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 165W 0.3-1.0A S1 230V C170 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 165W 0.5-1.5A S1 230V C170 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 22W 0.2-0.7A S1 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 22W 0.3-1.0A S1 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.2-0.7A S1 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.2-0.7A SL 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.3-1.0A S1 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.3-1.0A SL 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 40W 0.2-0.7A SN 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.2-0.7A S1 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.2-0.7A SL 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.3-1.0A S1 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.3-1.0A SL 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.2-0.7A SN 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 75W 0.5-1.5A S1 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.2-0.7A S1 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.2-0.7A SL 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.3-1.0A SL 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.5-1.5A S1 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.2-0.7A SN 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 22W 0.2-0.7A SNLDAE 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 22W 0.3-1.0A SNLDAE 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 40W 0.2-0.7A SNLDAE 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 40W 0.3-1.0A SNLDAE 230V C123 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 70W 0.3-1.0A NLD C150 230V sXt	220..240V, 50-60Hz, ta= -30...+60°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 8/13

Object / part No.	Cod e	Manufactu rer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	Philips	Xi FP 75W 0.2-0.7A SNLDAE 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 75W 0.3-1.0A SNLDAE 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 75W 0.5-1.5A SNLDAE 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 100W 0.2-0.7A SNLDAE 230V C165 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 110W 0.2-0.7A SNLDAE 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 110W 0.3-1.0A NLD C150 230V sXt	220..240V, 50-60Hz, ta= -30...+60°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 110W 0.3-1.0A SNLDAE 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 165W 0.3-1.0A SNLDAE 230V C170 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 165W 0.2-0.7A SNLDAE 230V C170 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 330W 0.2-0.75A SNLDAE 230V C240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 22W 0.2-0.7A SNLDAE 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 22W 0.3-1.0A SNLDAE 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 40W 0.2-7.0A SNLDAE 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 40W 0.3-1.0A SNLDAE 230V S175 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 75W 0.2-0.7A SNLDAE 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 75W 0.3-1.0A SNLDAE 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 150W 0.2-0.7A SNLDAE 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi FP 150W 0.3-1.0A SNLDAE 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 12W 0.2-0.7A SNEMP 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 22W 0.2-0.7A SNEMP 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 40W 0.2-0.7A SNEMP 230V C133 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 75W 0.2-0.7A SNEMP 230V C150 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 75W 0.2-0.7A SNEMP 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 110W 0.2-0.7A SNEMP 230V C150 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi SR 150W 0.2-0.7A SNEMP 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 100W 2.1-4.2A AOC 230V I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 150W 2.5-4.9A AOC 230V I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 9/13

Object / part No.	Cod e	Manufactu rer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	Philips	Xitanium 200W 2.8-5.6A AOC 230V I250	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 100W 0.3-1.05A S1 230V I175	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 150W 0.3-1.05A S1 230V I175	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 220W 0.3-1.05A S1 230V I230	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xi LP 220W 0.5-1.5A S1 230V I230	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 35W 0.7A 1-10V TWE I175	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 100W 0.7A 1-10V TWE I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 150W 0.7A 1-10V TWE I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 75W 0.7A TWE I175	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 150W 0.7A TWE I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 75W 1.05A 1-10V 230V C165 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 75W 0.70A 1-10V 230V C165 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 150W 0.70A 1-10V 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 250W 0.70A 1-10V 230V Q	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 75W 0.70A 1-10V 230V I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 150W 0.70A 1-10V 230V I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium Dim 250W 0.70A 1-10V 230V I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 75W 1-10V 230V C165	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 150W 1.05A 1-10V 230V S240 sXt	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 250W 1-10V 230V I220	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Philips	Xitanium 250W 1-10V 230V Q	220..240V, 50-60Hz, ta= -40...+55°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 14/100-500/38 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 24/200-1050/39 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 40/200-1050/64 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 60/200-1050/100 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 90/200-1050/165 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=100°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 135/200-1050/220 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=100°C	EN 61347-1 EN 61347-2-13	ENEC

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 10/13

Object / part No.	Cod e	Manufactu rer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	Tridonic	LCO 200/200-1050/355 NF C ADV3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 14/100-500/38 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 24/200-1050/39 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 40/200-1050/64 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 60/200-1050/100 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=95°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 90/200-1050/165 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=100°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 135/200-1050/220 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=100°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 200/200-1050/355 o4a NF C EXC3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=100°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 100/1050/95 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 100/1400/71 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 100/500/200 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 100/700/143 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 150/1050/142 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 150/1400/107 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 150/500/300 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 150/700/214 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 200/1050/190 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 200/1400/142 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 200/500/400 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 200/700/285 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 75/1050/72 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 75/1400/53 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 75/500/150 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 75/700/108 fixC L SNC2	220..240V, 50-60Hz, ta= -40...+65°C, tc max=80°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 165/220...240/1A0 1DIM G2 CE	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 11/13

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	OSRAM	OT 165/170...240/1A0 4DIMLT2 G2 CE	220..240V, 50-60Hz, ta= -40...+55°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 200W 200-1050mA 355V pD+ NFC C PRE3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 135W 200-1050mA 220V pD+ NFC C PRE3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=95°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Tridonic	LCO 90W 200-1050mA 165V pD+ NFC C PRE3	220..240V, 50-60Hz, ta= -40...+70°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 100/UNV/1A0 2DIM P7	120..277V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 150/UNV/1A0 2DIM P7	120..277V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 200/UNV/1A0 2DIM P7	120..277V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 100/ 220-240/1A4 2DIM P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 150/ 220-240/1A4 2DIM P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 200/ 220-240/1A4 2DIM P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 240/ 220-240/1A0 2DIM P7	220..240V, 50-60Hz, ta= -40...+55°C, tc max=85°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EBS-040S105BT2	176..305V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EBS-080S070BT2	176..305V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EBS-080S105BT2	176..305V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EBS-040S070BT2	176..305V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EUM-075S	90..305V, 50-60Hz, ta= -40...+80°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EUM – 100S	100..277V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EUM – 150S	100..277V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EUM – 200S	100..277V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	Inventronics	EUM – 240S	100..277V, 50-60Hz, ta= -40...+75°C, tc max=90°C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	IT DALI 20/220...240/1A0 E	220...240 V/50/60Hz, Ta =-40...+60 °C, Tc max =75 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	IT DALI 40/220...240/1A0 E	220...240 V/50/60Hz, Ta =-40...+60 °C, Tc max =85 °C	EN 61347-1 EN 61347-2-13	ENEC



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 12/13

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Control gear	A	OSRAM	IT DALI 75/220...240/1A0 E	220...240 V/50/60Hz, Ta = -40...+60 °C, Tc max = 100 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	IT DALI 110/220...240/1A0 E	220...240 V/50/60Hz, Ta = -40...+60 °C, Tc max = 90 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	IT DALI 150/220...240/1A0 E	220...240, 50/60Hz, Ta = -40...+55 °C, Tc max = 85 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	LACROIX	DL-PAK 70	220...240 50/60Hz, Ta = -25...+60 °C, Tc max = 90 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	DELTA	EUCI-040105GLA	220...240 V/50/60Hz, Ta = -40...+60 °C, Tc max = 85 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	DELTA	EUCI-075105GLA	220...240 V/50/60Hz, Ta = -40...+55 °C, Tc max = 85 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	DELTA	EUCI-130105GLA	220...240 V/50/60Hz, Ta = -40...+55 °C, Tc max = 85 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	DELTA	EUCI-170105GLA	220...240 V/50/60Hz, Ta = -40...+55 °C, Tc max = 90 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	OSRAM	OT 75 /220...240/1A0 1DIM G2 CE	220...240V, 50/60Hz, Ta = -40...+55 °C, Tc max = 85 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	DELTA	EUCI-022105GLB	220...240V, 50/60Hz, Ta = -40...+55 °C, Tc max = 85 °C	EN 61347-1 EN 61347-2-13	ENEC
Control gear	A	DELTA	EUCI-040105GLB	198...264V, 50/60Hz, Ta = -40...+55 °C, Tc max = 90 °C	EN 61347-1 EN 61347-2-13	ENEC
Wires LED	B	Mrowiec	H05V-U	500 V; 0,5 mm ²	EN 50525	BBJ
Internal wires	B	Mrowiec	H05V-K	500 V; 0,5 mm ²	EN 50525	BBJ
Internal wires	B	E.M.C. Colosio	RD10-B	300/500 V; 0,5 mm ²	EN 50525	IMQ
Silicon Fiberglass Insulating Sleeving	B	Isolcavi	GVES 1500	min. 1500 Volt, Temp -60...+250°C	IEC 60684-3-400 IEC 60684-3-402	UL
Terminal block	B	Stucchi	651/652	16A; 400 V	EN-61984	IMQ
Terminal block	B	Stucchi	661/662	6A; 400 V	EN-61984	IMQ
Connector	B	BJB	48.281	16A; 400 V	EN 60998-2-2	VDE
Connector	B	BJB	46.412	16A; 450 V	EN 60998-2-2	VDE
Connector	B	BJB	46.413	16A; 450 V	EN 60998-2-2	VDE
Connector	B	BJB	46.414	16A; 450 V	EN 60998-2-2	VDE
Connector	B	BJB	46.415	16A; 450 V	EN 60998-2-2	VDE
Connector	B	BJB	46.455	16A; 450 V	EN 60998-2-2	VDE
Connector	B	WAGO	224-101	24A; 400 V	EN 60998-2-2	VDE
Connector	B	WAGO	224-112	24A; 400 V	EN 60998-2-2	VDE
Terminal block	B	Wieland	GST1814S	20A; 400 V	EN 61535	VDE
Terminal block	B	Wieland	GST 15I2	16A; 250 V	EN 61535	VDE
Connector	B	EMC Colosio	M26B	17A; 300 V	EN 60598-1	IMQ
Knife switch (connector)	B	Longran	M29 M29 mini	16A; 450 V 16A; 250 V	EN 61984 EN 60998-2-1 EN 60998-1	TUV
Connector	B	LONGJOING	JL-700	1.5A, 30V	EN 61984	DEKRA
Connector system	B	Tyco Electronics Corp.	2213795, 2213831, 2213837, 2213858, 2328823, 2329013	30V AC/DC 50/60HZ, 1.5A	EN 61984	UL



Łukasiewicz- IMiF PREDOM Division
53, Krakowiaków Str.
02-255 WARSAW, POLAND

APPENDIX TO THE LICENCE No. 0085/ENEC+/22 – page 13/13

Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Connector system	B	Tyco Electronics Corp.	1-2213871-1, 1-2213871-2, 2213871-1, 2213871-2, X-2213362-X, X-2213627-X	t= -40...+80°C, tc max=80°C 150/240/300VAC, 50/60Hz, 15/7.5/6 A, Signal Contacts: 30VDC, 1.5A	EN 61984	UL
Connector system	B	LUG	iBlock	230V, 50Hz, Ta = -40°C do 70°C	EN61347-2-11	Tested and accepted by PREDOM Division TR No. Z7-2/016/B/20
Connector system	B	LONGJOING Nema	JL-240XA	t= -40...+700C, 480VAC, 50/60Hz, Signal Contacts: 30VDC, 0,25A	EN 61984	DEKRA
Luminaire protection	B	Vossloh schwabe	SP / 230 / 10K	220-240V, 50/60Hz, Ta = -30°C do 80°C	EN 61643-11	VDE
Luminaire protection	B	Vossloh schwabe	SPC 230 / 10K / i	100-277V, 50/60Hz, Ta = -35°C do 80°C	EN 61643-11	DEKRA
Luminaire protection	B	Inventronics	PU-20KX10KTXX	320Vac, 8A, 47-63Hz, Ta = -40°C do 85°C	EN 61643-11 EN 61643-21	VDE
Luminaire protection	B	Inventronics	PU-20Kx10KBx	320Vac, 15A, 47-63Hz, Ta = -40°C do 85°C	EN 61643-11 EN 61643-21	VDE
Luminaire protection	B	Inventronics	PU-10Kx05KBx	320Vac, 8A, 47-63Hz, Ta = -40°C do 85°C	EN 61643-11 EN 61643-21	VDE
Luminaire protection	B	Linoya Electronic Technology	LYSPD10D	300Vac, 50Hz, IP67	EN 61643-11	TUV

Supplementary information:

¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039.

The codes above have the following meaning:

- A - The component is replaceable with another one, also certified, with equivalent characteristics
- B - The component is replaceable if authorised by the test house
- C - Integrated component tested together with the appliance
- D - Alternative component

Certification Body:

Łukasiewicz- IMiF PREDOM Division

Place: Warszawa

Signed:

Józef Foks

Filip Walczak

Date: 2022-09-30

.....
Certification Office
Łukasiewicz- IMiF PREDOM
Division

.....
Leader of the Łukasiewicz- IMiF
PREDOM Division