

CRACK DETECTOR DEVELOPER SPRAY

EN

Product identification

Part numbers:

WP22034 – CRACK DET.SPRAY DEVELOPER 400ml



Description & Applications

CRACK DETECTOR SPRAY DEVELOPER (Rivelex200) is a spray that detects the cracks or porosity caused by the welding in any kind of surface. Thanks to its composition, it can be rapidly used, because it contains solvents that evaporate quickly, leaving a white powder on the treated pieces, that detects the cracks.

It can be used with red and fluorescent penetrants (Spray PENETRANT).

CFC FREE

It does not damage the treated materials.

The bases utilized are conformed to

ASME 2644 - type II

MIL-I-25135 - form D, type II



Instructions for use:

Shake the can for a minute before use.

Spray the CRACK DETECTOR SPRAY DEVELOPER (Rivelex200) on the workpiece previously treated with Spray PENETRANT from a 20-30 cm distance.

Wait from 10 to 20 minutes for the product to be effective.

Inspect the treated materials

For professional use only.

Other Specifications:

Base	Mixture of white solvents and powders
Propellant	Denatured Hydrocarbon, odourless.
Appearance	WHITE liquid

Note

The date marked on the product is the production date. This product does not expire.

The recommended use is within 5 years from the production date as the propellant could lose effectiveness.