

Specificații tehnice (F4.1)

Numărul procedurii de achiziție ocds-b3wdp1-MD-1593159612334 din _____
Denumirea procedurii de achiziție: Tehnică de calcul/ Ecran de proiecție/ Proiectoare

Cod CPV	Denumirea bunurilor/serviciilor	Modelul articolului	Țara de origine	Prod u- cĂtor ul	Specificarea tehnicĂ deplină solicitată de către autoritatea contractantă	Specificarea tehnicĂ deplină propusă de către ofertant	Standar de de referință
	2	3	4	5	6	7	8
	Bunuri						
Lotul nr. 1: Tehnică de calcul							
30200000-1	Laptop	X509JA	China	Asus	<p><u>NB Grey (Core i3-8145U 4Gb 256Gb) 15.6" FHD (1920x1080)</u> Non-glare, Intel Core i3-8145U (2x Core, 2.1GHz - 3.9GHz, 4Mb), 4Gb (Onboard) PC4-19200, 256Gb PCIE, Intel UHD Graphics, HDMI, 802.11ac, Bluetooth, 1x USB 3.1 Type C, 1x USB 3.1, 2x USB 2.0, Card Reader, Webcam, Endless OS, 2-cell 32 WHrs Battery, 1.9kg, Slate Grey</p> <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>	<p>"NB ASUS 15.6"" X509JA Grey (Core i3-1005G1 4Gb 256Gb) 15.6"" FHD (1920x1080) Non-glare, Intel Core i3-1005G1 (2x Core, 1.2GHz - 3.4GHz, 4Mb), 4Gb (Onboard) PC4-19200, 256Gb PCIE, Intel UHD Graphics, HDMI, 802.11ac, Bluetooth, 1x USB-C, 1x USB 3.1, 2x USB 2.0, Card Reader, Webcam, No OS, 2-cell 32Wh Battery, 1.9kg, Slate Grey"</p> <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>	
30200000-1	Laptop	X512FA	China	Asus	<p><u>NB Silver (Core i3-8145U 8Gb 256Gb) 15.6" FHD (1920x1080)</u> Non-glare, Intel Core i3-8145U</p>	<p>"NB ASUS 15.6"" X512FA Silver (Core i3-8145U 8Gb 512Gb)</p>	



					<p>(2x Core, 2.1GHz - 3.9GHz, 4Mb), 4Gb (Onboard + 4Gb) PC4-19200, 256Gb PCIE, Intel UHD Graphics, HDMI, 802.11ac, Bluetooth, 1x USB 3.1 Type C, 1x USB 3.1, 2x USB 2.0, Card Reader, Webcam, Endless OS, 2-cell 32 WHrs Battery, 1.9kg, Transparent Silver</p> <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>	<p>15.6" FHD (1920x1080) Non-glare, Intel Core i3-8145U (2x Core, 2.1GHz - 3.9GHz, 4Mb), 8Gb (4Gb Onboard + 4Gb) PC4-19200, 512Gb PCIE, Intel UHD Graphics, HDMI, 802.11ac, Bluetooth, 1x USB 3.1 Type C, 1x USB 3.1, 2x USB 2.0, Card Reader, HD Webcam, No OS, 2-cell 37Wh Battery, Illuminated Keyboard, 1.7kg, Transparent Silver"</p> <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>
30200000-1	<p>Computer pentru elevi + boxe</p>	Navigator	RM	<p>Ultra Service</p>	<ul style="list-style-type: none"> • CPU Intel Core i3-9100F 3.6-4.2 GHz • MB CPUSupports 9th Gen Intel® Core™ Processors Chipset Intel® B365. Memory 2xDDR4 DIMM sockets supporting up to 32 GB of system memory. Support for DDR4 2666/2400/2133 MHz memory modules. 1xD-Sub port. 1xDVI-D port. 1xHDMI port. Audio Realtek® ALC887 codec. LAN Realtek® GbE LANchip (10/100/1000 Mbit). Storage Interface 1xM.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) • .4GBDDR4- 2666MHz • 2.5" SATA SSD- 256GB • Case ATX 500W • 21.5" • Keyboard & Mouse, USB Speakers, 6w <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>	<p>CPU Intel Core i3-9100 3.6-4.2GHz (4C/4T, 6MB, S1151,14nm, Integrated UHD Graphics 630, 65W) Box</p> <p>"MB Gigabyte B365M HD3 1.0 mATX Chipset Intel® B365 Memory 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory Dual channel memory architecture Support for DDR4 2666/2400/2133 MHz memory modules Onboard Graphics Integrated Graphics Processor- Intel® HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x DVI-D port, supporting a</p>




						<p>maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz Maximum shared memory of 1 GB</p> <p>Audio Realtek® ALC887 codec High Definition Audio 2/4/5.1/7.1-channel LAN Realtek® GbE LAN chip (10/100/1000 Mbit) Expansion Slots 1 x PCI Express x16 slot, running at x16 1 x PCI Express x16 slot, running at x4 2 x PCI Express x1 slots</p> <p>Multi-Graphics Technology Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™ technologies</p> <p>Storage Interface - Chipset: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) 6 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, RAID 5, and RAID 10</p> <p>USB - Chipset: 6 x USB 3.1 Gen 1 ports (4 ports on the back panel, 2 ports</p>
--	--	--	--	--	--	--



					<p>available through the internal USB header) 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)</p> <p>https://www.gigabyte.com/Motherboard/B365M-HD3-rev-10#kf .4GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V 2.5" SATA SSD 256GB Apacer "AS350" Panther [R/W:560/540MB/s, 85/86K IOPS, S11, BiCS], Retail "Case ATX 500W Sohoo 2810BG, 2xUSB2.0, Black, ATX-500W-12cm</p> <p>MB Support: ATX/Micro ATX/Mini-ITX Driver bays: 1 x 5.25" External + 5 x 3.5" (4 Internal + 1 External) Cooling System: Rear: 1x 80/90mm fan (optional) Case size: (W x H x D): 175mm x 405mm x 330mm</p> <p>PSU ATX 500W: 12cm fan, 2xSATA, 2xMolex, 1.2m power cord" "21.5" AOC "e2270Swhn", Black (1920x1080, 5ms, 200cd, LED20M:1, D-Sub + HDMI) (21.5" TN : LED, 1920x1080 Full-HD, 0.248mm, 5 ms, 200 cd/m², DCR 20 Mln:1 (600:1),</p>
--	--	--	--	--	---



						<p>90°/65° @C/R>10, Analog D-Sub, HDMI, Headphone out, Built-in PSU, Fixed Stand (Tilt -5/+15°), VESA Mount 100x100, Black)"</p> <p>"Keyboard & Mouse SVEN KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB</p> <p>"Speakers SVEN ""325"" Black, 6w, Power: USB / DC 5V</p> <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>
30200000-1	<p>Computer pentru activitatea operationala</p>	Navigator	RM	Ultra Service	<ul style="list-style-type: none"> • CPU Intel Core i3-9100F 3.6-4.2 GHz • MB CPU Supports 9th Gen Intel® Core™ Processors Chipset Intel® B365. Memory 2xDDR4 DIMM sockets supporting up to 32 GB of system memory. Support for DDR4 2666/2400/2133 MHz memory modules. 1xD-Sub port. 1xDVI-D port. 1xHDMI port. Audio Realtek® ALC887 codec. LAN Realtek® GbE LANchip (10/100/1000 Mbit). Storage Interface 1xM.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) • .8GBDDR4- 2666MHz • 2.5" SATA SSD- 512GB • Case ATX 500W • 21.5" • Keyboard & Mouse, USB <p>Speakers, 6w</p> <p>• Instalarea Sistemului de operare licențiat Windows 10 pro 64bit pentru 2 unități</p>	<p>CPU Intel Core i3-9100 3.6-4.2GHz (4C/4T, 6MB, S1151, 14nm, Integrated UHD Graphics 630, 65W) Box</p> <p>"MB Gigabyte B365M HD3 1.0 mATX Chipset Intel® B365</p> <p>Memory 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory</p> <p>Dual channel memory architecture</p> <p>Support for DDR4 2666/2400/2133 MHz memory modules</p> <p>Onboard Graphics</p> <p>Integrated Graphics Processor- Intel® HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz</p> <p>1 x DVI-D port, supporting a</p>




				<p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>	<p>maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz Maximum shared memory of 1 GB Audio Realtek® ALC887 codec High Definition Audio 2/4/5.1/7.1-channel LAN Realtek® GbE LAN chip (10/100/1000 Mbit) Expansion Slots 1 x PCI Express x16 slot, running at x16 1 x PCI Express x16 slot, running at x4 2 x PCI Express x1 slots Multi-Graphics Technology Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™ technologies Storage Interface - Chipset: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) 6 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, RAID 5, and RAID 10 USB - Chipset: 6 x USB 3.1 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header) 6 x USB 2.0/1.1 ports (2 ports</p>
--	--	--	--	---	--



						<p>on the back panel, 4 ports available through the internal USB headers)</p> <p>"</p> <p>.8GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V 2.5" SATA SSD 512GB Apacer "AS350" Panther [R/W:560/540MB/s, 76/68K IOPS, S11, BiCS], Retail "Case ATX 500W Sohoo 2810BG, 2xUSB2.0, Black, ATX-500W-12cm</p> <p>.</p> <p>MB Support: ATX/Micro ATX/Mini-ITX Driver bays: 1 x 5.25"" External + 5 x 3.5"" (4 Internal + 1 External) Cooling System: Rear: 1x 80/90mm fan (optional) Case size: (W x H x D): 175mm x 405mm x 330mm</p> <p>PSU ATX 500W: 12cm fan, 2xSATA, 2xMolex, 1.2m power cord" "21.5"" AOC ""e2270Swhn"" , Black (1920x1080, 5ms, 200cd, LED20M:1, D-Sub + HDMI) (21.5"" TN : LED, 1920x1080 Full-HD, 0.248mm, 5 ms, 200 cd/m², DCR 20 Mln:1 (600:1), 90°/65° @C/R>10, Analog D-Sub, HDMI, Headphone out, Built-in PSU, Fixed Stand (Tilt -5/+15°), VESA Mount 100x100, Black)" "Keyboard & Mouse SVEN</p>
--	--	--	--	--	--	---



						<p>KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB</p> <p>"</p> <p>"Speakers SVEN ""325"" Black, 6w, Power: USB / DC 5V</p> <ul style="list-style-type: none"> • Instalarea Sistemului de operare licențiat Windows 10 pro 64bit pentru 2 unități <p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>
30200000-1	Computer pentru contabilitate	Navigator	RM	Ultra Service	<ul style="list-style-type: none"> • CPU Intel Core i5-9400 2.9-4.1 GHz • MB CPUSupports 9th Gen Intel® Core™ Processors Chipset Intel® B365. Memory 2xDDR4 DIMM sockets supporting up to 32 GB of system memory. Support for DDR4 2666/2400/2133 MHz memory modules. 1xD-Sub port. 1xDVI-D port. 1xHDMI port. Audio Realtek® ALC887 codec. LAN Realtek® GbE LANchip (10/100/1000 Mbit). Storage Interface 1xM.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) • 16GBDDR4- 2666MHz • .M.2 NVMe SSD 256GB • 3.5" HDD 1.0TB-SATA- 64MB • Case ATX 500W • 23.8" (IPS 1920x1080, 5ms, 250cd, LED20M:1(1000:1), D-Sub+HDMI+DP, Speakers) • Keyboard & Mouse, USB • Speakers, 6w • Instalarea Sistemului de operare licențiat Windows 10 pro 64bit 	<p>CPU Intel Core i5-9400 2.9-4.1GHz (6C/6T, 9MB, S1151, 14nm, Integrated UHD Graphics 630, 65W) Tray</p> <p>"AC Deepcool LGA115X ""THETA15 PWM"" (17.8-36dBA, 2000-2800RPM, 50.25CFM, 100mm, PWM, 95W6 290g.)</p> <p>·</p> <p>Overall Dimension : 97.5X97.5X46mm</p> <p>Fan Dimension : Φ100X25mm</p> <p>Net Weight : 290g</p> <p>Bearing Type : Hydro Bearing</p> <p>Rated Voltage : 12VDC</p> <p>Operating Voltage : 10.8~13.2VDC</p> <p>Started Voltage : 7VDC</p> <p>Rated Current : 0.19±10% A</p> <p>Power Input : 2.28W</p> <p>Fan Speed : 2800±150~2800±10%RPM</p> <p>Max. Air Flow : 50.25CFM</p> <p>Noise : 17.8~36.0dB(A)</p>



				<p>Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării</p>	<p>http://www.deepcool.com/product/cpucooler/2013-12/7_235.shtml" "MB Gigabyte B365M HD3 1.0 mATX Chipset Intel® B365 Memory 2 x DDR4 DIMM sockets supporting up to 32 GB of system memory Dual channel memory architecture Support for DDR4 2666/2400/2133 MHz memory modules Onboard Graphics Integrated Graphics Processor- Intel® HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz Maximum shared memory of 1 GB Audio Realtek® ALC887 codec High Definition Audio 2/4/5.1/7.1-channel LAN Realtek® GbE LAN chip (10/100/1000 Mbit) Expansion Slots 1 x PCI Express x16 slot, running at x16</p>
--	--	--	--	---	--



					<p>1 x PCI Express x16 slot, running at x4 2 x PCI Express x1 slots Multi-Graphics Technology Support for AMD Quad-GPU CrossFire™ and 2-Way AMD CrossFire™ technologies Storage Interface - Chipset: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) 6 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, RAID 5, and RAID 10 USB - Chipset: 6 x USB 3.1 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header) 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers) " 16GB DDR4- 2666MHz Apacer PC21300, CL19, 288pin DIMM 1.2V .M.2 NVMe SSD 256GB ADATA XPG SX6000 Lite [PCIe 3.0 x4, R/W:1800/900MB/s, 100/170K IOPS, 3DTLC] 3.5" HDD 1.0TB-SATA - 64MB Toshiba "Performance P300 (HDWD110UZSVA)" "Case ATX 500W Sohoo 2810BG, 2xUSB2.0, Black,</p>
--	--	--	--	--	---



						<p>ATX-500W-12cm</p> <p>MB Support: ATX/Micro ATX/Mini-ITX Driver bays: 1 x 5.25" External + 5 x 3.5" (4 Internal + 1 External) Cooling System: Rear: 1x 80/90mm fan (optional) Case size: (W x H x D): 175mm x 405mm x 330mm</p> <p>PSU ATX 500W: 12cm fan, 2xSATA, 2xMolex, 1.2m power cord" "23.8" Philips "243V7QJABF", Black (IPS 1920x1080, 5ms,250cd, LED200M:1, D-Sub+HDMI+DP, Speakers) (23.8" IPS W-LED, 1920x1080 Full-HD, 93 ppi, 5ms GTG, 250 cd/m², DCR 200 Mln:1 (1000:1), 16.7M Colors, 178°/178° @C/R>10, 30-83 kHz(H)/56-76 Hz(V), HDMI + DisplayPort 1.2 + Analog D-Sub, Speakers, Audio-In, Headphone-Out, Built-in Power supply, Fixed Stand (Tilt - 5/+20°), VESA Mount 100x100, LowBlue Mode, Flicker-free, EasyRead mode, Edge-to-edge narrow border display, Black Shipping content: Monitor with stand, D-Sub cable, Audio cable, Power cable, User Documentation)" "Keyboard & Mouse SVEN</p>
--	--	--	--	--	--	---



						KB-S330C, Fullsize layout, Splash proof, Fn key, Black, USB " "Speakers SVEN ""325"" Black, 6w, Power: USB / DC 5V - Windows 10 Pro 64Bit Russian 1pk DSP OEI DVD Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării
30200000-1	Dispozitiv multifuncțional (imprimantă /copiator/ scanner)	LaserJet Pro MFP M130fn	China	HP	Imprimantă multifuncțională: PC Fax Rezoluția Scanner 1200 x 1200 dpi Formatul A4 Mod tiparire Alb-negru Tehnologie Laser Dimensiuni min. 398 x 388 x 482 (mm) Interfata Ethernet (RJ-45), Wi-Fi 802.11n, USB 2.0 Putere 255 W. Rezoluție imprimare 1200 x 1200 dpi Copiator/ Scanner Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării	HP LaserJet Pro MFP M130fn Print/Copy/Scan, A4, up to 23ppm, 256MB, 2-line LCD, 1200dpi, up to 10000 pages/monthly, HP ePrint, Hi-Speed USB 2.0, Fast E Suport de mentenanță tehnică la locul de utilizare a tehnicii de calcul timp de 1 (unu) an din data livrării
Lotul nr. 2: Proiectoare						
30200000-1	Proiector pentru sala festivități	MX611	China	BenQ	Tehnologia de afișare – DLP. Rezoluția nativă - 1024x768. Luminositate min - 3700 lumini. Contrast - 13000:1. Zoom optic - 1.6 . Dimensiunea ecranului maximă - 7.62 m. Difuzor incorporat. Putere sunet - 10 W. Putere lampa 260 W. Viață lampa min 4500 ore. Intrări - 2x VGA,	"DLP XGA Projector 4000Lum, 20000:1 BenQ ""MX611"", White Projection System DLP DC3 DMD Chip Native Resolution 1024x768 pixels Brightness 4,000 ANSI Lumens Contrast Ratio 20000:1



				<p>HDMI, S-Video, composite, 2x 3.5 mm. Suport 3D. USB reader. Ieșiri - VGA, mini jack 3.5 mm. Interfețe rețea - USB (tip A), USB (tip mini-B), RJ45, RS-232. Nivel de zgomot - 35 dB.</p>	<p>Display Color 1.07 Billion Colors Aspect Ratio Native 4:3 (5 aspect ratio selectable)</p> <p>Lens Control Manual Zoom and Focus Throw Ratio 1.96~2.15 Projection Size 30"~300" Image Size Diagonal 300" Zoom Ratio 1.1x Keystone Adjustment Vertical: ± 30 degrees Projection Offset 110%±2.5%</p> <p>Interface Computer In (D-sub 15pin, Female) x1 Monitor out (D-sub 15pin, Female) x1 Composite Video(RCA) x1 S-Video HDMI-1 HDMI-2/MHL x1 Audio in(mini jack) x1 Audio out(mini jack) x1 USB TypeA(1.5A power) x1 USB Type min B(For Page up/down and FW upgrade) x1 RS232 In (D-sub 9pin, male) x1 IR Receiver(Front+Top) x2</p> <p>Built in Speaker 2W</p> <p>Resolution Support VGA(640 x 480) to WUXGA_RB(1920X1200) *RB=Reduced blanking Horizontal Frequency 15-102KHz</p>
--	--	--	--	--	--



						<p>Vertical Scan Rate 23-120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM</p> <p>Light Source Lamp Light Source Life 4000/10000/8000/15000 hours (Normal/Eco/SmartEco/Lamp save mode) Power Consumption Max 355W. Normal 320W. Eco 240W.</p> <p>Security Security Bar,Kensington lock</p> <p>Noise Level 34/29dBA Dimensions(W x H x D) 296x120x221 mm Weight 2.3 kg</p> <p>Accessories (Standard): Remote control (5J.JGV06.001); AAA Batteryx2; Power Cord (by region); VGA cable; Warranty Card (by region); QSG (4J.J3E01.001); User Manual CD (5B.J3E01.001)</p> <p>Accessories (Optional): Spare Lamp Kit (5J.JGR05.001); 3D Glasses (5J.J9H25.002); Wireless Dongle - QCast Mirror (5A.JH328.10X); Wireless Dongle - QCast (5J.JCK28.X01);"</p>
--	--	--	--	--	--	---



30200000-1	Proiector pentru clase	MX535	China	BenQ	<p>Tehnologia de afișare – DLP. Rezoluția nativă - 800x600. Luminozitate - 3300 lumeni. Contrast - 13000:1. Difuzor incorporat. Putere lampa - 2 W, 190 W. Viață lampa – min 4500 ore. Intrări - HDMI, 2x D-sub, compozat, S-Video, Mini Jack, IR Receiver. Suport 3D. Ieșiri - D-sub, Mini Jack. Interfețe rețea - USB (tip mini-B), RS232. Nivel de zgomot - 33 dB.</p>	<p>"DLP XGA Projector 3600Lum, 15000:1 BenQ ""MX535"" , White Projection System DLP Native Resolution XGA, 1024 x 768 Brightness* 3600 ANSI Lumen Contrast Ratio 15000:1</p> <p>Lens F=2.46-2.66, f=21.8-25.6 Aspect Ratio Native 4:3 (5 aspect ratio selectable) Throw Ratio 1.94-2.32 Zoom Ratio 1.2x Projection Offset Vertical: 106%±2.5% (Full image height) Projection Size 60""~300""</p> <p>Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200)*RB = Reduced blanking Horizontal Frequency 15K-102KHz Vertical Scan Rate 23-120Hz</p> <p>HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM</p> <p>DMD Chip DC3 Power Consumption 252W(Normal), 211W(Eco), Standby <0.5W Light Source UHP 203W Light Source Life 5000/10000/15000 hours</p> <p>Interface:</p>	
------------	------------------------	-------	-------	------	--	---	--



					<p>Computer in (D-sub 15pin) x2 *integrate with component HDMI x2 Monitor out x 1 Composite Video in (RCA) x 1 1 S-Video in x 1 Audio in (Mini Jack) x 1 Audio out (Mini Jack) x 1 Speaker 2W x 1 USB (Type mini B) x 1 RS232 (DB-9pin) x 1 IR Receiver x1 (Front)</p> <p>3D Compatibility: Frame Sequential: Up to 60Hz 720p Frame Packing: Up to 24 Hz 1080p Side by Side: Up to 24Hz 1080p Top Bottom: Up to 60Hz 1080p</p> <p>Noise Level 32/29 dBA (Normal/Economic mode) Power Supply AC100 to 240V, 50 to 60 Hz Security Security bar / Kensington Security Slot Dimensions(W x H x D) 332.4 x 99 x 214.3 mm Weight 5.24 lbs (2.38 Kg)</p> <p>Accessories (Standard): Remote Control w Battery (5J.JG706.001), Warranty Card (by region), Power Cord (by region), VGA cable, QSG</p>
--	--	--	--	--	---



						(4J.JG701.001) Accessories (Optional): Spare Lamp Kit (5J.JG705.001)"	
Lotul nr. 3: Ecran de proiectie							
30200000-1	Ecran de proiectie manual	CMPC12	China	CHARM OUN	Ecran de proiectie cu actionare manuala. Dimeniune: 236x175cm. Format 4:3. Prinderea se face de perete sau de tavan. Carcasa metalica. Suprafata alba mata antireflex.	Manual 240x180cm CHARMOUNT CMPC120, 120", Ratio 4:3, Black Border	

Semnat:
Ofertantul Sofi Poliart SRL



Numele, Prenumele: Langa Adrian În calitate de: Administrator
Adresa: str. Renasterii 7, or.Ungheni