## ThinkVision P27h-20 Monitor

## **Specifications**

## **DISPLAY**

**Panel Size** 27-inch

**Screen Dimensions** 

596.74 mm x 335.66 mm

Panel Type

4-side NearEdgeless In-Plane Switching

**Backlight** 

**WLED** 

**Aspect Ratio** 

16:9

Resolution

2560 x 1440

**Pixel Pitch** 

0.2331 x 0.2331 mm

Dot/Pixel Per Inch (DPI/PPI)

Viewing Angle (H x V @ CR 10:1)

178° / 178°

**Response Time** 

4ms (extreme mode) 6ms (normal mode)

Refresh Rate

60 Hz

**Brightness (typical)** 

350 cd/m<sup>2</sup>

**Contrast Ratio (typical)** 

**Dynamic Contrast Ratio (typical)** 

3M:1

**Color Gamut** 

99% sRGB, 99% BT.709,

85% DCI-P3

**Color Support (typical)** 

16.7 Million

**Processor LUT** 8-bit

Anti-glare

Yes

## CONNECTIVITY

Video Signal

1 x USB Type-C Gen1 (DP1.2 Alt Mode) 1 x HDMI 1.4

1x DP 12

1 x DP 1.2 (Out)

**Audio Signal** 

1x Audio Out (3.5 mm)

**USB Hub** 

Yes

**Ethernet** 

Yes (10M/100M/1000M)

**USB** Upstream

1 x USB 3.1 Gen1 (by USB Type-C Gen1)

**USB** Downstream

4 x USB 3.1 Gen1 (1 x BC1.2)

**MULTI-MEDIA** 

**Integrated Speakers** 

Yes (2 x 1W)

**Optional Soundbar Support** 

Yes (PN 0A36190)

**SPECIAL FEATURES** 

**Factory Calibration** 

Yes (Avg. Delta E<2)

**POWER** 

Power Consumption (typ./max.)

27W / 150W

Power Consumption Sleep/Off Mode

< 0.5W

**Power Consumption Switch-off Mode** 

< 0.3W

**ENERGY STAR Power Consumption** 

19W / 61kWh

**Power Supply** 

Internal

**USB Type-C Power Delivery (W)** 

up to 90 W\*

**Smart Power\*\*** 

Yes

**Voltage Required** 

AC 100 to 240 V (50-60 Hz)

**MECHANICAL** 

Tilt Angle (front/back)

-5° / 35°

Swivel Angle (left/right)

+45°/ -45°

Lift (max range)

135 mm

Pivot

-90° / 90°

**VESA Mount Capability** 

Yes (100 x 100 mm)

**Kensington Lock Slot** 

Cable Management

**Bezel Color** 

Raven Black

Bezel Width (side)

2.0 mm

Bezel Width (top/bottom)

2.0 / 2.0 mm

**DIMENSION** 

Size Packed (D x H x W, mm/inch)

182 x 463 x 722 mm 7.17 x 18.23 x 28.43 inches Size Unpacked w/ Stand (D x H x W, mm/inch) (lowest position)

208 x 441.5 x 613.8 mm 8.19 x 17.38 x 27.17 inches

Size Unpacked w/ Stand

(D x H x W, mm/inch) (highest position)

208 x 576.5 x 613.8 mm 8.19 x 22.70 x 27.17 inches

Size Unpacked w/o Stand (head only) (D x H x W, mm/inch)

46.9 x 353.8 x 613.8 mm 1.85 x 13.92 x 27.17 inches

Min. Distance from Table to Panel (lowest pixel at bottom of screen, mm)

Max. Distance from Table to Panel (highest pixel at top of screen, mm)

Weight Packed (kg/lbs.)

9.55 kg / 21.01 lbs.

Weight Unpacked (kg/lbs.)

7.35 kg / 16.17 lbs.

Weight (monitor head only) (kg/lbs.)

4.87 kg / 10.71 lbs.

Full Container Load (40' STD / 20' STD)

792 / 352 units

WHAT'S IN THE BOX

Monitor with stand

1 x Power cable (1.8 m) 1 x DP cable (1.8 m) (NA only)

1 x USB Type-C to Type-C cable (1.8 m)

1 x USB Type-C to Type-A cable (1.8 m) (NA only)

Factory calibration report Quick setup guide

CERTIFICATION

**ENERGY STAR Rating** 

CCC Yes

TCO

8.0

TCO Edge

2.0

**EPEAT** Silver

RoHS (EU 2002/95/EC)

Yes

**Windows Certification** 

Windows 7, Windows 10

**TÜV Rheinland Eye Comfort** 

China Energy Efficiency Standard













<sup>\*</sup>Listed as maximum capacity of power delivery. Actual capacity may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting

<sup>\*\*</sup>The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device. Get up to 90 W\* of power delivery through the USB Type-C cable with the Smart Power function.