

Certificate of Compliance



No. 0P171016.JBBTQ23

Technical Construction File no. TJS201710132133

Certificate's
Holder:

Jinan Biobase Biotech Co., Ltd.
Room 501, Tianqiao District Technology Center,
No. 6 Lanxiang Middle Road, Tianqiao District, Jinan

Certification ECM
Mark:



Product:
Model(s):

Centrifuge
(see the following annex I)

Verification to:

Standard:
EN 61326-1:2013, EN 61000-6-1:2007,
EN 61000-6-3:2007+A1:2011+AC:2012,
EN 61010-1:2010,
EN 60204-1:2006+A1:2009+AC:2010

related to CE Directive(s):
2014/35/EU (Low Voltage)
2014/30/EU (Electromagnetic Compatibility)

Remark: The product(s) has been verified on a voluntary basis. The product(s) satisfies the requirements of the Certification Mark of ECM, in reference to the above listed Standard(s). The above Compliance Mark can be affixed on the product(s) accordingly to the ECM regulation about its release and its use. The regulation can be found at www.entecerma.it. This Certificate of Compliance can be checked for validity at www.entecerma.it

This verification doesn't imply assessment of the production of the product(s).

Additional information, clarification about the **CE** Marking:



We attest that a TCF for the **CE** Marking process is in place. Whereas the Manufacturer is Responsible to start the **CE Marking Certification Procedure** and to perform all the necessary activities, as required by the Directive before placing the **CE** Mark on the product(s).

Date of issue 16 October 2017

Expiry date 15 October 2022

Chief Manager
Marco Morino

Deputy Manager
Amanda Payne

Ente Certificazione Macchine Srl

Via Ca' Bella, 243 – Loc. Castello di Serravalle – 40053 Valsamoggia (BO) - ITALY
 ☎ +39 051 6705141 📠 +39 051 6705156 ✉ info@entecerma.it 🌐 www.entecerma.it

Annex I













No. 0P171016.JBBTQ23

Technical Construction File no. TJS201710132133

Model(s): Mini-4K, Mini-6K, Mini-7K, Mini-10K, Mini-10K+, Mini-15K, Mini-4610K, Mini-4610KII, Mini-4KH, Mini-6KH, Mini-10KH, LC-HD, LC-4KII, LC-H4KII, LC-4KA, LC-4K-2, LC-5K, LC-4KB, LC-4KC, LC-T4K, LC-H4K, BKC-TL4, BKC-TL4II, BKC-TL4III, BKC-TL4IV, BKC-TL5VII, BKC-TL5III, BKC-TL5IV, BKC-TL5, BKC-TL5II, BKC-TL6, BKC-TL6II, BKC-TL4V, BKC-TL5VI, BKC-TL5V, BKC-TL6III, BKC-TL6IV, BKC-TL6V, BKC-TL5L, BKC-TL5LII, BKC-TL5RIV, BKC-TL6R, BKC-TL8R, BKC-VL5R, BKC-VL6R, BKC-VL8R, BKC-TL5R, BKC-TL5RII, BKC-TL5RIII, BKC-TL5RL, BKC-VL6RLII, BKC-VL6RL, BKC-VL7RL, BKC-VL8RL, BKC-MH16, BKC-TH16, BKC-TH18, BKC-TH16II, BKC-TH18II, BKC-TH21, BKC-TH18R, BKC-TH18RII, BKC-TH23R, BKC-TH16R, BKC-TH20R, BKC-TH16RII, BKC-TH20RII, BKC-TH12R, BKC-TH16RIII, BKC-TH20RIII, BKC-TH24RII, BKC-VH20R, BKC-VH21RII, BKC-TH23RII, BKC-TH24R, BKC-TH24RL, BKC-VH20RII, BKC-VH21RL, BKC-VH10RL, BKC-TH20RL, BKC-TH21RL, BKC-GC12, BKC-GC24, BKC-PCR16, BKC-PRP5, BKC-MF5A, BKC-MF5B, BKC-MF5C, BKC-AU4, BKC-AU5, BKC-AU5R, BKC-BB6, BKC-BB6A, BKC-BB7, BKC-HC12A, BKC-TB12, BKC-TB4K, BKC-OIL5VII

Low Speed Centrifuge(economical type)

Introduction	Picture	Technical Parameters
<p>Model: LC-HD Handle-centrifuge can use for chemical, biological laboratories and hospital laboratories.</p>		<p>Capacity: 4*15ml Packing size: 550*400*320mm/16 pcs Gross weight: 20kg</p>
<p>Model: LC-4KII It can be used for qualitative analysis and in biochemistry labs.</p>		<p>Max. speed: 4000rpm, step adjusted speed Capacity: 20ml*6 Max. RCF: 1790xg Timing: 0~30min Power supply: AC110/220V, 50Hz Packing size: 280*280*290mm Gross weight: 4kg</p>
<p>Model: LC-H4KII It can be used in hospital, biochemistry lab, making determination and analyzing to blood serum and blood plasma immunity.</p>		<p>Speed range: starting~4000rpm Capacity: 18*5ml Timing range: 0~30min Max. RCF: 2325xg Mechanical lock Power supply: AC220V, 50Hz Packing size: 350*360*340mm Gross weight: 10kg</p>
<p>Model: LC-4KA It can be used in hospitals and biochemical labs for qualitative analysis of serum, urea and plasma. Frame material: high strength plastic with door switch</p>		<p>Max. speed: 4000r/min Capacity: 8*15ml Max. RCF: 2325xg Timing range: 0~30min With mechanical lock Power supply: AC220V, 50Hz Packing size: 350*360*340mm Gross weight: 10kg</p>
<p>Model: LC-4K-2 It can be used to make qualitative analysis and biochemistry labs widely.</p>		<p>Max. speed: 4000rpm, step adjusted speed Capacity: 12*20ml Max. RCF: 2325xg Time range: 0~30min With safety switch Power supply: AC220V, 50Hz Packing size: 380*330*310mm Gross weight: 9kg</p>

Introduction	Picture	Technical Parameters
<p>Model: LC-5K It has steady performance. It has the characteristics of large capacity, low noise, low temperature rise, beautiful appearance. It covers a wide range of application in scientific research institute of biology, chemistry, medicine, pharmacy, food and environment protection. This model also is good to separate plasma or other suspension liquid.</p>		<p>Max. speed: 5000rpm Max. RCF: 3600xg Capacity: 12*20ml Time range: 0~30min Power supply: AC220V, 50Hz Packing size: 350*360*340mm Gross weight: 10kg</p>
<p>Model: LC-4KB Application: hospitals and biochemical labs for qualitative analysis of serum, urea and plasma. Frame material: high strength plastic. Door switch</p>		<p>Max. speed: 4000rpm Max. RCF: 2325xg Capacity: 12*20ml Time range: 0~30min Power supply: AC220V, 50Hz Packing size: 350*360*340mm Gross weight: 10kg</p>
<p>Model: LC-4KC Application: scientific research institute of biology, chemistry, medicine, pharmacy, food and environment protection. This model also is good to separate plasma or other suspension liquid. Steady performance; Microprocessor control; Driven by brushless motor and easy to operate; With mechanical lock.</p>		<p>Max. Speed: 4000rpm Max. RCF: 2325xg Angle rotor capacity : 20ml*12 Time range: 0~99min Power supply: AC220V, 50Hz Packing size: 350*360*340mm Gross weight: 10kg</p>
<p>Model: LC-T4K Application: hospital, bio-chemistry lab, making determination and analyzing to blood serum and so on. With safety switch</p>		<p>Speed range: starting~4000rpm Capacity: 8*20ml Timing range: 0~30min Max. RCF: 2325xg Power supply: AC220V, 50Hz Packing size: 380*330*310mm Gross weight: 9kg</p>
<p>Model: LC-H4K Application: hospital, bio-chemistry lab, making determination and analyzing to blood serum and so on. With mechanical lock</p>		<p>Speed range: starting~4000rpm Capacity: 12*10ml Clocking range: 0~30min Centrifugal force: 2325*g Power supply: AC220V, 50Hz Packing size: 350*360*340mm Gross weight: 10kg</p>