

Numărul licitației:	ocds-b3wdp1-MD-1592467750169	29 iun 2020, 10:00 - 13 iul 2020, 10:00	Alternativa nr.:
Denumirea licitației:	Echipament și accesorii pentru computer	Lot: 3;4;	Pagina: 1 din 1

Cod CPV	Denumirea bunurilor și/sau a serviciilor	Mod el artic.	Tara de origine	Prod u-cător ul	Specific teh soluc.	Specificarea tehnică propusă	Stand arde
1	2	3	4	5	6	7	8
Lot 3 Imprimante multifuncionale Laser A4							
1	Imprimante multifuncionale Laser A4 Xerox B215 (cartus inclus) +2 cartuse originale pentru 3mii fiecare.	XEROX	Olanda	Xerox	Printer/Copier/Scanner/Fax, Alimentator automat de documente (35-sheet), Ecran tactil LCD alb-negru cu 6 linii, Memorie 256Mb, 1200x1200dpi, 23 ppm, 60-163r/m2, Scan 9600x9600 dpi-24 bit, 250sheet tray, Timp de imprimare a primei pagini in 6 sec sau mai puțin, Reducere/mărire 25-400% în trepte de 1%, USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g/n, Wireless Direct Connection ,USB 2.0, Cartridge 737 sau analog (2400 pages*), Cablu USB +2 cartus original de rezerva Garantie min 24 luni	XEROX B215 + 2 cartuse additional originale a cate 3000 imprimari/bucata. Tip: Multifunctionala Laser BW A4 (copiator/imprimanta/scanner/fax/Wi-Fi) Viteza (A4): 30 ppm A4 Volum lunar: 30.000 copii Memorie: 256 MB RAM Procesor: 600 MHz Duplex Automat: Da Alimentator automat de documente (45-sheet) Specificații Copiere Rezoluție copiere: minim 1200 x 1200 dpi Duplex Automat: Da (1-2,2-2,2-1) Mărire/Micșorare: 25%-400% cu pasul de 1 % Specificații Imprimare Rezoluție imprimare: minim 600x600 dpi pina la 4800x600 Conectivitate: 10/100/1000Base-T Ethernet, USB, Wi-Fi Limbaje de imprimare: Emulări PCL® 5e și 6, emulare PostScript® 3 Sisteme Operaționale: Microsoft® Windows® XP SP3, Server 2003, Server 2008, Vista, 7 (32- and 64-bit), Mac OS® 10.5 and above; Protocoloale Rețea: TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, IPv6; Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway), TCP/IP; AppleTalk®: EtherTalk®; Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled); WSD, IPP; SMB (Windows network) Specificații Scanare Posibilități: Scanare color si a/n, imprimare, copiere, e-mail, fax Rezoluție scanare: 600x600 dpi imbunatatit 9600x9600 dpi 24 bit; ADF 40 pagini; Scanare către: TWAIN/WIA, scanare către PC, scanare către WSD, scanare către e-mail; Formate Fișier: PDF/JPEG/TIFF Securizare și contorizare; Securitate: HTTPS securizat (SSL) IPsec, autentificare 802.1X, WPA2 Personal, filtrare IPv4 și IPv6, filtrare adrese MAC, SNMPv3. Termen Garanție: 36 luni	
Lot 4 Copiator A4							
	Copiator A4 Versalink B605X (cartus inclus) + 2 cartuse originale pentru 46700 mii imprimari fiecare. + 1 tava aditionala pentru 550 coli + 1 tava de capacitate mare pentru 2200 coli.				A4 monochrome laser All-in-One printer - Print, Copy, Scan, Send Automatic Double sided printing Double side Print speed min. 48ppm (A4) , Print resolution 1200 dpi x 1200 dpi, Direct printing JPEG, TIFF, PDF available from USB memory, and Web Access Paper input min. 1100 shets (80 gsm) + min. 100-sheet(80 gsm) multi purpose tray. Optional expand paper feed to a minimum of 2200 pages.Paper output min. 250 sheets (80 gsm) Supported Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper.Page Description Language - PCL5e/6, Adobe Postscript Level 3Copy Reduction/Enlargement - Zoom: 25-400 % in 1 % increments Fixed Zoom Ratio: 25 %, 50 %, 70 %, 100 %, 141 %, 200 %, 400 % FCOT max. 6 seconds Scan resolution - from 100 dpi to 600 dpi	VersaLink B605X (cartus inclus) + 2 cartuse originale pentru 46700 imprimari/fiecare. + inca o tava aditionala pentru 550 coli + tava de cap. Mare pentru inca 2200 coli. 55ppm A4, double side 52.2 ppm (4 in 1), 7" Touch Screen UI, Single pass DADF, USB/Ethernet, 1.05GHz Dual Core, 2GB, 550 sheet tray, 150 sheet bypass tray, 320GB Hard Disk Drive One-sided Speed 8.5 x 11": Up to 58 ppm black-and-white A4 (210 x 297mm): Up to 55.5 ppm black-and-white 8.5 x 14" (216 x 356mm): Up to 48.5 ppm black-and-whiteTwo-sided Speed8.5 x 11": Up to 52.2 ppm black-and-whiteA4 (210 x 297mm): Up to 49.3 ppm black-and-white8.5 x 14" (216 x 356mm): Up to 27 ppm black-and-whiteMonthly Duty CycleUp to 250,000 pages / monthRecommended AverageUp to 20,000 pages (Monthly Print Volume)Hard Drive 320 GB HDDProcessor1.05 GHz ARM Dual CoreMemory 2 GB ConnectivityEthernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair Controller Features Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform, Xerox App Gallery, Xerox Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver) User Interface LanguagesEnglish, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian Total Paper CapacityTotal: 2,700 SheetsBypass Tray: 150 Sheets, Paper Handling Tray: 550 Sheets, High Capacity Feeder: 2,000 SheetsMaximum Paper Capacity: 3,250 Sheets Print First-print-out Time As fast as 7.5 seconds Print Resolution Up to 1200 x	

			<p>Automatic Double sided scanning - 2-sided to 2-sided TWAIN/WIA scanning available, Scan to USB Memory. Send destinations - E-Mail/Internet FAX (SMTP), PC (SMB, FTP, WebDAV) for TIFF, JPEG, PDF, XPS, PDF/XPS (compact), PDF/A-1b, Searchable PDF/XPS, Office Open XML (PowerPoint). Security min. IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, HDD Password Lock, Data Erase, Department ID, SSO-H, Access Management System. Optional supported Encryption, User and Device signatures, Secure Watermarks, Data Loss Prevention. Memory min. 1.5 GB, min. 150 GB Hard Disk Drive. Min. 6 inch WVGA Colour TFT LCD Tilttable Touch MFP should come with a floor stand and a supply of original consumables for printing at least 30,000 pages. Interface min. USB 2.0, 2 x USB Host, 1000BaseT Ethernet. No wireless. Operating System compatibility – Win XP, Win 7, Win 10, Win Server 2003/ 2008/ 2012 or later. Cassette Feeding Module-AA1 Pedestal . Garantie min 24 luni, +2 cartus original de rezerva</p>	<p>1200 dpi Page Description Languages PCL 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe PostScript 3 Maximum Print Area 4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper Print Features Application DefaultsBanner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to new paper size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit)N-up Page Layout (up to 16 pages per sheet) Print Features (Contd.) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox Earth Smart Driver Setting Print from USB Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A Operating Systems Windows 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS 10.11, 10.12, 10.13 Citrix Redhat Enterprise Linux Fedora Core IBM AIX HP-UX Oracle Solaris SUSE SAP Fonts PostScript fonts: 136 PCL fonts: 83 Xerox Mobile Express Driver Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. Xerox Global Print Driver A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and nonXerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. Xerox Pull Print Driver Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office, Ysoft SafeQ, Pharos and others.</p> <p>Copy Document Scanner 100-sheet Single-pass Duplex Automatic Document Feeder (DADF) Maximum Scan Area Platen: Up to 8.5 x 14" (215.9 x 355.6mm) DADF: Up to 8.5 x 14" (215.9 x 355.6mm) Simplex Copy Speed Up to 58 cpm (copies per minute) 8.5 x 11 in. black and white Duplex Copy Speed Up to 52.2 cpm 8.5 x 11 in. black and white First-copy-out Time As fast as 5.8 seconds Sides (input:output) 1:1, 1:2, 2:2 and 2:1 Quantity 1 to 999 Resolution (max.) Up to 600 x 600 dpi Reduction / Enlargement Variable zoom from 25% to 400% in 1% increments Concurrency Concurrent scanning and printing Copy Features Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping) Automatic Background Suppression Book Copying with Center Erase Booklet Copying Collation Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Lighten/Darken N-up Reduce / Enlarge 25% to 400% Image Shift Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness</p> <p>Scan CapabilityBlack and white and color scanning Concurrency Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Simplex Input Speed Black-and-white: Scan up to 58 ipm (images per minute): 8.5 x 11" (215.9 x 279.4mm)/ 55 ipm A4 Color: Scan up to 55 ipm: 8.5 x 11" (215.9 x 279.4mm) / 52 ipm A4 Duplex Input Speed Black-and-white: Scan up to 58 ipm (images per minute): 8.5 x 11" (215.9 x 279.4mm) / 55 ipm A4 Color: Scan up to 55 ipm: 8.5 x 11" (215.9 x 279.4mm) / 52 ipm A4 Resolution 600 x 600 dpi Bit Depth 24-bit color / 8-bit grayscale Maximum Scan Area Platen: Up to 8.5 x 14" (215.9 x 355.6mm) Document Feeder: Up to 8.5 x 14" (215.9 x 355.6mm) Network Filing Protocols FTP</p>
--	--	--	--	--

					<p>SMTP SMB File Formats JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A Scan Driver Compatibility (Network Only) WIA TWAIN Supported Scan Destinations Scan to Home Scan to USB Scan to Email Scan to Network (FTP or Browse SMB) Network Scanning - Software Solutions Xerox ConnectKey Apps Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless onnectKey Apps to the ConnectKey-enabled device. (Found at the Xerox App Gallery) Fax Fax Speed 33.6 Kbps Memory 4 MB Resolution Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi Compression MH/MR/MMR/JBIG Fax Features Walk-up Fax, LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts) Security Security Features Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering Security Features (Contd.) IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Paper Handling: Document Feeder ... Capacity Single-pass Duplex Automatic Document Feeder (DADF): 100 sheets Sizes Custom sizes: 5.5 x 5.5" to 8.5 x 14" (140 x 140mm to 216 x 356mm) Weights One-sided: 16 lb. bond to 32 lb. bond (60 to 128 gsm) Two-sided: 16 lb. bond to 32 lb. bond (60 to 128 gsm) Paper Handling: Bypass Tray Capacity 150 sheets Sizes Custom sizes: 3 x 5" to 8.5 x 14" (76 x 127mm to 216 x 356mm) Weights One-sided: 16 lb. to 80 lb. cover / 60 to 220 gsm Two-sided: 16 lb. to 65 lb. cover / 60 to 176 gsm Media Types Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Card Stock Card Stock Letterhead Custom 1 – 5 Paper Handling: Tray 1 ... Capacity 550 sheets Sizes Custom sizes: 3 x 7.5 in. to 8.5 x 14" (76.2 x 190 to 216 x 356mm) Weights One-sided: 16 lb. to 80 lb. cover / 60 to 220 gsm Two- sided: 16 lb. to 65 lb. cover / 60 to 176 gsm Media Types Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 – 5 High Capacity Feeder ... Capacity 2000 sheets Sizes Standard sizes: A4 SEF, Letter SEF Weights One-sided: 16 lb. to 65 lb. cover / 60 to 176 gsm Two-sided: 16 lb. to 65 lb. cover / 60 to 176 gsm Types Plain Paper Bond Punched Pre-Printed Recycled Lightweight Card Stock Letterhead Custom 1 – 5 Paper Output Tray ... Capacity 400 sheets with tray full sensor (without Finisher or Mailbox) Automatic Two-sided Printing Standard Paper Output Mailbox ... Capacity Four 100-sheet bins Device Management Network Protocols TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD, LDAP, Bonjour / AirPrint, FTP, Most protocols not in use can be disabled Administrative Protocols DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS Xerox CentreWare Web A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management Embedded Web Server Device Status Tray status/contents Consumables status Billing / Usage Quick Links Online Support Print Queue Viewing Job print queue management-view and delete Job Submission Print-ready files (PS, PCL, PDF, XPS, JPEG) Device Administration Allows simple, remote installation setting of configuration options and management of the device Browsers Microsoft</p>
--	--	--	--	--	---

					<p>Internet Explorer Microsoft Edge Mozilla Firefox Apple Safari Google Chrome</p> <p>Remote Services ... Xerox Meter Assistant Service Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Xerox Supplies Assistant Service Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.</p> <p>Maintenance Assistant Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. Device Specification ... Electrical Requirements Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 12 A Device Spec: Power Consumption Continuous Print 950 watts or less Ready (Standby) 79 watts or less Energy Saver (Sleep Mode) 1.1 watts or less Power Off Mode 220-240 VAC: 0.3 watts or less 110-127 VAC: 0.2 watts or less</p> <p>Device Spec: Operating Environment Required Temperature Range Storage: 32 Degree to 95 Degree F / 0 Degree to 35 Degree C Operating: 50 to 90 Degree F / 10 to 32 Degree C Required Relative Humidity 15% to 85% Sound Power Levels Running: 70 dB(a) or less Standby: 43 dB(a) or less Sound Pressure Levels Running: 58.3 dB(a) or less Standby: 29 dB(a) or less Boot Time (from Off to UI Ready) Less than 79 seconds Warm-up Time (from Sleep to UI Ready) Less than 47 seconds. Warranty 36 months</p>	
Total						

Semnat: _____ Numele, prenumele: **Bosovschi Dumitru** În calitate de: **Manager vinzari**

Ofertantul: **FPC "Aproservice-X" SRL** Adresa: **202, bd. Ștefan cel Mare, or. Chișinău**

*- Garanția constituie 36 luni.

*- Garanția este valabilă doar la procurarea consumabilelor și mentenanța de la partener local autorizat.

