Formularul Ofertei F4.1

Numărul licitației	ocds-b3wdp1-MD-1599727545454 din 10.09.2020 Denumirea Beneficiar: Academia de Studii Economice din Moldova	Data: " 26" noiembrie 2020	Alternativa nr.: Nu
Denumirea licitației	" Echipament și accesorii pentru computer"	Valabilitatea ofertei : 60 zile Termenul de livrare : 30 zile LOT nr. 8 : Foto-Video camere	Pagina: 1din

Lotul nr.8 Foto-Video camere (Se aplică cota 0 TVA, conform Hotărârii de Guvern)

COD CPV Denumirea bunurilor/ser viciilor		Modelul articolului	Țara de origine	Produ- cătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	- 4	5	6	7	8
3000000-9	Camera video	AG-UX90 4K Handheld Camcorder	Japan	Panasonic	Camera Unit Pickup Devices 1.0-type MOS solid state image sensor Effective Pixels 17.78 megapixel: FHD 59.94p/29.97p/23.98p 8.59 megapixel: UHD 29.97p/23.98p LENS Optical image stabilizer lens, optical 15x motorized zoom F2.8 to F4.5 (f=8.8 mm to 132 mm) 35 mm equivalent:f=24.5 mm to 367.5 mm; FHD 59.94p/29.97p/23.98p f=35.4 mm to 531.0 mm: UHD 29.97p /23.98p; Filter Diameter: 67 mm ND Filter: 4 Positions (OFF, 1/4, 1/16, 1/64); Shortest Shooting Distance (M.O.D.);:Approx. 1.0 m from the front lens; Gain setting L/M/H selector switch (toggle switch) Standard mode: 0 dB to 30 dB (Adjustable in 1 dB steps) (Automatic setting can be assigned to L/M/H); Extended ON: -3 dB to 30 dB (Adjustable in 1 dB steps) (Automatic setting can be assigned to L/M/H); 33 dB and 36 dB switched (when assigning [S.GAIN] to the USER button); Color Temperature Setting ATW, ATW LOCK, Ach, Bch, preset 3200 K/preset 5600 K/VAR (2000 K to 15000 K) Shutter Speed 60i/60p mode: 1/60 sec., 1/100 sec., 1/120 sec.; Minimum Subject Illumination 1.3 lx; (F2.8, Super Gain 36dB, Manual slow shutter 1/30s) DIGITAL ZOOM 2x/5x/10x,i.Zoom: max. 25x (optical zoom + digital zoom); Lens Hood	Image Sensor: 1-Chip 1" MOS Sensor Tip sensor: MOS 1.0 inch Effective Pixels: UHD: 8.59 MP FHD: 17.78 MP Zoom: Leica Dicomar 15x optical zoom Diafragma F2.8 - F4.5 (f=8.8 mm - 132 mm) 35mm echivalent: 35.4 - 531 mm (UHD) 24.5 mm - 367.5 mm (FHD) Filtre ND: Off; 1/4; 1/8; 1/16 Distanta minima focus (M.O.D.): 1 metru in fata lentilei Diametru filtru: 67 mm Senzitivitate in low light 1.3 lux (F2.8, Super Gain 36 dB, [1/30] manual slow shutter) Sensor Resolution: 3840 x 2160 (8.59 MP) Effective Sensor Resolution: 3840 x 2160 (8.59 MP) Gain: 0 to 30 dB (Native) Minimum Illumination: 1.3 Lux at 1/30 Shutter Speed White Balance Range: 2000 to 15,000K Focal Length: 8.8 to 132mm 35mm Equivalent Focal Length: 24.5 to 367.5mm Optical Zoom Ratio: 15x Max Digital Zoom: 10x Maximum Aperture: f/2.8 Minimum Aperture: f/2.8 Minimum Aperture: f/4.5 Filter Size: 67 mm Control Rings: Focus Zoom: Iris Image Stabilization: Optical Focus Control: Autofocus	Cetificat de comformitate

Hood with lens cover; Memory Card Recorder; Recording Media*1 SDHC memory card (4 GB to 32 GB); SDXC memory card (48 GB to 128 GB); UHS-I supported; Recording slot Slot x 2System format59.94 Hz; Recording Format MOV, MP4, AVCHD Recording Mode Please see page 1 for the Recording Format table; Video Signal for External Output 8 bit 4:2:2 Recording video signal 8 bit 4:2:0 Video Compression Format MPEG-4 AVC/H.264 High Profile (MOV/MP4/AVCHD); Digital Audio; Sampling Frequency 48 kHz/16 bit 2 ch Audio Signal Format **LPCM** (MOV/MP4), Dolby Digital (AVCHD) Headroom 12 dB; Video input/output VIDEO OUTPUT VIDEO OUT connector x 1; HDMI Type A connector x 1, VIERA Link not supported Built-in microphone Stereo microphone XLR Input XLR (3-pin) x 2 (INPUT1, INPUT2) high impedance, LINE/MIC/MIC+48V (switchable SW) LINE: +4 dBu/0 dBu (switchable menu) MIC: -40 dBu/-50 dBu/-60 dBu (switchable menu) AUDIO OUTPUT HDMI (Audio Output) 2 ch (LPCM) Camera Remote 2.5 mm diameter super mini jack x1 (ZOOM, S/S) 3.5 mm diameter mini jack x1 (FOCUS, IRIS) USB 3.0 (Host) Standard-A connector, 9-pin, external media device connection*2, bus power supported USB 3.0 (Device) Micro-B connector, 10-pin. LCD monitor 3.5-type LCD monitor, Approx. 1,150,000 dots View Finder 0.24-type EVF, Approx. 1,560,000 dots equivalent Included accessories Battery, Battery charger, AC adaptor, Microphone holder, Screw for microphone holder (12 mm), AC cable x 2, Eye cup, Lens hood, INPUT terminal cap, Operating instructions

Manual Focus Shutter Speed: 1/60 to 1/8000 sec Scan Rate Adjustable: Yes Built-In ND Filter: None Built-In Microphone Type: Stereo Recording Modes: MP4 4:2:0 8-Bit: 3840 x 2160p at 23.98/29.97 fps (100 Mb/s) 1920 x 1080p at 23.98/29.97/59.94 fps (50 to 200 Mb/s) AVCHD 4:2:0 8-Bit: 1920 x 1080p at 23.98/59.94 fps (21 to 25 Mb/s) 1920 x 1080i at 59.94 fps (17 to 21 Mb/s) 1440 x 1080i at 59.94 fps (5 Mb/s) 1280 x 720p at 59.94 fps (8 Mb/s) 720 x 480i at 59.94 fps (9 Mb/s) Variable Frame Rates 1080p: 2 to 60 fps 1080p: 2 to 60 fps Audio Recording MP4: 2-Channel 16-Bit 48 kHz LPCM Audio AVCHD: 2-Channel 16-Bit 48 kHz LPCM Audio Still Image Support JPEG: 8.3 MP (3840 x 2160) 2 MP (1920 x 1080); .9 MP (1280 x 720) IP Streaming: None Video Connectors: 1 x RCA (Composite) Output 1 x HDMI Output : Audio Connectors 2 x 3-Pin XLR Mic/Line Level (+48 V Phantom Power) Input 1 x 1/8" / 3.5 mm Stereo Headphone Output : Other I/O 1 x 2.5 mm Camera Interface Control Input 1 x 3.5 mm Camera Interface Control Input 1 x USB Type-A Camera Interface Data Output 1 x USB Micro-B Camera Interface Data Input/Output Display Type: Articulating LCD Size: 3.5" Resolution: 1,150,000 Dot EVF Display Type: OLED Screen Size: .24" EVF Resolution: 1,560,000 Dots Included accessories Battery, Battery charger, AC adaptor, Microphone holder,

	_						
22222000		,				Screw for microphone holder (12 mm), AC cable x 2, Eye cup, Lens hood, INPUT terminal cap, Operating instructions Garantie: 24 luni	
3000000-9	Camera foto DSLR 6D	EOS 6D MARK II Body + obiectiv Canon EF 24-70mm f/2.8L II USM	China	Canon	Camera foto DSLR 6D mark II Camera Body with Accessory Kit with 24-70mm f/2.8L II USM Lens for 6D mark II, 128 GB Extreme PRO UHS-I SDXC Memory Card	Camera foto DSLR 6D mark II Camera Body with Accessory Kit with 24-70mm f/2.8L II USM Lens for 6D mark II, SanDisk 128 GB Extreme PRO UHS-I SDXC Memory Card: Tip card: SDXC Capacitate: 128 Gb Tip Bus: UHS-I Clasa Viteza: 10 Clasa Viteza UHS: U3 Interfata Viteza Bus: UHS Class I Clasa Viteza Video: V30 Transfer de date Viteza de citire 170 MB/s Maximum Viteza de scriere 90 MB/s Maximum Viteza de scriere 30 MB/s Minimum	Cetificat de comformitate
30000000-9	Camera foto With 28-70 mm Lens-Black	Appha 7 II Full- Frame Mirrorless Camera with 28-70 mm Lens-Black	China	Sony	Camera foto Sony – Appha 7 a 7 II Full-Frame Mirrorless Camera With 28-70 mm Lens-Black	Garantie: 24 luni Appha 7 II Full-Frame Mirrorless Camera with 28-70 mm Lens-Black Lens Mount: Sony E Camera Format Full-Frame (1x Crop Factor) Pixels: Actual: 24.7 Megapixel Effective: 24.3 Megapixel Maximum Resolution: 6000 x 4000 Aspect Ratio: 3:2, 16:9 Sensor Type: CMOS Sensor Size: 35.8 x 23.9 mm Image File Format JPEG, Raw Bit Depth: 14-Bit Image Stabilization: Sensor-Shift, 5-Axis Recording Modes: XAVC S Full HD (1920 x 1080) at 24.00p/29.97p/59.94p [50 Mb/s] AVCHD Full HD (1920 x 1080) at 59.94p [28 Mb/s] Full HD (1920 x 1080) at 24.00p/59.94i [17 to 24 Mb/s] MP4 HDV (1440 x 1080) at 29.97p [12 Mb/s] SD (640 x 480) at 29.97p [3 Mb/s] External Recording Modes Full HD (1920 x 1080)	Cetificat de comformitate

			Audio Recording "Built-In Microphone (Stereo)	
			External Microphone Input: Audio File	
			Format	
			AAC LC, Dolby Digital 2ch, Linear PCM	
			(Stereo)	
18		emakan s	Media/Memory Card Slot: Single Slot:	
		1,111	SD/SDHC/SDXC/Memory Stick Duo	
			Hybrid (UHS-I)	
			Internal Memory : None	
			Connectivity: 3.5mm Headphone, 3.5mm	
			Microphone, HDMI D (Micro), Multi-	
			Terminal Interface, USB Micro-B (USB 2.0)	
			Wireless: Wi-Fi	
			Battery: 1 x NP-FW50 Rechargeable	
			Lithium-Ion, 1020 VDC	
			Dimensions (W x H x D) : 5 x 3.8 x 2.4"/	
			126.9 x 95.7 x 59.7 mm	
		3	Weight: 1.22 lb / 556 g	
	-		28-70mm Lens :	
			Focal Length: 28 to 70mm	
			Maximum Aperture: f/3.5 to 5.6	
			Minimum Aperture : f/22 to 36	
94.31 F			Angle of View: 75° to 34°	
			Maximum Magnification: 0.19x	
			Minimum Focus Distance: 11.81" / 0.3 m	
	~		Optical Design: 9 Elements in 8 Groups	
			Diaphragm Blades: 7, Rounded	
			Focus Type : Autofocus	
			Image Stabilization : Yes	
			Filter Size: 55 mm (Front)	
AA 11			Garantie : 12 luni	

Semnat:

Numele, Prenumele: Cîrlig Ion În calitate de: Director

Ofertantul: "WEST BUY SRL ". Adresa: MD-2075, bld. Mircea cel Bătrîn 39 ap/143, or.Chișinău, RM.

Specificații de preț (F4.2)

	eds-b3wdp1-MD-1599727545454 din 10.09.2020 enumirea Beneficiar: Academia de Studii Economice din Moldova	Data: "26 " noiembrie 2020	Alternativa nr.: Nu
	Echipament și accesorii pentru computer"	LOT nr. 8 : Foto-Video camere	Pagina: 1din
tației		LOT III.	5. Poto-video camere

Lotul 8. Foto-Video camere (Se aplică cota 0 TVA, conform Hotărârii de Guvern)

Nr	Cod CPV	Denumirea bunurilor și/sau a serviciilor	Unit. de măs.	Canti- tatea	Preț unitar fără TVA	Pret unitar cu TVA	Suma fără TVA	Suma cu TVA	Termenul de livrare/ prestare
	1	2	3	4	5	6	7	8	9
1	30000000-9	Camera video	Buc.	2	30440,00		60880,00		30 de zile
2	30000000-9	Camera foto DSLR 6D	Buc.	1	58200,00	_	58200,00	-	
3	30000000-9	Camera foto With 28-70 mm Lens-Black	Buc.	2	21400,00		42800,00	-	30 de zile 30 de zile
		Total lotul 8			Е =		161880,00		

Semnat:

Numele, Prenumele: Cîrlig Ion În calitate de: Director

Ofertantuk, WEST BUY SRL ". Adresa: MD-2075, bld. Mircea cel Bătrîn 39 ap/143, or.Chișinău, RM