

| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|----|-------------------|--|------|-------|--------|-------|
| | 8164 | | | | | |
| | 287315590 1261 | Electrod S 1125/2 E 51.5A1 1 dxl 5 x 450 mm | kg | 0,13 | 30,00 | 4,09 |
| | 232032260 0282 | Bitum pentru protectie conducte | kg | 0,07 | 14,00 | 1,03 |
| | 232032260 0374 | Citom | kg | 0,02 | 7,00 | 0,15 |
| | 211230732 4986 | Hirtie, sulfit tip I, ptr. izolare conducta 80-100 gr/mp-sul | kg | 0,02 | 5,00 | 0,10 |
| | 232015620 0951 | Motorina motor DIESEL-ld | kg | 0,14 | 15,00 | 2,21 |
| | 311050000 3004 | Convertizor de sudura de 14 kw | h-ut | 0,06 | 77,00 | 4,62 |
| | 295227000 3306 | Electropompa de apa 4-6 kw | h-ut | 0,001 | 6,00 | 0,01 |
| 14 | AcA04A | Montarea in pamint a conductelor din otel, asamblate prin sudura electrica, avind diametrul de 50- 100 mm | m | | | 83,08 |
| | 713605001 2000 | Instalator alimentari apa | h-om | 0,50 | 57,66 | 28,83 |
| | 252121670 1025 | Teava din otel D=25x2,5mm | m | 1,01 | 33,00 | 35,00 |
| | 241111590 4512 | Oxigen tehnic gazos S2031 | m3 | 0,09 | 19,00 | 1,80 |
| | 241354730 8164 | Carbura de calciu tehnica (carbide) S102 | kg | 0,20 | 25,00 | 5,25 |
| | 287315590 1261 | Electrod S 1125/2 E 51.5A1 1 dxl 5 x 450 mm | kg | 0,13 | 30,00 | 4,09 |
| | 232032260 0282 | Bitum pentru protectie conducte | kg | 0,07 | 14,00 | 1,03 |
| | 232032260 0374 | Citom | kg | 0,02 | 7,00 | 0,15 |
| | 211230732 4986 | Hirtie, sulfit tip I, ptr. izolare conducta 80-100 gr/mp-sul | kg | 0,02 | 5,00 | 0,10 |
| | 232015620 0951 | Motorina motor DIESEL-ld | kg | 0,14 | 15,00 | 2,21 |
| | 311050000 3004 | Convertizor de sudura de 14 kw | h-ut | 0,06 | 77,00 | 4,62 |
| | 295227000 3306 | Electropompa de apa 4-6 kw | h-ut | 0,001 | 6,00 | 0,01 |
| 15 | AcF11B | Spalarea conductelor din otel 2 1/2" -4", de apa potabila dupa montarea si imbinarea, inaintea receptiei | m | | | 16,72 |
| | 713605001 2000 | Instalator alimentari apa | h-om | 0,10 | 57,66 | 5,77 |
| | 410011620 2820 | Apa potabila | m3 | 0,15 | 9,00 | 1,35 |
| | 341054000 5603 | Autocisterna 5-8 t cu dispozitive de stropire | h-ut | 0,08 | 120,00 | 9,60 |
| 16 | IzA08A | Vopsitorii pe conducte, executate manual cu vopsea de ulei, avind | m | | | 5,69 |