

8.25R16LT



SP901



SP907



SP908



SP912



SP918

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
SP901	6.50H	16PR	128/124	K	13.0	1800/1600	770
SP907	6.50H	16PR	128/124	K	13.0	1800/1600	770
SP908	6.50H	16PR	128/124	K	16.5	1800/1600	770
SP912	6.50H	16PR	128/124	K	15.0	1800/1600	770
SP918	6.50H	16PR	128/124	L	15.0	1800/1600	770

37*12.5R16.5LT



SP339

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
SP339	8.25	10PR	134	N	14.1	2120	450

7.50R20



SP502

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
SP502	6.00	16PR	133/131	M	14.1	2060/1950	930

8.25R20



SPX501



SP901



SP908



SP912

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
SPX501	6.50	16PR	139/137	K	15.6	2430/2300	930
SP901	6.50	16PR	139/137	K	15.3	2430/2300	900
SP908	6.50	16PR	139/137	K	16.5	2430/2300	930
SP912	6.50H	16PR	139/137	K	16.5	2430/2300	930